

## Properties reference

---

This reference describes agent configuration properties.

When you create an agent profile, you choose whether to store the agent configuration in AM's configuration store or locally to the agent installation. The local configuration file syntax is the same as that of a standard Java properties file.

### Property aliases

A property alias specifies a path for a property. A property can have multiple aliases but each alias is unique to that property.

#### *How the agent manages multiple aliases*

When you assign multiple values to the same property through different aliases, the agent assigns the values as follows:

- For list properties, it appends each assignment to the list.
- For simple string properties, it overwrites the current value with each new value. The final value is the last value to be assigned.

The following example assigns different values to a string property with three aliases:

```
com.sun.identity.agents.app.username=one
com.sun.identity.agents.config.profilename=two
org.forgerock.agents.profile.name=three
```

The final value of the property is `three`, the last value to be assigned.

#### *How AM manages multiple aliases*

Each version of AM recognizes a different group of agent aliases. When you are using AM commands, such as `ssoadm` to configure an agent, consider the following points on using recognized and unrecognized aliases:

- When you use a recognized alias in an `ssoadm` command (for example, `com.sun.identity.agents.config.notenforced.ip.cache.size=2000`), the agent updates the value for the property represented by that alias.

For the above example, **Max Entries in Not-Enforced IP Cache** is displayed as 2000 in the **Application** tab of the AM console.

- When you use an unrecognized alias in an `ssoadm` command (for example, `org.forgerock.agents.notenforced.ip.cache.size=4000`), the agent creates a custom property.

For the above example, `org.forgerock.agents.notenforced.ip.cache.size=4000` is displayed in **Custom Properties**, in the **Advanced** tab of the AM console.

- When a property is set by both a standard property and a custom property, the custom property takes precedence. The value of the standard property is not updated, and both values are displayed in the configuration.

## List properties

List properties can be configured with or without an index location. The following formats are allowed and equivalent:

```
property[0]=one
property[1]=two
property[2]=three
```

```
property=one
property=two
property=three
```

When the agent assigns values to a list property, it adds to the list in the order the assignments are made, ignoring any index specified, and appending to the end of the list. The following formats are equivalent:

```
property[ ]=one
property[ ]=two
property[ ]=three
```

```
property[10]=one
property[1]=two
property[42]=three
```

The agent uses the index location only in the following cases:

- When the index location is set to `@` and the value is comma-separated:

The agent sets multiple properties according to the number of comma-separated values specified. In the following example, there are three comma-separated values:

```
property[@]=one, two, three
```

The agent sets three individual properties. The final assignment is as follows:

```
property[ ]=one  
property[ ]=two  
property[ ]=three
```

- When the value for an index location is empty:

The agent deletes that location in the list. In the following example, the last value for index location [1] is empty:

```
property[0]=one  
property[1]=two  
property[2]=three  
property[1]=
```

The agent deletes index location [1] from the list and then moves index location [2] to [1]. The final assignment is as follows:

```
property[0]=one  
property[1]=three
```

- When the index location is empty and the value is empty:

The agent deletes all values from the list; the list exists, but is empty. In the following example, the second value for index location [ ] is empty:

```
property[ ]=one  
property[ ]=  
property[ ]=two  
property[ ]=three
```

The agent does the following:

- Adds the text "one" to the list
- Deletes all values from the list
- Adds the text "two" into index location [0]
- Adds the text "three" into index location [1]

The final assignment is as follows:

```
property[0]=two  
property[1]=three
```

## List of bootstrap properties

Property	Description	Function
<a href="#"><u>org.forgerock.agents.filter.mode.map</u></a>	<a href="#"><u>Agent Filter Mode Map</u></a>	Agent
<a href="#"><u>org.forgerock.agents.profile.name</u></a>	<a href="#"><u>Agent Profile Name</u></a>	Profile, Required
<a href="#"><u>org.forgerock.agents.agent.profile.realm</u></a>	<a href="#"><u>Agent Profile Realm</u></a>	Profile, Required
<a href="#"><u>org.forgerock.agents.am.hostname</u></a>	<a href="#"><u>AM Authentication Service Host Name</u></a>	Authentication service, Required
<a href="#"><u>org.forgerock.agents.am.path</u></a>	<a href="#"><u>AM Authentication Service Path</u></a>	Authentication service, Required
<a href="#"><u>org.forgerock.agents.am.port</u></a>	<a href="#"><u>AM Authentication Service Port</u></a>	Authentication service, Required
<a href="#"><u>org.forgerock.agents.am.protocol</u></a>	<a href="#"><u>AM Authentication Service Protocol</u></a>	Authentication service, Required
<a href="#"><u>org.forgerock.agents.fallback.mode.enabled</u></a>	<a href="#"><u>Autonomous mode</u></a>	Agent, Required
<a href="#"><u>org.forgerock.agents.csv.monitoring.directory</u></a>	<a href="#"><u>CSV Monitoring Directory</u></a>	Monitoring
<a href="#"><u>org.forgerock.agents.lock.config.enabled</u></a>	<a href="#"><u>Enable Configuration Lock</u></a>	Profile
<a href="#"><u>org.forgerock.agents.http.client.reuse.connections.enabled</u></a>	<a href="#"><u>Enable HTTP Connection Reuse</u></a>	Connection pooling
<a href="#"><u>org.forgerock.agents.http.client.connection.state.enabled</u></a>	<a href="#"><u>Enable HTTP Connection State</u></a>	Connection pooling
<a href="#"><u>org.forgerock.agents.http.client.retry.requests.enabled</u></a>	<a href="#"><u>Enable HTTP Retry</u></a>	Connection pooling



Property	Description	Function
<a href="#"><u>org.forgerock.agents.policy.change.notifications.enabled</u></a>	<a href="#"><u>Enable Notification of Policy Changes</u></a>	Notifications
<a href="#"><u>org.forgerock.agents.config.change.notifications.enabled</u></a>	<a href="#"><u>Enable Notifications of Agent Configuration Change</u></a>	Notifications
<a href="#"><u>org.forgerock.agents.prometheus.monitoring.enabled</u></a>	<a href="#"><u>Enable Prometheus Monitoring</u></a>	Global
<a href="#"><u>org.forgerock.agents.encryptor.classname</u></a>	<a href="#"><u>Encrypting Java class</u></a>	Authentication service, Encryption, Required
<a href="#"><u>org.forgerock.agents.encryption.key.digest</u></a>	<a href="#"><u>Encryption Digest</u></a>	Authentication service, Encryption
<a href="#"><u>org.forgerock.agents.sso.exchange.cache.ttl.minutes</u></a>	<a href="#"><u>Exchanged SSO Token Cache TTL</u></a>	Profile
<a href="#"><u>org.forgerock.agents.sso.expired.session.cache.ttl.minutes</u></a>	<a href="#"><u>Expired Session Cache Timeout</u></a>	Session
<a href="#"><u>org.forgerock.agents.http.client.connection.timeout.seconds</u></a>	<a href="#"><u>HTTP Connection Timeout</u></a>	Connection pooling
<a href="#"><u>org.forgerock.agents.http.client.socket.timeout.seconds</u></a>	<a href="#"><u>HTTP Socket Timeout</u></a>	Connection pooling
<a href="#"><u>org.forgerock.agents.not.enforced.rule.pattern.matcher.classname</u></a>	<a href="#"><u>Java Class for Matching Not Enforced Rules</u></a>	Not-enforced
<a href="#"><u>org.forgerock.agents.jwt.cache.ttl.minutes</u></a>	<a href="#"><u>JWT Cache TTL</u></a>	Profile
<a href="#"><u>org.forgerock.agents.jwt.cookie.name</u></a>	<a href="#"><u>JWT Cookie Name</u></a>	Profile
<a href="#"><u>org.forgerock.agents.local.audit.file.path</u></a>	<a href="#"><u>Local Audit Log Filename</u></a>	Audit
<a href="#"><u>org.forgerock.agents.config.location</u></a>	<a href="#"><u>Location of Agent Configuration Repository</u></a>	Profile, Required

Property	Description	Function
<a href="#"><u>org.forgerock.agents.expired.session.cache.size</u></a>	<a href="#"><u>Max Entries in Expired Session Cache</u></a>	Session
<a href="#"><u>org.forgerock.agents.jwt.cache.size</u></a>	<a href="#"><u>Max Entries in JWT Cache</u></a>	Profile
<a href="#"><u>org.forgerock.agents.policy.cache.per.session.size</u></a>	<a href="#"><u>Max Entries in Policy Cache per Session</u></a>	Policy enforcement
<a href="#"><u>org.forgerock.agents.pdp.cache.size</u></a>	<a href="#"><u>Max Entries in POST Data Preservation Storage</u></a>	POST data preservation
<a href="#"><u>org.forgerock.agents.sso.exchange.cache.size</u></a>	<a href="#"><u>Max Entries in SSO Exchange Cache</u></a>	Profile
<a href="#"><u>org.forgerock.agents.http.client.max.connections</u></a>	<a href="#"><u>Max HTTP Connection Count</u></a>	Connection pooling
<a href="#"><u>org.forgerock.agents.policy.cache.session.size</u></a>	<a href="#"><u>Max Sessions in Policy Cache</u></a>	Policy enforcement
<a href="#"><u>org.forgerock.agents.auto.not.enforce.favicon</u></a>	<a href="#"><u>Not-Enforced Favicon</u></a>	Not-enforced
<a href="#"><u>org.forgerock.agents.policy.cache.ttl.minutes</u></a>	<a href="#"><u>Policy Cache TTL</u></a>	Policy enforcement
<a href="#"><u>org.forgerock.agents.pdp.cache.ttl.minutes</u></a>	<a href="#"><u>POST Data Preservation Cache TTL</u></a>	POST data preservation
<a href="#"><u>com.sun.identity.agents.config.postdata.reserve.cache.entry.ttl</u></a>	<a href="#"><u>POST Data Preservation Cache TTL in Milliseconds (deprecated)</u></a>	POST data preservation
<a href="#"><u>org.forgerock.agents.pdp.directory.sweep.seconds</u></a>	<a href="#"><u>POST Data Preservation Directory Sweep Interval</u></a>	POST data preservation

Property	Description	Function
<a href="#"><u>org.forgerock.agents.pdp.cache.total.size.mb</u></a>	<a href="#"><u>POST Data Preservation Storage Size</u></a>	POST data preservation
<a href="#"><u>org.forgerock.agents.public.am.url</u></a>	<a href="#"><u>Public AM URL</u></a>	Miscellaneous, Required
<a href="#"><u>org.forgerock.agents.service.resolver.class.name</u></a>	<a href="#"><u>Service Resolver Class Name</u></a>	Miscellaneous
<a href="#"><u>org.forgerock.agents.session.cache.ttl.minutes</u></a>	<a href="#"><u>Session Cache TTL</u></a>	Session
<a href="#"><u>org.forgerock.agents.strategy.when.am.unavailable</u></a>	<a href="#"><u>Strategy when AM unavailable</u></a>	Agent

## List of all properties

Property	Description (UI name)	Function
<a href="#"><u>org.forgerock.agents.access.denied.uri.map</u></a>	<a href="#"><u>Access Denied URI Map</u></a>	Access denied
<a href="#"><u>org.forgerock.agents.debug.level</u></a>	<a href="#"><u>Agent Debug Level</u></a>	Logs
<a href="#"><u>org.forgerock.agents.filter.mode.map</u></a>	<a href="#"><u>Agent Filter Mode Map</u></a>	Agent
<a href="#"><u>org.forgerock.agents.profile.name</u></a>	<a href="#"><u>Agent Profile Name</u></a>	Profile, Required
<a href="#"><u>org.forgerock.agents.agent.profile.realm</u></a>	<a href="#"><u>Agent Profile Realm</u></a>	Profile, Required
<a href="#"><u>org.forgerock.agents.agent.hostname</u></a>	<a href="#"><u>Alternative Agent Host Name</u></a>	Agent
<a href="#"><u>org.forgerock.agents.agent.port</u></a>	<a href="#"><u>Alternative Agent Port Number</u></a>	Agent
<a href="#"><u>org.forgerock.agents.agent.protocol</u></a>	<a href="#"><u>Alternative Agent Protocol</u></a>	Agent
<a href="#"><u>org.forgerock.agents.config.logout.session.invalidate.enabled</u></a>	<a href="#"><u>Always invalidate sessions</u></a>	Logout

Property	Description (UI name)	Function
<a href="#"><u>org.forgerock.agents.am.hostname</u></a>	<a href="#"><u>AM Authentication Service Host Name</u></a>	Authentication service, Required
<a href="#"><u>org.forgerock.agents.am.path</u></a>	<a href="#"><u>AM Authentication Service Path</u></a>	Authentication service, Required
<a href="#"><u>org.forgerock.agents.am.port</u></a>	<a href="#"><u>AM Authentication Service Port</u></a>	Authentication service, Required
<a href="#"><u>org.forgerock.agents.am.protocol</u></a>	<a href="#"><u>AM Authentication Service Protocol</u></a>	Authentication service, Required
<a href="#"><u>com.sun.identity.agents.config.login.url</u></a>	<a href="#"><u>AM Login URL List</u></a>	Custom login redirect, Default Login Redirect, Login redirect, Login Redirect (Default)
<a href="#"><u>org.forgerock.agents.audit.what</u></a>	<a href="#"><u>Audit Access Types</u></a>	Audit
<a href="#"><u>org.forgerock.agents.local.audit.log.retention.count</u></a>	<a href="#"><u>Audit Logfile Retention Count</u></a>	Audit
<a href="#"><u>org.forgerock.agents.audit.where</u></a>	<a href="#"><u>Audit Log Location</u></a>	Audit
<a href="#"><u>org.forgerock.agents.authn.exchange.cookie.name</u></a>	<a href="#"><u>Authentication Exchange Cookie Name</u></a>	Login
<a href="#"><u>org.forgerock.agents.authn.exchange.uri</u></a>	<a href="#"><u>Authentication Exchange URI</u></a>	Login
<a href="#"><u>org.forgerock.agents.authn.fail.reason.parameter.name</u></a>	<a href="#"><u>Authentication Fail Reason Parameter Name</u></a>	Authentication failure
<a href="#"><u>org.forgerock.agents.authn.fail.reason.remapper</u></a>	<a href="#"><u>Authentication Fail Reason Parameter Value Map</u></a>	Authentication failure
<a href="#"><u>org.forgerock.agents.authn.fail.url</u></a>	<a href="#"><u>Authentication Fail URL</u></a>	Authentication failure

Property	Description (UI name)	Function
<a href="#"><u>org.forgerock.agents.authn.redirect.uri</u></a>	<a href="#"><u>Authentication Redirect URI</u></a>	Cross-domain single sign-on, Required
<a href="#"><u>org.forgerock.agents.fallback.mode.enabled</u></a>	<a href="#"><u>Autonomous mode</u></a>	Agent, Required
<a href="#"><u>org.forgerock.agents.http.header.containing.remote.hostname</u></a>	<a href="#"><u>Client Hostname Header</u></a>	Client identification, Continuous security
<a href="#"><u>org.forgerock.agents.http.header.containing.ip.address</u></a>	<a href="#"><u>Client IP Address Header</u></a>	Client identification, Continuous security
<a href="#"><u>org.forgerock.agents.acceptable.ip.addresses.map</u></a>	<a href="#"><u>Client IP Validation Address Map</u></a>	Client identification
<a href="#"><u>org.forgerock.agents.original.ip.check.mode.map</u></a>	<a href="#"><u>Client IP Validation Mode</u></a>	Client identification
<a href="#"><u>org.forgerock.agents.conditional.logout.url.list</u></a>	<a href="#"><u>Conditional Logout URL List</u></a>	Logout
<a href="#"><u>org.forgerock.agents.config.reload.seconds</u></a>	<a href="#"><u>Configuration Reload Interval</u></a>	Profile
<a href="#"><u>org.forgerock.agents.container.encoding</u></a>	<a href="#"><u>Container Character Encoding</u></a>	Container, Not-enforced
<a href="#"><u>org.forgerock.agents.container.parameter.encoding</u></a>	<a href="#"><u>Container Parameter Encoding</u></a>	Container, Not-enforced
<a href="#"><u>org.forgerock.agents.continuous.security.cookies.map</u></a>	<a href="#"><u>Continuous Security Cookie Map</u></a>	Continuous security
<a href="#"><u>org.forgerock.agents.continuous.security.headers.map</u></a>	<a href="#"><u>Continuous Security Header Map</u></a>	Continuous security

Property	Description (UI name)	Function
<a href="#"><u>org.forgerock.agents.accept.ipdp.cookie</u></a>	<a href="#"><u>Convert SSO Tokens Into OIDC JWTs</u></a>	SSO cookie handling
<a href="#"><u>org.forgerock.agents.cookie.reset.enabled</u></a>	<a href="#"><u>Cookie Reset</u></a>	Cookie reset
<a href="#"><u>org.forgerock.agents.attribute.cookie.separator</u></a>	<a href="#"><u>Cookie Separator Character</u></a>	Attributes
<a href="#"><u>org.forgerock.agents.csv.monitoring.directory</u></a>	<a href="#"><u>CSV Monitoring Directory</u></a>	Monitoring
<a href="#"><u>org.forgerock.agents.response.header.map</u></a>	<a href="#"><u>Custom Response Header Map</u></a>	Miscellaneous
<a href="#"><u>org.forgerock.agents.debug.prefix</u></a>	<a href="#"><u>Debug File Rotation Prefix (deprecated)</u></a>	Deprecated
<a href="#"><u>org.forgerock.agents.debug.retention.count</u></a>	<a href="#"><u>Debug File Rotation Retention Count (deprecated)</u></a>	Deprecated
<a href="#"><u>org.forgerock.agents.debug.rotation.size.bytes</u></a>	<a href="#"><u>Debug File Rotation Size (deprecated)</u></a>	Deprecated
<a href="#"><u>org.forgerock.agents.debug.suffix</u></a>	<a href="#"><u>Debug File Rotation Suffix (deprecated)</u></a>	Deprecated
<a href="#"><u>org.forgerock.agents.debug.rotation.time.minutes</u></a>	<a href="#"><u>Debug File Rotation Time (deprecated)</u></a>	Deprecated
<a href="#"><u>org.forgerock.agents.fqdn.default</u></a>	<a href="#"><u>Default FQDN</u></a>	Fully qualified domain name
<a href="#"><u>org.forgerock.agents.attribute.cookie.encode.enabled</u></a>	<a href="#"><u>Enable Attribute Encoding</u></a>	Attributes
<a href="#"><u>org.forgerock.agents.advice.b64.url.encode.enabled</u></a>	<a href="#"><u>Enable Composite Advice Encoding</u></a>	Policy enforcement
<a href="#"><u>org.forgerock.agents.lock.config.enabled</u></a>	<a href="#"><u>Enable Configuration Lock</u></a>	Profile

Property	Description (UI name)	Function
<a href="#"><u>org.forgerock.agents.use.connection.pooling.enabled</u></a>	<a href="#"><u>Enable Connection Pooling</u></a>	Connection pooling
<a href="#"><u>org.forgerock.agents.legacy.login.enabled</u></a>	<a href="#"><u>Enable Custom Login Mode</u></a>	Custom login redirect, Default Login Redirect, Login redirect, Login Redirect (Default)
<a href="#"><u>com.iplanet.am.cookie.encode</u></a>	<a href="#"><u>Enable Encoded Cookies</u></a>	Cookie
<a href="#"><u>org.forgerock.agents.fqdn.check.enabled</u></a>	<a href="#"><u>Enable FQDN Checking</u></a>	Fully qualified domain name
<a href="#"><u>org.forgerock.agents.302.redirects.enabled</u></a>	<a href="#"><u>Enable HTTP 302 Redirects</u></a>	Global
<a href="#"><u>org.forgerock.agents.http.client.reuse.connections.enabled</u></a>	<a href="#"><u>Enable HTTP Connection Reuse</u></a>	Connection pooling
<a href="#"><u>org.forgerock.agents.http.client.connection.state.enabled</u></a>	<a href="#"><u>Enable HTTP Connection State</u></a>	Connection pooling
<a href="#"><u>com.sun.identity.cookie.httponly</u></a>	<a href="#"><u>Enable HTTP Only Cookies</u></a>	Cookie
<a href="#"><u>org.forgerock.agents.http.client.retry.requests.enabled</u></a>	<a href="#"><u>Enable HTTP Retry</u></a>	Connection pooling
<a href="#"><u>org.forgerock.agents.ignore.path.info.enabled</u></a>	<a href="#"><u>Enable Ignore Path Info</u></a>	Miscellaneous
<a href="#"><u>org.forgerock.agents.legacy.support.enabled</u></a>	<a href="#"><u>Enable Legacy Support Handlers (deprecated)</u></a>	Legacy support
<a href="#"><u>org.forgerock.agents.load.balancer.cookies.enabled</u></a>	<a href="#"><u>Enable Load Balancer Cookies</u></a>	Cookie
<a href="#"><u>org.forgerock.agents.local.audit.log.rotation.enabled</u></a>	<a href="#"><u>Enable Local Audit Log Rotation</u></a>	Audit

Property	Description (UI name)	Function
<a href="#"><u>org.forgerock.agents.logout.introspection.enabled</u></a>	<a href="#"><u>Enable Logout Introspection</u></a>	Logout
<a href="#"><u>org.forgerock.agents.notenforced.ip.cache.enabled</u></a>	<a href="#"><u>Enable Not-Enforced IP Cache</u></a>	Not-enforced
<a href="#"><u>org.forgerock.agents.notenforced.uri.cache.enabled</u></a>	<a href="#"><u>Enable Not-Enforced URIs Cache</u></a>	Not-enforced
<a href="#"><u>org.forgerock.agents.policy.change.notifications.enabled</u></a>	<a href="#"><u>Enable Notification of Policy Changes</u></a>	Notifications
<a href="#"><u>com.ipplanet.am.session.client.polling.enabled</u></a>	<a href="#"><u>Enable Notification of Session Logout (deprecated)</u></a>	Notifications
<a href="#"><u>org.forgerock.agents.session.change.notifications.enabled</u></a>	<a href="#"><u>Enable Notification of Session Logout</u></a>	Notifications
<a href="#"><u>org.forgerock.agents.config.change.notifications.enabled</u></a>	<a href="#"><u>Enable Notifications of Agent Configuration Change</u></a>	Notifications
<a href="#"><u>org.forgerock.agents.user.realm.override.s.policy.evaluation.realm.enabled</u></a>	<a href="#"><u>Enable Policy Evaluation in User Authentication Realm</u></a>	Policy enforcement
<a href="#"><u>org.forgerock.agents.port.check.enabled</u></a>	<a href="#"><u>Enable Port Checking (deprecated)</u></a>	Port check
<a href="#"><u>org.forgerock.agents.post.data.preservation.enabled</u></a>	<a href="#"><u>Enable POST Data Preservation</u></a>	POST data preservation
<a href="#"><u>org.forgerock.agents.prometheus.monitoring.enabled</u></a>	<a href="#"><u>Enable Prometheus Monitoring</u></a>	Global
<a href="#"><u>org.forgerock.agents.authn.success.redirect.session.url.enabled</u></a>	<a href="#"><u>Enable Redirect to AM Success URL</u></a>	Login



Property	Description (UI name)	Function
<a href="#"><u>org.forgerock.agents.accept.sso.tokens.enabled</u></a>	<a href="#"><u>Enable SSO Token Acceptance</u></a>	Custom login redirect, Login redirect, SSO cookie handling
<a href="#"><u>org.forgerock.agents.userid.mapping.mode.use.dn.enabled</u></a>	<a href="#"><u>Enable User Principal Flag</u></a>	User mapping
<a href="#"><u>org.forgerock.agents.encrypted.password</u></a>	<a href="#"><u>Encrypted Agent Password</u></a>	Miscellaneous, Required
<a href="#"><u>org.forgerock.agents.encryptor.classname</u></a>	<a href="#"><u>Encrypting Java class</u></a>	Authentication service, Encryption, Required
<a href="#"><u>org.forgerock.agents.encryption.key.digest</u></a>	<a href="#"><u>Encryption Digest</u></a>	Authentication service, Encryption
<a href="#"><u>am.encryption.pwd</u></a>	<a href="#"><u>Encryption Key</u></a>	Authentication service, Encryption, Required
<a href="#"><u>org.forgerock.agents.sso.exchange.cache.ttl.minutes</u></a>	<a href="#"><u>Exchanged SSO Token Cache TTL</u></a>	Profile
<a href="#"><u>org.forgerock.agents.samesite.excluded.user.agents.list</u></a>	<a href="#"><u>Exclude Agents From Samesite Cookie Attributes</u></a>	SameSite
<a href="#"><u>org.forgerock.agents.sso.expired.session.cache.ttl.minutes</u></a>	<a href="#"><u>Expired Session Cache Timeout</u></a>	Session
<a href="#"><u>org.forgerock.agents.config.monitoring.to.csv</u></a>	<a href="#"><u>Export Monitoring Metrics to CSV</u></a>	Monitoring
<a href="#"><u>org.forgerock.agents.fallforward.mode.enabled</u></a>	<a href="#"><u>Fall-Forward Mode (deprecated)</u></a>	Profile
<a href="#"><u>org.forgerock.agents.attribute.date.format</u></a>	<a href="#"><u>Fetch Attribute Date Format</u></a>	Attributes
<a href="#"><u>org.forgerock.agents.fqdn.map</u></a>	<a href="#"><u>FQDN Map</u></a>	Fully qualified domain name

Property	Description (UI name)	Function
<a href="#"><u>org.forgerock.agents.authn.fragment.relay.uri</u></a>	<a href="#"><u>Fragment Relay URI</u></a>	Fragment
<a href="#"><u>org.forgerock.agents.continuous.security.get.list</u></a>	<a href="#"><u>GET Parameter List for URL Policy Env</u></a>	Policy enforcement
<a href="#"><u>com.sun.identity.agents.config.redirect.param</u></a>	<a href="#"><u>Goto Parameter Name</u></a>	Global
<a href="#"><u>org.forgerock.agents.default.goto.url</u></a>	<a href="#"><u>Goto URL</u></a>	Authentication failure
<a href="#"><u>org.forgerock.agents.302.redirect.http.content.type</u></a>	<a href="#"><u>HTTP 302 Redirect Content Type</u></a>	Global
<a href="#"><u>org.forgerock.agents.302.redirect.http.data</u></a>	<a href="#"><u>HTTP 302 Redirect Data</u></a>	Global
<a href="#"><u>org.forgerock.agents.config.json.url.invert</u></a>	<a href="#"><u>HTTP 302 Redirect Invert Not-Enforced List</u></a>	Global
<a href="#"><u>org.forgerock.agents.config.json.url</u></a>	<a href="#"><u>HTTP 302 Redirect Not-Enforced List</u></a>	Global
<a href="#"><u>org.forgerock.agents.302.redirect.http.status.code</u></a>	<a href="#"><u>HTTP 302 Redirect Replacement HTTP Status Code</u></a>	Global
<a href="#"><u>org.forgerock.agents.http.client.connection.timeout.seconds</u></a>	<a href="#"><u>HTTP Connection Timeout</u></a>	Connection pooling
<a href="#"><u>org.forgerock.agents.http.session.binding.enabled</u></a>	<a href="#"><u>HTTP Session Binding</u></a>	Miscellaneous
<a href="#"><u>org.forgerock.agents.http.client.socket.timeout.seconds</u></a>	<a href="#"><u>HTTP Socket Timeout</u></a>	Connection pooling
<a href="#"><u>org.forgerock.agents.idle.time.window.minutes</u></a>	<a href="#"><u>Idle Time Refresh Window</u></a>	Miscellaneous
<a href="#"><u>org.forgerock.agents.notenforced.ip.invert.enabled</u></a>	<a href="#"><u>Invert Not-Enforced IPs</u></a>	Not-enforced

Property	Description (UI name)	Function
<a href="#"><u>org.forgerock.agents.notenforced.uri.invert.enabled</u></a>	<a href="#"><u>Invert Not-Enforced URIs</u></a>	Not-enforced
<a href="#"><u>org.forgerock.agents.not.enforced.rule.pattern.matcher.classname</u></a>	<a href="#"><u>Java Class for Matching Not Enforced Rules</u></a>	Not-enforced
<a href="#"><u>org.forgerock.agents.continuous.security.http.session.list</u></a>	<a href="#"><u>JSession Parameter List for URL Policy Env</u></a>	Policy enforcement
<a href="#"><u>org.forgerock.agents.jwt.cache.ttl.minutes</u></a>	<a href="#"><u>JWT Cache TTL</u></a>	Profile
<a href="#"><u>org.forgerock.agents.jwt.cookie.domain.list</u></a>	<a href="#"><u>JWT Cookie Domain List</u></a>	Profile
<a href="#"><u>org.forgerock.agents.jwt.cookie.name</u></a>	<a href="#"><u>JWT Cookie Name</u></a>	Profile
<a href="#"><u>org.forgerock.agents.legacy.login.url.list</u></a>	<a href="#"><u>Legacy Login URL List</u></a>	Custom login redirect, Default Login Redirect, Login redirect, Login Redirect (Default)
<a href="#"><u>org.forgerock.agents.legacy.user.agent.list</u></a>	<a href="#"><u>Legacy User Agent List (deprecated)</u></a>	Legacy support
<a href="#"><u>org.forgerock.agents.legacy.redirect.uri</u></a>	<a href="#"><u>Legacy User Agent Redirect URI (deprecated)</u></a>	Legacy support
<a href="#"><u>org.forgerock.agents.load.balancer.cookie.name</u></a>	<a href="#"><u>Load Balancer Cookie Name</u></a>	Cookie
<a href="#"><u>org.forgerock.agents.local.audit.file.path</u></a>	<a href="#"><u>Local Audit Log Filename</u></a>	Audit
<a href="#"><u>org.forgerock.agents.local.audit.log.rotation.bytes</u></a>	<a href="#"><u>Local Audit Log Rotation Size</u></a>	Audit
<a href="#"><u>org.forgerock.agents.locale.country</u></a>	<a href="#"><u>Locale Country</u></a>	Locale
<a href="#"><u>org.forgerock.agents.locale.language</u></a>	<a href="#"><u>Locale Language</u></a>	Locale

Property	Description (UI name)	Function
<a href="#"><u>org.forgerock.agents.config.location</u></a>	<a href="#"><u>Location of Agent Configuration Repository</u></a>	Profile, Required
<a href="#"><u>com.ipplanet.services.debug.directory</u></a>	<a href="#"><u>Log File Directory (deprecated)</u></a>	Deprecated
<a href="#"><u>org.forgerock.agents.login.attempt.limit.count</u></a>	<a href="#"><u>Login Attempt Limit</u></a>	Login
<a href="#"><u>org.forgerock.agents.login.counter.cookie.name</u></a>	<a href="#"><u>Login Attempt Limit Cookie Name</u></a>	Login
<a href="#"><u>org.forgerock.agents.login.reason.parameter.name</u></a>	<a href="#"><u>Login Reason Parameter Name</u></a>	Custom login redirect, Login redirect
<a href="#"><u>org.forgerock.agents.login.reason.remapper</u></a>	<a href="#"><u>Login Reason Value Map</u></a>	Login
<a href="#"><u>org.forgerock.agents.logout.goto.map</u></a>	<a href="#"><u>Logout Entry URI Map</u></a>	Logout
<a href="#"><u>org.forgerock.agents.logout.request.parameter.map</u></a>	<a href="#"><u>Logout Request Parameter Map</u></a>	Logout
<a href="#"><u>org.forgerock.agents.logout.endpoint.map</u></a>	<a href="#"><u>Logout URI Map</u></a>	Logout
<a href="#"><u>org.forgerock.agents.authn.cookie.max.age.seconds</u></a>	<a href="#"><u>Max Age of Pre-Authentication Cookie</u></a>	Cookie, Pre-authentication
<a href="#"><u>org.forgerock.agents.expired.session.cache.size</u></a>	<a href="#"><u>Max Entries in Expired Session Cache</u></a>	Session
<a href="#"><u>org.forgerock.agents.jwt.cache.size</u></a>	<a href="#"><u>Max Entries in JWT Cache</u></a>	Profile
<a href="#"><u>org.forgerock.agents.notenforced.ip.cache.size</u></a>	<a href="#"><u>Max Entries in Not-Enforced IP Cache</u></a>	Not-enforced
<a href="#"><u>org.forgerock.agents.notenforced.uri.cache.size</u></a>	<a href="#"><u>Max Entries in Not-Enforced URI Cache</u></a>	Not-enforced

Property	Description (UI name)	Function
<a href="#"><u>org.forgerock.agents.policy.cache.per.session.size</u></a>	<a href="#"><u>Max Entries in Policy Cache per Session</u></a>	Policy enforcement
<a href="#"><u>org.forgerock.agents.pdp.cache.size</u></a>	<a href="#"><u>Max Entries in POST Data Preservation Storage</u></a>	POST data preservation
<a href="#"><u>org.forgerock.agents.sso.exchange.cache.size</u></a>	<a href="#"><u>Max Entries in SSO Exchange Cache</u></a>	Profile
<a href="#"><u>org.forgerock.agents.http.client.max.connections</u></a>	<a href="#"><u>Max HTTP Connection Count</u></a>	Connection pooling
<a href="#"><u>org.forgerock.agents.max.decompression.size.bytes</u></a>	<a href="#"><u>Maximum Decompression Size</u></a>	Cookie
<a href="#"><u>org.forgerock.agents.policy.cache.session.size</u></a>	<a href="#"><u>Max Sessions in Policy Cache</u></a>	Policy enforcement
<a href="#"><u>org.forgerock.agents.pdp.noentry.url.map</u></a>	<a href="#"><u>Missing POST Data Preservation Entry URI Map</u></a>	POST data preservation
<a href="#"><u>org.forgerock.agents.notenforced.ip.list</u></a>	<a href="#"><u>Not-Enforced Client IP List</u></a>	Not-enforced
<a href="#"><u>org.forgerock.agents.notenforced.compound.separator</u></a>	<a href="#"><u>Not-Enforced Compound Rule Separator</u></a>	Not-enforced
<a href="#"><u>org.forgerock.agents.auto.not.enforce.favicon</u></a>	<a href="#"><u>Not-Enforced Favicon</u></a>	Not-enforced
<a href="#"><u>org.forgerock.agents.notenforced.uri.list</u></a>	<a href="#"><u>Not-Enforced URIs</u></a>	Not-enforced
<a href="#"><u>org.forgerock.agents.oauth.login.url.list</u></a>	<a href="#"><u>OAuth Login URL List</u></a>	Custom login redirect, Default Login Redirect, Login redirect, Login Redirect (Default)

Property	Description (UI name)	Function
<a href="#"><u>org.forgerock.agents.obsolete.notification.url</u></a>	<a href="#"><u>Obsolete Notification URL</u></a> (deprecated)	Notifications
<a href="#"><u>org.forgerock.agents.policy.cache.ttl.minutes</u></a>	<a href="#"><u>Policy Cache TTL</u></a>	Policy enforcement
<a href="#"><u>org.forgerock.agents.policy.evaluation.realm.map</u></a>	<a href="#"><u>Policy Evaluation Realm Map</u></a>	Policy enforcement
<a href="#"><u>org.forgerock.agents.policy.set.map</u></a>	<a href="#"><u>Policy Set Map</u></a>	Policy enforcement
<a href="#"><u>org.forgerock.agents.port.check.file</u></a>	<a href="#"><u>Port Check Filename</u></a> (deprecated)	Port check
<a href="#"><u>org.forgerock.agents.port.check.map</u></a>	<a href="#"><u>Port Check Protocol Map</u></a> (deprecated)	Port check
<a href="#"><u>org.forgerock.agents.pdp.cache.ttl.minutes</u></a>	<a href="#"><u>POST Data Preservation Cache TTL</u></a>	POST data preservation
<a href="#"><u>com.sun.identity.agents.config.postdata.reserve.cache.entry.ttl</u></a>	<a href="#"><u>POST Data Preservation Cache TTL in Milliseconds</u></a> (deprecated)	POST data preservation
<a href="#"><u>org.forgerock.agents.pdp.cookie.name</u></a>	<a href="#"><u>Post Data Preservation Cookie Name</u></a>	Cookie, POST data preservation
<a href="#"><u>org.forgerock.agents.pdp.directory.sweep.seconds</u></a>	<a href="#"><u>POST Data Preservation Directory Sweep Interval</u></a>	POST data preservation
<a href="#"><u>org.forgerock.agents.pdp.directory</u></a>	<a href="#"><u>POST Data Preservation File Directory</u></a>	POST data preservation

Property	Description (UI name)	Function
<a href="#"><u>org.forgerock.agents.pdp.use.filesystem.enabled</u></a>	<a href="#"><u>POST Data Preservation in Files or Cache</u></a>	POST data preservation
<a href="#"><u>org.forgerock.agents.pdp.sticky.session.value</u></a>	<a href="#"><u>POST Data Preservation Sticky Session Key Value</u></a>	POST data preservation
<a href="#"><u>org.forgerock.agents.pdp.sticky.session.mode</u></a>	<a href="#"><u>POST Data Preservation Sticky Session Mode</u></a>	POST data preservation
<a href="#"><u>org.forgerock.agents.pdp.cache.total.size.mb</u></a>	<a href="#"><u>POST Data Preservation Storage Size</u></a>	POST data preservation
<a href="#"><u>org.forgerock.agents.continuous.security.post.list</u></a>	<a href="#"><u>POST Parameter List for URL Policy Env</u></a>	Policy enforcement
<a href="#"><u>org.forgerock.agents.authn.cookie.name</u></a>	<a href="#"><u>Pre-Authentication Cookie Name</u></a>	Cookie, Pre-authentication
<a href="#"><u>org.forgerock.agents.cookie.signing.value</u></a>	<a href="#"><u>Pre-Authn and Post Data Preservation Cookie Signing Value</u></a>	Cookie, POST data preservation, Pre-authentication
<a href="#"><u>org.forgerock.agents.profile.attribute.fetch.mode</u></a>	<a href="#"><u>Profile Attribute Fetch Mode</u></a>	Attributes, Cookie reset, Profile
<a href="#"><u>org.forgerock.agents.profile.attribute.map</u></a>	<a href="#"><u>Profile Attribute Map</u></a>	Profile
<a href="#"><u>org.forgerock.agents.public.am.url</u></a>	<a href="#"><u>Public AM URL</u></a>	Miscellaneous, Required
<a href="#"><u>org.forgerock.agents.wanted.http.url.param.list</u></a>	<a href="#"><u>Query Parameter List for Policy Evaluation</u></a>	Query parameter
<a href="#"><u>org.forgerock.agents.am.unavailability.recheck.window.in.seconds</u></a>	<a href="#"><u>Recheck availability of AM</u></a>	Agent

Property	Description (UI name)	Function
<a href="#"><u>org.forgerock.agents.redirect.cookie.name</u></a>	<a href="#"><u>Redirect Attempt Cookie Name</u></a>	Miscellaneous
<a href="#"><u>org.forgerock.agents.redirect.attempt.limit</u></a>	<a href="#"><u>Redirect Attempt Limit</u></a>	Login
<a href="#"><u>org.forgerock.agents.wanted.http.url.params.regex.list</u></a>	<a href="#"><u>Regex Query Parameters List for Policy Evaluation</u></a>	Query parameter
<a href="#"><u>org.forgerock.agents.unwanted.http.url.params.regex.list</u></a>	<a href="#"><u>Regex Remove Query Parameters List for Policy Evaluation</u></a>	Query parameter
<a href="#"><u>org.forgerock.agents.unwanted.http.url.p aram.list</u></a>	<a href="#"><u>Remove Query Parameters List for Policy Evaluation</u></a>	Query parameter
<a href="#"><u>org.forgerock.agents.cookie.reset.domain .map</u></a>	<a href="#"><u>Reset Cookie Domain Map</u></a>	Cookie reset
<a href="#"><u>org.forgerock.agents.cookie.reset.name.li st</u></a>	<a href="#"><u>Reset Cookie List</u></a>	Cookie reset
<a href="#"><u>org.forgerock.agents.cookie.reset.path.m ap</u></a>	<a href="#"><u>Reset Cookie Path Map</u></a>	Cookie reset
<a href="#"><u>org.forgerock.agents.response.attribute.f etch.mode</u></a>	<a href="#"><u>Response Attribute Fetch Mode</u></a>	Attributes, Response
<a href="#"><u>org.forgerock.agents.response.attribute. map</u></a>	<a href="#"><u>Response Attribute Map</u></a>	Response
<a href="#"><u>org.forgerock.agents.restrict.to.realm.ma p</u></a>	<a href="#"><u>Restrict to Realm Map</u></a>	Policy enforcement
<a href="#"><u>org.forgerock.agents.service.resolver.clas s.name</u></a>	<a href="#"><u>Service Resolver Class Name</u></a>	Miscellaneous
<a href="#"><u>org.forgerock.agents.session.attribute.fet ch.mode</u></a>	<a href="#"><u>Session Attribute Fetch Mode</u></a>	Attributes, Cookie reset, Session
<a href="#"><u>org.forgerock.agents.session.attribute.ma p</u></a>	<a href="#"><u>Session Attribute Map</u></a>	Session



Property	Description (UI name)	Function
<a href="#"><u>org.forgerock.agents.session.cache.ttl.minutes</u></a>	<a href="#"><u>Session Cache TTL</u></a>	Session
<a href="#"><u>org.forgerock.agents.set.cookie.attribute.map</u></a>	<a href="#"><u>Set-Cookie Attribute Map</u></a>	SameSite
<a href="#"><u>org.forgerock.agents.set.cookie.internal.map</u></a>	<a href="#"><u>Set-Cookie Internal Map</u></a>	SameSite
<a href="#"><u>org.forgerock.agents.ipdp.cookie.domain.list</u></a>	<a href="#"><u>SSO Cookie Domain List</u></a>	SSO cookie handling
<a href="#"><u>org.forgerock.agents.strategy.when.am.unavailable</u></a>	<a href="#"><u>Strategy when AM unavailable</u></a>	Agent
<a href="#"><u>org.forgerock.agents.secure.cookies.enabled</u></a>	<a href="#"><u>Transmit Cookies Securely</u></a>	Cross-domain single sign-on
<a href="#"><u>org.forgerock.agents.user.mapping.mode.attribute.name</u></a>	<a href="#"><u>User Attribute Name</u></a>	User mapping
<a href="#"><u>org.forgerock.agents.user.mapping.mode</u></a>	<a href="#"><u>User Mapping Mode</u></a>	User mapping
<a href="#"><u>org.forgerock.agents.userid.mapping.mode.use.session.property.name</u></a>	<a href="#"><u>User Session Name</u></a>	User mapping
<a href="#"><u>org.forgerock.agents.balance.websocket.interval.minutes</u></a>	<a href="#"><u>WebSocket Connection Interval</u></a>	Profile
<a href="#"><u>org.forgerock.agents.declare.websocket.dead.after.milliseconds</u></a>	<a href="#"><u>WebSocket Expired Timeout</u></a>	Timeout
<a href="#"><u>org.forgerock.agents.ping.websocket.after.inactive.milliseconds</u></a>	<a href="#"><u>WebSocket Idle Timeout</u></a>	Timeout
<a href="#"><u>org.forgerock.agents.xss.code.element.list</u></a>	<a href="#"><u>XSS Code Element List</u></a>	Cross-site scripting
<a href="#"><u>org.forgerock.agents.xss.redirect.uri.map</u></a>	<a href="#"><u>XSS Redirect URI Map</u></a>	Cross-site scripting

Access denied

# Access Denied URI Map

The URIs of custom pages to return when access is denied. The key is the web application name. The value is the custom URI.

To set a global custom access denied URI for web applications without other custom access denied URIs defined, leave the key empty and set the value to the global custom access denied URI, `/sample/accessdenied.html`.

To set a custom access denied URI for a specific web application, set the key to the name of the web application, and the value to the web application access denied URI, such as `/myApp/accessdenied.html`.

Specify a full URL if required, including the host name. For example:  
`https://help.example.com/errors/accessdenied.html`.

Property name	<code>org.forgerock.agents.access.denied.uri.map</code>
Aliases	<code>com.sun.identity.agents.config.access.denied.uri</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6 <code>org.forgerock.agents.access.denied.uri.map</code> Introduced in Java Agent 5.6
Function	Access denied
Type	Map <ul style="list-style-type: none"><li>• Keys: web application</li><li>• Values: URI of page saying 'access denied'</li></ul>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Application Title: Access Denied URI Map Legacy title: Resource Access Denied URI

## Agent

### Alternative Agent Protocol

---

In environments when agents are behind a load balancer or reverse proxy which does a SSL offloading, the request URL is changed to match the URL that the agent receives.

The agent then uses the new URL as the redirection value in the pre-authentication cookie, created during the first unauthenticated request to the agent.

Use the following properties to override the agent redirection value with the URL of the original client request: Alternative Agent Host Name, and Alternative Agent Port Number.

Property name	<code>org.forgerock.agents.agent.protocol</code>
Aliases	<code>com.sun.identity.agents.config.agent.protocol</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  <code>org.forgerock.agents.agent.protocol</code> Introduced in Java Agent 5.6
Function	Agent
Type	String
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Advanced  Title: Alternative Agent Protocol

### Autonomous mode

---

When `true` the agent operates independently of AM, without needing to contact an AM instance. Agents allow access to resources as defined in not-enforced lists; otherwise, they deny access.

Property name	<code>org.forgerock.agents.fallback.mode.enabled</code>
Aliases	<code>com.forgerock.agents.config.fallback.mode</code> Introduced in Java Agent 5.9.0  <code>org.forgerock.agents.fallback.mode.enabled</code> Introduced in Java Agent 5.9.0  <code>org.forgerock.agents.autonomous.mode.enabled</code> Introduced in Java Agent 5.9.0
Function	Agent, Required
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>false</code>
Bootstrap property	Yes
Required property	Yes - If this property is missing, the agent fails to start
Restart required	Yes - Restart the container after changing the property
Local configuration file	<code>AgentBootstrap.properties</code>

## Recheck availability of AM

The duration after which the agent rechecks AM availability, when Autonomous mode is `false`, and AM becomes unavailable at runtime.

Consider these points when you configure this property:

- If the duration is too short, the agent checks AM availability too often, and agent performance can be reduced.
- If the duration is zero, the agent checks AM availability for every call. Requests that match not-enforced rules can take longer.

Property name	<code>org.forgerock.agents.am.unavailability.recheck.window.in.seconds</code>
Aliases	<code>org.forgerock.agents.am.unavailability.recheck.window.in.seconds</code> Introduced in Java Agent 5.9.0 <u>Recognized</u> from AM 7.2

Function	Agent
Type	Integer
Default	5
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Profile (from AM 7.2) Title: Recheck availability of AM

## Alternative Agent Port Number

In environments when agents are behind a load balancer or reverse proxy which does a SSL offloading, the request URL is changed to match the URL that the agent receives.

The agent then uses the new URL as the redirection value in the pre-authentication cookie, created during the first unauthenticated request to the agent.

Use the following properties to override the agent redirection value with the URL of the original client request: [Alternative Agent Host Name](#), and [Alternative Agent Protocol](#).

Property name	org.forgerock.agents.agent.port
Aliases	com.sun.identity.agents.config.agent.port Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  org.forgerock.agents.agent.port Introduced in Java Agent 5.6
Function	Agent
Type	Integer
Default	''
Bootstrap property	No
Required property	No

Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Advanced  Title: Alternative Agent Port Number

## Alternative Agent Host Name

---

In environments when agents are behind a load balancer or reverse proxy which does a SSL offloading, the request URL is changed to match the URL that the agent receives.

The agent then uses the new URL as the redirection value in the pre-authentication cookie, created during the first unauthenticated request to the agent.

Use the following properties to override the agent redirection value with the URL of the original client request: [Alternative Agent Port Number](#) and [Alternative Agent Protocol](#).

Property name	org.forgerock.agents.agent.hostname
Aliases	com.sun.identity.agents.config.agent.host Introduced in Java Agent 5.0 <a href="#">Recognized</a> from AM 6  org.forgerock.agents.agent.hostname Introduced in Java Agent 5.6
Function	Agent
Type	String
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Advanced  Title: Alternative Agent Host Name

## Agent Filter Mode Map

---

A map of web application name to agent filter mode:

- Key: Web application name.
- Value: Agent filter mode.

The following example configures one filter mode for the BankApp web application. All other web applications use the default filter mode, URL\_POLICY :

```
org.forgerock.agents.filter.mode.map[BankApp]=SSO_ONLY
```

The following example configures the NONE filter mode for all applications in the web container: org.forgerock.agents.filter.mode.map[ALL]=NONE

The mode J2EE\_POLICY does not apply to Java Agents 5.10. However, for backward-compatibility, it is displayed in the AM agent profile page.

Property name	org.forgerock.agents.filter.mode.map
Aliases	com.sun.identity.agents.config.filter.mode Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  org.forgerock.agents.filter.mode.map Introduced in Java Agent 5.6.2.1
Function	Agent
Supported settings	<b>NONE</b> The agent performs no authentication check, and grants access to any resource. When the value is NONE and logging is enabled, for auditing purposes, the agent filter logs all incoming requests.  <b>SSO_ONLY</b> Any user having either a valid SSO token or JWT can access any resource.  <b>URL_POLICY</b> The normal operating mode of the agent, in which resource access is granted by AM policy evaluation.
Default	URL_POLICY
Bootstrap property	Yes
Required property	No
Restart required	No

Local configuration file	AgentBootstrap.properties
AM console	Tab: Global  Title: Agent Filter Mode Map  Legacy title: Agent Filter Mode

## Strategy when AM unavailable

---

When Autonomous mode is `false`, this property defines the strategy to use when AM becomes unavailable at runtime (for example, due to network errors).

Property name	<code>org.forgerock.agents.strategy.when.am.unavailable</code>
Aliases	<code>org.forgerock.agents.strategy.when.am.unavailable</code> Introduced in Java Agent 5.9.0
Function	Agent



## Supported settings

### ***IMMEDIATE\_403***

When AM is unavailable, every request immediately returns an HTTP 403

### ***IMMEDIATE\_503***

When AM is unavailable, every request immediately return an HTTP 503

### ***EVAL\_NER\_ELSE\_403***

When AM is unavailable, incoming requests are matched against not-enforced rules. Access is granted to matched resources, everything else returns HTTP 403.

### ***EVAL\_NER\_ELSE\_503***

When AM is unavailable, incoming requests are matched against not-enforced rules. Access is granted to matched resources, everything else returns HTTP 503.

### ***EVAL\_NER\_USE\_CACHE\_UNTIL\_EXPIRED\_ELSE\_403***

When AM is unavailable, incoming requests are matched against not-enforced rules. Unmatched requests are resolved against the cache. Requests unmatched by the cache result in HTTP 403. Cached entries expire naturally. Note that after the interval defined in "Policy Cache TTL" (org.forgerock.agents.policy.cache.ttl.minutes), this becomes exactly like EVAL\_NER\_ELSE\_403.

### ***EVAL\_NER\_USE\_CACHE\_UNTIL\_EXPIRED\_ELSE\_503***

When AM is unavailable, incoming requests are matched against not-enforced rules. Unmatched requests are resolved against the cache. Requests unmatched by the cache result in HTTP 503. Cached entries expire naturally. Note that after the interval defined in "Policy Cache TTL" (org.forgerock.agents.policy.cache.ttl.minutes), this becomes exactly like EVAL\_NER\_ELSE\_503.

### ***EVAL\_NER\_CACHE\_INDEFINITELY\_ELSE\_403***

As soon as AM becomes unavailable, values in the agent caches are frozen and preserved indefinitely. Incoming requests are matched against not-enforced rules. Unmatched requests are resolved against the agent's frozen cache. Requests not matching the cache result in HTTP 403.

	<p><b><i>EVAL_NER_CACHE_INDEFINITELY_ELSE_503</i></b></p> <p>As soon as AM becomes unavailable, values in the agent caches are frozen and preserved indefinitely. Incoming requests are matched against not-enforced rules. Unmatched requests are resolved against the agent's frozen cache. Requests not matching the cache result in HTTP 503.</p>
Default	EVAL_NER_USE_CACHE_UNTIL_EXPIRED_ELSE_503
Bootstrap property	Yes
Required property	No
Restart required	No
Local configuration file	AgentBootstrap.properties

## Attributes

### Session Attribute Fetch Mode

Map the name of an AM session attribute specified in [Session Attribute Map](#) as follows:

- NONE: Do not map
- HTTP\_HEADER: Map the to the name of an HTTP session header
- HTTP\_COOKIE: Map to the name of an HTTP cookie
- REQUEST\_ATTRIBUTE: Map to the name of an HTTP session attribute

When the value is HTTP\_COOKIE , [Cookie Reset](#) is automatically set to true . Before redirecting the client for login, and when the client logs out, the agent resets profile and session attributes cookies, and cookies in the [Reset Cookie List](#).

Property name	org.forgerock.agents.session.attribute.fetch.mode
---------------	---------------------------------------------------

Aliases	<p><code>org.forgerock.agents.session.attribute.fetch.mode</code> Introduced in Java Agent 5.6</p> <p><code>com.sun.identity.agents.config.session.attribute.fetch.mode</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6</p>
Function	Attributes, Cookie reset, Session
Supported settings	<p><b>NONE</b> No AM attributes are mapped.</p> <p><b>HTTP_HEADER</b> The named AM attributes are mapped to headers in the outgoing HTTP response.</p> <p><b>REQUEST_ATTRIBUTE</b> The named AM attributes are mapped to request attributes in the outgoing HTTP response.</p> <p><b>HTTP_COOKIE</b> The named AM attributes are mapped to cookies in the outgoing HTTP response.</p>
Default	NONE
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	<p>Tab: Application</p> <p>Title: Session Attribute Fetch Mode</p>

## Cookie Separator Character

The separator for multiple values of the same attribute when it is set as a cookie.

Property name	<code>org.forgerock.agents.attribute.cookie.separator</code>
---------------	--------------------------------------------------------------

Aliases	<p><code>com.sun.identity.agents.config.attribute.cookie.separator</code></p> <p>Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6</p> <p><code>org.forgerock.agents.attribute.cookie.separator</code></p> <p>Introduced in Java Agent 5.6</p>
Function	Attributes
Type	String
Default	
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	<p>Tab: Application</p> <p>Title: Cookie Separator Character</p>

## Fetch Attribute Date Format

The `java.text.SimpleDateFormat` of date attribute values used when an attribute is set in an HTTP header.

Property name	<code>org.forgerock.agents.attribute.date.format</code>
Aliases	<p><code>com.sun.identity.agents.config.attribute.date.format</code></p> <p>Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6</p> <p><code>org.forgerock.agents.attribute.date.format</code></p> <p>Introduced in Java Agent 5.6</p>
Function	Attributes
Type	String

Default	EEE, d MMM yyyy hh:mm:ss z
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Application Title: Fetch Attribute Date Format

## Response Attribute Fetch Mode

Map the name of an AM policy response attribute specified in [Response Attribute Map](#) as follows:

- NONE: Do not map
- HTTP\_HEADER: Map the to the name of an HTTP response header
- HTTP\_COOKIE: Map to the name of an HTTP cookie
- REQUEST\_ATTRIBUTE: Map to the name of an HTTP request attribute

Property name	<code>org.forgerock.agents.response.attribute.fetch.mode</code>
Aliases	<code>com.sun.identity.agents.config.response.attribute.fetch.mode</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  <code>org.forgerock.agents.response.attribute.fetch.mode</code> Introduced in Java Agent 5.6
Function	Attributes, Response

Supported settings	<p><b>NONE</b> No AM attributes are mapped.</p> <p><b>HTTP_HEADER</b> The named AM attributes are mapped to headers in the outgoing HTTP response.</p> <p><b>REQUEST_ATTRIBUTE</b> The named AM attributes are mapped to request attributes in the outgoing HTTP response.</p> <p><b>HTTP_COOKIE</b> The named AM attributes are mapped to cookies in the outgoing HTTP response.</p>
Default	NONE
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	<p>Tab: Application</p> <p>Title: Response Attribute Fetch Mode</p>

## Profile Attribute Fetch Mode

Map the name of an AM profile attribute specified in [Profile Attribute Map](#) as follows:

- NONE: Do not map
- HTTP\_HEADER: Map the to the name of an HTTP profile header
- HTTP\_COOKIE: Map to the name of an HTTP cookie
- REQUEST\_ATTRIBUTE: Map to the name of an HTTP profile attribute

Property name	org.forgerock.agents.profile.attribute.fetch.mode
---------------	---------------------------------------------------

Aliases	<p><code>com.sun.identity.agents.config.profile.attribute.fetch.mode</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6</p> <p><code>org.forgerock.agents.profile.attribute.fetch.mode</code> Introduced in Java Agent 5.6</p>
Function	Attributes, Cookie reset, Profile
Supported settings	<p><b>NONE</b> No AM attributes are mapped.</p> <p><b>HTTP_HEADER</b> The named AM attributes are mapped to headers in the outgoing HTTP response.</p> <p><b>REQUEST_ATTRIBUTE</b> The named AM attributes are mapped to request attributes in the outgoing HTTP response.</p> <p><b>HTTP_COOKIE</b> The named AM attributes are mapped to cookies in the outgoing HTTP response.</p>
Default	NONE
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	<p>Tab: Application</p> <p>Title: Profile Attribute Fetch Mode</p>

## Enable Attribute Encoding

When `true`, attribute values are URL-encoded before being set as a cookie.

Property name	<code>org.forgerock.agents.attribute.cookie.encode.enabled</code>
---------------	-------------------------------------------------------------------

Aliases	<p><code>com.sun.identity.agents.config.attribute.cookie.encode</code></p> <p>Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6</p> <p><code>org.forgerock.agents.attribute.cookie.encode.enabled</code></p> <p>Introduced in Java Agent 5.6</p>
Function	Attributes
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>true</code>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	<p>Tab: Application</p> <p>Title: Enable Attribute Encoding</p> <p>Legacy title: Attribute Cookie Encode</p>

## Audit

### Enable Local Audit Log Rotation

When `true`, rotate local audit log files that have reached the size specified by Local Audit Log Rotation Size.

Property name	<code>org.forgerock.agents.local.audit.log.rotation.enabled</code>
---------------	--------------------------------------------------------------------



Aliases	<p><code>org.forgerock.agents.local.audit.log.rotation.enabled</code> Introduced in Java Agent 5.6</p> <p><code>com.sun.identity.agents.config.local.log.rotate</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6</p>
Function	Audit
Type	Boolean: true returns true; all other strings return false.
Default	false
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	<p>Tab: Global</p> <p>Title: Enable Local Audit Log Rotation</p> <p>Legacy title: Rotate Local Audit Log</p>

## Local Audit Log Rotation Size

The maximum size in bytes of the local audit log files. When Enable Local Audit Log Rotation is `true`, the agent rotates the log file when it reaches this size.

Property name	<code>org.forgerock.agents.local.audit.log.rotation.bytes</code>
Aliases	<p><code>com.sun.identity.agents.config.local.log.size</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6</p> <p><code>org.forgerock.agents.local.audit.log.rotation.bytes</code> Introduced in Java Agent 5.7</p>

Function	Audit
Type	Integer
Default	52428800
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Global Title: Local Audit Log Rotation Size

## Audit Logfile Retention Count

The number of audit log files to retain after rotation. When the specified limit is reached, the oldest file is deleted when a file rotation occurs.

When the value is `-1`, all rotated files are kept. When the value is, for example, `10`, the current file and nine older rotated files are kept.

Property name	<code>org.forgerock.agents.local.audit.log.retention.count</code>
Aliases	<code>org.forgerock.agents.local.audit.log.retention.count</code> Introduced in Java Agent 5.7 <u>Recognized</u> from AM 7
Function	Audit
Type	Integer
Default	<code>-1</code>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties

AM console	Tab: Global (from AM 7) Title: Audit Logfile Retention Count
------------	-----------------------------------------------------------------

## Audit Access Types

The type of messages to audit.

Property name	<code>org.forgerock.agents.audit.what</code>
Aliases	<code>com.sun.identity.agents.config.audit.accessstype</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6 <code>org.forgerock.agents.audit.what</code> Introduced in Java Agent 5.6
Function	Audit
Supported settings	<b><i>LOG_NONE</i></b> Don't audit anything. <b><i>LOG_ALLOW</i></b> Audit only allowed requests. <b><i>LOG_DENY</i></b> Audit only denied requests. <b><i>LOG_BOTH</i></b> Audit both allowed and denied requests.
Default	LOG_NONE
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Global Title: Audit Access Types

## Local Audit Log Filename

---

The full path to the agent's local audit log file.

Default: None; local auditing is disabled

Property name	<code>org.forgerock.agents.local.audit.file.path</code>
Aliases	<code>com.sun.identity.agents.config.local.logfile</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 7  <code>org.forgerock.agents.local.audit.file.path</code> Introduced in Java Agent 5.6
Function	Audit
Type	String
Bootstrap property	Yes
Required property	No
Restart required	No
Local configuration file	<code>AgentBootstrap.properties</code>

## Audit Log Location

---

The location where the agent logs audit messages. If Audit Access Types is `LOG_NONE`, this property has no effect.

Property name	<code>org.forgerock.agents.audit.where</code>
Aliases	<code>com.sun.identity.agents.config.log.dispositio n</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  <code>org.forgerock.agents.audit.where</code> Introduced in Java Agent 5.6
Function	Audit

Supported settings	<p><b>NONE</b> Don't audit anything, anywhere.</p> <p><b>LOCAL</b> Audit locally only.</p> <p><b>REMOTE</b> Audit remotely only.</p> <p><b>ALL</b> Audit both locally and remotely.</p>
Default	NONE
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	<p>Tab: Global</p> <p>Title: Audit Log Location</p>

## Authentication failure

### Authentication Fail Reason Parameter Name

---

A query parameter name to contain the reason why authentication failed. The agent appends this parameter to the URL or URI defined by [Authentication Fail URL](#).

If this property is not set, the agent does not append the reason for the authentication failure, when redirecting to the URL or URI.

To reduce the risk of leaking useful information, configure [Authentication Fail Reason Parameter Value Map](#) to change the strings for the above values.

Property name	org.forgerock.agents.authn.fail.reason.parameter.name
---------------	-------------------------------------------------------

Aliases	org.forgerock.agents.authn.fail.reason.parameter.name Introduced in Java Agent 5.7 <u>Recognized</u> from AM 7
Function	Authentication failure
Type	String
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Miscellaneous (from AM 7)  Title: Authentication Fail Reason Parameter Name

## Authentication Fail Reason Parameter Value Map

After an authentication failure, malicious users can use the information you expose to gain access to the system. Map the reason for authentication failure to something generic, or something that is meaningful inside your organization.

When Authentication Fail URL is set, this property maps reasons for authentication failure to custom messages, as follows:

- **AUTHN\_BOOKKEEPING\_COOKIE\_MISSING** : The agent cannot find the authentication tracking cookie. This error can happen if the user successfully authenticates, but clicks the back button of the browser to return to the previous page.
- **NONCE\_MISSING** : The agent found the authentication tracking cookie, but it cannot find the unique identifier of the authentication request inside the cookie. This error can happen if the user successfully authenticates, but clicks the back button of the browser to return to the previous page.
- **BAD\_AUDIENCE** : The audience in the JWT did not correspond to the audience in the cookie entry. This error can happen if all agents working in a cluster do not have the same Agent Profile Name.
- **NO\_TOKEN** : The agent cannot find the session ID token.
- **TOKEN\_EXPIRED** : The agent found the session ID token, but it is past its expiry date.

- `AM_SAYS_INVALID` : The agent found the session ID token, the expiry time is correct, but AM returns that the ID token is invalid.
- `JWT_INVALID` : The agent found the session ID token, but cannot parse it.
- `EXCEPTION` : The agent found the session ID token, but threw an exception while parsing it. Alternatively, the agent cannot connect to AM to validate the ID token, maybe due to a network outage.

Specify the authentication failure reason from the preceding table as the map key, and your custom error identifier string as the value. For example:

```
org.forgerock.agents.authn.fail.reason.remapper[TOKEN_EXPIRED]=MY_ERROR_MESSAGE
```

Consider remapping all the failure reasons to a new error message, then be specific on those that hold more meaning for your environment. For example:

```
org.forgerock.agents.authn.fail.reason.remapper=ERROR
```

```
org.forgerock.agents.authn.fail.reason.remapper[AUTHN_BOOKKEEPING_COOKIE_MISSING]=BACK_BUTTON_PRESSED
```

```
org.forgerock.agents.authn.fail.reason.remapper[NONCE_MISSING]=BACK_BUTTON_PRESSED
```

To map all the authentication failure reasons to the same message, you do not need to specify a key in the property.

Property name	<code>org.forgerock.agents.authn.fail.reason.remapper</code>
Aliases	<code>org.forgerock.agents.authn.fail.reason.remapper</code> Introduced in Java Agent 5.7 <a href="#">Recognized</a> from AM 7
Function	Authentication failure
Type	Map <ul style="list-style-type: none"> <li>• Keys: failed auth reason code</li> <li>• Values: masked value</li> </ul>
Bootstrap property	No
Required property	No
Restart required	No

Local configuration file	AgentConfig.properties
AM console	Tab: Miscellaneous (from AM 7)  Title: Authentication Fail Reason Parameter Value Map

## Authentication Fail URL

---

The URL or URI to which the agent redirects the user after a failed authentication.

If this property is not set, the agent redirects the user to the URL defined in [Goto URL](#). If neither property is set, the agent returns an HTTP 400 Bad Request.

To configure the agent to send the reason for authentication failure in a named query parameter, configure [Authentication Fail Reason Parameter Name](#).

Property name	org.forgerock.agents.authn.fail.url
Aliases	org.forgerock.agents.authn.fail.url Introduced in Java Agent 5.7 <a href="#">Recognized</a> from AM 7
Function	Authentication failure
Type	String
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Miscellaneous (from AM 7)  Title: Authentication Fail URL  Legacy title: Authentication Fail Reason Url

## Goto URL

---

When [Authentication Fail URL](#) is not set, this property sets the URL or URI to which the agent redirects the user after a failed authentication. If neither property is set, the agent



returns an HTTP 400 Bad Request.

To configure the agent to send the reason for authentication failure in a named query parameter, configure Authentication Fail Reason Parameter Name.

Property name	<code>org.forgerock.agents.default.goto.url</code>
Aliases	<code>com.sun.identity.agents.config.openam.agent.default_goto_url</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 7  <code>org.forgerock.agents.default.goto.url</code> Introduced in Java Agent 5.7
Function	Authentication failure
Type	String
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Miscellaneous (from AM 7)  Title: Goto URL

## Authentication service

### AM Authentication Service Path

The path to the AM server.

Property name	<code>org.forgerock.agents.am.path</code>
Aliases	<code>com.iplanet.am.services.deploymentDescriptor</code> Introduced in Java Agent 5.0  <code>org.forgerock.agents.am.path</code> Introduced in Java Agent 5.6
Function	Authentication service, Required

Type	String
Bootstrap property	Yes
Required property	Yes - If this property is missing, the agent fails to start
Restart required	Yes - Restart the container after changing the property
Local configuration file	AgentBootstrap.properties

## Encrypting Java class

The Java class used to encrypt the agent password.

During installation, the class is set in the bootstrap properties file with the default value. The default value is `secure`; it is not recommended or necessary to change it.

Change the class only to reduce your level of encryption. To change the class, make sure that the class is available at runtime, regenerate the agent password using the agent installer, and manually edit the newly generated encrypted password into the bootstrap properties file.

Property name	<code>org.forgerock.agents.encryptor.classname</code>
Aliases	<code>org.forgerock.agents.encryptor.classname</code> Introduced in Java Agent 5.7  <code>com.iplanet.security.encryptor</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6
Function	Authentication service, Encryption, Required
Type	String
Default	<code>org.forgerock.openam.shared.security.crypto.AESWrapEncryption</code>
Bootstrap property	Yes
Required property	Yes - If this property is missing, the agent fails to start
Restart required	Yes - Restart the container after changing the property
Local configuration file	AgentBootstrap.properties

# AM Authentication Service Protocol

The protocol used by the AM server. Set to one of the following values:

- HTTP
- HTTPS

Property name	<code>org.forgerock.agents.am.protocol</code>
Aliases	<code>org.forgerock.agents.am.protocol</code> Introduced in Java Agent 5.6  <code>com.ipplanet.am.server.protocol</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6
Function	Authentication service, Required
Type	String
Bootstrap property	Yes
Required property	Yes - If this property is missing, the agent fails to start
Restart required	Yes - Restart the container after changing the property
Local configuration file	<code>AgentBootstrap.properties</code>
AM console	Tab: AM Services  Title: AM Authentication Service Protocol

# AM Authentication Service Host Name

The AM server host name.

Property name	<code>org.forgerock.agents.am.hostname</code>
Aliases	<code>com.ipplanet.am.server.host</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  <code>org.forgerock.agents.am.hostname</code> Introduced in Java Agent 5.6

Function	Authentication service, Required
Type	String
Bootstrap property	Yes
Required property	Yes - If this property is missing, the agent fails to start
Restart required	Yes - Restart the container after changing the property
Local configuration file	AgentBootstrap.properties
AM console	Tab: AM Services  Title: AM Authentication Service Host Name

## AM Authentication Service Port

The AM server port number.

Property name	org.forgerock.agents.am.port
Aliases	com.ipplanet.am.server.port Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  org.forgerock.agents.am.port Introduced in Java Agent 5.6
Function	Authentication service, Required
Type	String
Bootstrap property	Yes
Required property	Yes - If this property is missing, the agent fails to start
Restart required	Yes - Restart the container after changing the property
Local configuration file	AgentBootstrap.properties
AM console	Tab: AM Services  Title: AM Authentication Service Port

## Encryption Key

---

The key with which to encrypt the agent password.

The key is set during installation process. To change it after installation:

- Manually invoke `agentadmin` with the `--getEncryptKey` option
- Manually edit the result into the bootstrap property file, against the encryption key property
- Re-encrypt your password using `agentadmin` with the `--encrypt` option
- Manually edit the encrypted result into the bootstrap property file, against the encrypted password property

If this property is not set, the agent terminates with a configuration error.

Property name	<code>am.encryption.pwd</code>
Aliases	<code>am.encryption.pwd</code> Introduced in Java Agent 5.0
Function	Authentication service, Encryption, Required
Type	String
Bootstrap property	No
Required property	Yes - If this property is missing, the agent fails to start
Restart required	Yes - Restart the container after changing the property
Local configuration file	<code>AgentKey.properties</code>

## Encryption Digest

---

The hashing algorithm used internally by the agent.

The algorithm must be the same as that used in AM, and is set to the correct value by default. **Change this property only with extreme caution.**

Property name	<code>org.forgerock.agents.encryption.key.digest</code>
---------------	---------------------------------------------------------

Aliases	<p><code>org.forgerock.openam.encryption.key.digest</code> Introduced in Java Agent 5.0</p> <p><code>org.forgerock.agents.encryption.key.digest</code> Introduced in Java Agent 5.6</p>
Function	Authentication service, Encryption
Type	String
Default	SHA256
Bootstrap property	Yes
Required property	No
Restart required	Yes - Restart the container after changing the property
Local configuration file	<code>AgentBootstrap.properties</code>

## Client identification

### Client Hostname Header

The name of the HTTP header used to determine the hostname of a client. See also [Client IP Address Header](#).

If this property is not set, the value returned by `HttpServletRequest.getRemoteHost` is used.

Property name	<code>org.forgerock.agents.http.header.containing.remote.hostname</code>
Aliases	<p><code>org.forgerock.agents.http.header.containing.remote.hostname</code> Introduced in Java Agent 5.6</p> <p><code>com.sun.identity.agents.config.client.hostname.header</code> Introduced in Java Agent 5.0 <a href="#">Recognized</a> from AM 6</p>
Function	Client identification, Continuous security
Type	String

Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Advanced  Title: Client Hostname Header

## Client IP Validation Mode

For each authenticated request from a named web application, check that the IP address of the request satisfies one of the following acceptance criteria:

- It originates from the IP address used for first authentication.
- It has acceptable changes only, as mapped in [Client IP Validation Address Map](#)
- If the web application is not named, check the the IP address globally, for all web applications.

Property name	org.forgerock.agents.original.ip.check.mode.map
Aliases	org.forgerock.agents.original.ip.check.mode.map Introduced in Java Agent 5.8.0 <a href="#">Recognized</a> from AM 7.1
Function	Client identification
Supported settings	<b>OFF</b> IP address checking is disabled.  <b>DENY</b> An "unacceptable" IP address change triggers an HTTP 403 response.  <b>LOGOUT</b> An "unacceptable" IP address change causes the agent to invalidate the user token by calling the logout endpoint in AM and killing the user's cookies.
Default	OFF

Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Application (from AM 7.1) Title: Client IP Validation Mode

## Client IP Validation Address Map

A map of acceptable alternative values for IP addresses, or address ranges in CIDR format, that incoming requests may change to without triggering DENY or LOGOUT behaviour.

This property is used by [Client IP Validation Mode](#).

Property name	org.forgerock.agents.acceptable.ip.address.map
Aliases	org.forgerock.agents.acceptable.ip.address.map Introduced in Java Agent 5.8.0 <a href="#">Recognized</a> from AM 7.1
Function	Client identification
Type	Map <ul style="list-style-type: none"> <li>• Keys: web application</li> <li>• Values: acceptable IP addresses, comma separated, CIDR format acceptable</li> </ul>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties



AM console	Tab: Application (from AM 7.1)  Title: Client IP Validation Address Map
------------	-------------------------------------------------------------------------------

## Client IP Address Header

---

The name of the HTTP header used to determine the IP address of a client. See also [Client Hostname Header](#).

If this property is not set, the value returned by `HttpServletRequest.getRemoteAddr` is used.

Property name	<code>org.forgerock.agents.http.header.containing.ip.address</code>
Aliases	<code>com.sun.identity.agents.config.client.ip.header</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  <code>org.forgerock.agents.http.header.containing.ip.address</code> Introduced in Java Agent 5.6
Function	Client identification, Continuous security
Type	String
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Advanced  Title: Client IP Address Header

## Connection pooling

### Max HTTP Connection Count

---

When Enable Connection Pooling is `true`, this property defines the maximum number of HTTP connections allowed at any time.

Property name	<code>org.forgerock.agents.http.client.max.connections</code>
Aliases	<code>org.forgerock.agents.http.client.max.connections</code> Introduced in Java Agent 5.8.0
Function	Connection pooling
Type	Integer
Default	1000
Bootstrap property	Yes
Required property	No
Restart required	Yes - Restart the container after changing the property
Local configuration file	<code>AgentBootstrap.properties</code>
AM console	Tab: Redirect  Title: Max HTTP Connection Count

## HTTP Connection Timeout

When Enable Connection Pooling is `true`, this property defines the connection timeout in seconds.

Property name	<code>org.forgerock.agents.http.client.connection.timeout.seconds</code>
Aliases	<code>org.forgerock.agents.http.client.connection.timeout.seconds</code> Introduced in Java Agent 5.8.0
Function	Connection pooling
Type	Integer
Default	10

Bootstrap property	Yes
Required property	No
Restart required	Yes - Restart the container after changing the property
Local configuration file	AgentBootstrap.properties
AM console	Tab: Redirect Title: HTTP Connection Timeout

## Enable HTTP Connection Reuse

When [Enable Connection Pooling](#) is `true`, this property enables connection reuse.

Property name	<code>org.forgerock.agents.http.client.reuse.connections.enabled</code>
Aliases	<code>org.forgerock.agents.http.client.reuse.connections.enabled</code> Introduced in Java Agent 5.8.0
Function	Connection pooling
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>true</code>
Bootstrap property	Yes
Required property	No
Restart required	Yes - Restart the container after changing the property
Local configuration file	AgentBootstrap.properties

## Enable HTTP Connection State

This option only applies when these properties are `true`:

- [Enable Connection Pooling](#)
- [Enable HTTP Connection Reuse](#)

Set this property to `true` to change the Apache HTTP Client default behavior, and allow connection reuse.

Because the client certificate is defined at the client level, all requests to the same target share the same client certificate, so enabling this property should not be an issue.

Property name	<code>org.forgerock.agents.http.client.connection.state.enabled</code>
Aliases	<code>org.forgerock.agents.http.client.connection.state.enabled</code> Introduced in Java Agent 5.8.0
Function	Connection pooling
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>true</code>
Bootstrap property	Yes
Required property	No
Restart required	Yes - Restart the container after changing the property
Local configuration file	<code>AgentBootstrap.properties</code>

## Enable Connection Pooling

When `true`, the agent uses connection pooling. Use connection pooling to improve performance when AM is available over low bandwidth connections, or to throttle the maximum number of connections made by the agent.

When AM is available over high bandwidth connections, connection pooling can reduce performance.

Property name	<code>org.forgerock.agents.use.connection.pooling.enabled</code>
Aliases	<code>org.forgerock.agents.use.connection.pooling.enabled</code> Introduced in Java Agent 5.8.0
Function	Connection pooling

Type	Boolean: true returns true; all other strings return false .
Default	false
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties

## HTTP Socket Timeout

When Enable Connection Pooling is true , this property defines the socket timeout in seconds.

Property name	org.forgerock.agents.http.client.socket.timeout.seconds
Aliases	org.forgerock.agents.http.client.socket.timeout.seconds Introduced in Java Agent 5.8.0
Function	Connection pooling
Type	Integer
Default	10
Bootstrap property	Yes
Required property	No
Restart required	Yes - Restart the container after changing the property
Local configuration file	AgentBootstrap.properties

## Enable HTTP Retry

When Enable Connection Pooling is true , this property enables retries after failed requests.

Property name	<code>org.forgerock.agents.http.client.retry.requests.enabled</code>
Aliases	<code>org.forgerock.agents.http.client.retry.requests.enabled</code> Introduced in Java Agent 5.8.0
Function	Connection pooling
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>true</code>
Bootstrap property	Yes
Required property	No
Restart required	Yes - Restart the container after changing the property
Local configuration file	<code>AgentBootstrap.properties</code>

## Container

### Container Character Encoding

The character encoding used by the agent when encoding extended characters in the resource paths of not-enforced rules.

Property name	<code>org.forgerock.agents.container.encoding</code>
Aliases	<code>org.forgerock.agents.container.encoding</code> Introduced in Java Agent 5.9.1
Function	Container, Not-enforced
Type	String
Default	UTF-8
Bootstrap property	No
Required property	No
Restart required	No

Local configuration file	AgentConfig.properties
--------------------------	------------------------

## Container Parameter Encoding

---

The character encoding used by the agent when encoding extended characters in the HTTP query parameters of not-enforced rules.

Property name	org.forgerock.agents.container.param.encoding
Aliases	org.forgerock.agents.container.param.encoding Introduced in Java Agent 5.9.1
Function	Container, Not-enforced
Type	String
Default	ISO-8859-1
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties

## Continuous security

### Continuous Security Cookie Map

---

Maps cookie values available in inbound resource requests to entries in the environmental conditions map, which agents send to AM during policy evaluation.

Property name	org.forgerock.agents.continuous.security.cookies.map
---------------	------------------------------------------------------

Aliases	<p><code>org.forgerock.agents.continuous.security.cookies.map</code> Introduced in Java Agent 5.6</p> <p><code>org.forgerock.openam.agents.config.continuous.security.cookies</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6</p>
Function	Continuous security
Type	<p>Map</p> <ul style="list-style-type: none"> <li>• Keys: incoming cookie name</li> <li>• Values: name of entry in environment map</li> </ul>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	<p>Tab: Application</p> <p>Title: Continuous Security Cookie Map</p> <p>Legacy title: Continuous Security Cookies</p>

## Continuous Security Header Map

Maps header values in inbound resource requests to entries in the environmental conditions map, which agents send to AM during policy evaluation.

Example:

```
org.forgerock.agents.continuous.security.headers.map[User-Agent]=myUserAgentHeaderEntry
```

Property name	<code>org.forgerock.agents.continuous.security.headers.map</code>
---------------	-------------------------------------------------------------------



Aliases	<p><code>org.forgerock.agents.continuous.security.headers.map</code> Introduced in Java Agent 5.6</p> <p><code>org.forgerock.openam.agents.config.continuous.security.headers</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6</p>
Function	Continuous security
Type	<p>Map</p> <ul style="list-style-type: none"> <li>• Keys: incoming header name</li> <li>• Values: name of entry in environment map</li> </ul>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	<p>Tab: Application</p> <p>Title: Continuous Security Header Map</p> <p>Legacy title: Continuous Security Headers</p>

## Client Hostname Header

The name of the HTTP header used to determine the hostname of a client. See also [Client IP Address Header](#).

If this property is not set, the value returned by `HttpServletRequest.getRemoteHost` is used.

Property name	<code>org.forgerock.agents.http.header.containing.remote.hostname</code>
---------------	--------------------------------------------------------------------------

Aliases	<p><code>org.forgerock.agents.http.header.containing.remote.hostname</code> Introduced in Java Agent 5.6</p> <p><code>com.sun.identity.agents.config.client.hostname.header</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6</p>
Function	Client identification, Continuous security
Type	String
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	<p>Tab: Advanced</p> <p>Title: Client Hostname Header</p>

## Client IP Address Header

The name of the HTTP header used to determine the IP address of a client. See also [Client Hostname Header](#).

If this property is not set, the value returned by `HttpServletRequest.getRemoteAddr` is used.

Property name	<code>org.forgerock.agents.http.header.containing.ip.address</code>
Aliases	<p><code>com.sun.identity.agents.config.client.ip.header</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6</p> <p><code>org.forgerock.agents.http.header.containing.ip.address</code> Introduced in Java Agent 5.6</p>
Function	Client identification, Continuous security

Type	String
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Advanced Title: Client IP Address Header

## Cookie

### Maximum Decompression Size

The maximum size, in bytes, a compressed cookie is allowed to expand to when decompressed.

Property name	org.forgerock.agents.max.decompression.size.bytes
Aliases	org.forgerock.agents.max.decompression.size.bytes Introduced in Java Agent 5.10.0
Function	Cookie
Type	Integer
Default	32768
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties

### Pre-Authn and Post Data Preservation Cookie Signing

## Value

If set to a non-zero length, the value is used to generate a derived key to sign pre-authentication and POST data preservation cookies.

Property name	<code>org.forgerock.agents.cookie.signing.value</code>
Aliases	<code>org.forgerock.agents.cookie.signing.value</code> Introduced in Java Agent 5.10.0
Function	Cookie, POST data preservation, Pre-authentication
Type	String
Bootstrap property	No
Required property	No
Restart required	Yes - Restart the container after changing the property
Local configuration file	<code>AgentKey.properties</code>

## Max Age of Pre-Authentication Cookie

The maximum age in seconds of the pre-authentication cookie configured in [Pre-Authentication Cookie Name](#).

Property name	<code>org.forgerock.agents.authn.cookie.max.age.seconds</code>
Aliases	<code>org.forgerock.agents.authn.cookie.max.age.seconds</code> Introduced in Java Agent 5.6.3.0 <a href="#">Recognized</a> from AM 7
Function	Cookie, Pre-authentication
Type	Integer
Default	600
Bootstrap property	No
Required property	No

Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Global (from AM 7)  Title: Max Age of Pre-Authentication Cookie  Legacy title: Pre-Authenticated Cookie Max Age

## Load Balancer Cookie Name

---

The load balancer cookie name. Make sure that this property has the same value as the AM property `com.ipplanet.am.lbcookie.name`.

Property name	<code>org.forgerock.agents.load.balancer.cookie.name</code>
Aliases	<code>org.forgerock.agents.load.balancer.cookie.name</code>  Introduced in Java Agent 5.8.0 <u>Recognized</u> from AM 7.1
Function	Cookie
Type	String
Default	<code>amlbcookie</code>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Global (from AM 7.1)  Title: Load Balancer Cookie Name

## Enable Encoded Cookies

---

When `true`, cookies are base64-encoded.

Property name	<code>com.iplanet.am.cookie.encode</code>
Aliases	<code>com.iplanet.am.cookie.encode</code> Introduced in Java Agent 5.6 <u>Recognized</u> from AM 7
Function	Cookie
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>false</code>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: SS0 (from AM 7)  Title: Enable Encoded Cookies  Legacy title: Encode Cookies

## Enable HTTP Only Cookies

When `true`, cookies are flagged as `HTTPOnly`. Use this property to prevent scripts and third-party programs from accessing the cookies.

Property name	<code>com.sun.identity.cookie.httponly</code>
Aliases	<code>com.sun.identity.cookie.httponly</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 7
Function	Cookie
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>true</code>
Bootstrap property	No

Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: SSO (from AM 7) Title: Enable HTTP Only Cookies Legacy title: Http Only

## Pre-Authentication Cookie Name

---

The name of the pre-authentication cookie. This cookie tracks the progress of authentication with AM, and protects requests from replay attacks. It contains the following information:

- URL of the original request
- HTTP mode
- Secure ID (subsequently baked into the nonce of the returned JWT)
- Relevant ACR information
- Transaction ID
- Expiry time configured by [Max Age of Pre-Authentication Cookie](#)

(Before Java Agent 5.7), The agent creates a single cookie containing records to identify all concurrent authentication requests to AM. In environments with lots of concurrent requests, or where the protected URLs are long, the cookie can reach the maximum size supported by the browser. When this happens, new authentication requests fail and the agent issues a 403 HTTP message to the user.

(Java Agent 5.7 and later versions) The agent can optionally create a cookie for each authentication request to AM. In some environments, this creates a large number of cookies. If you have tests in your environment that make multiple requests to AM from the same browser, you may find intermittent 403 HTTP messages; browsers can limit how many cookies they handle.

Configure the cookie name as follows:

- To use one cookie for all concurrent authentication requests to AM, configure as a string. For example, `org.forgerock.agents.authn.cookie.name=cookie-name`.
- To use one cookie for each authentication request to AM, configure as `%n`, or as `%n` before, in the middle of, or after a string. When the agent creates the cookie, it translates the string `%n` into a unique identifier. For example:

- `org.forgerock.agents.authn.cookie.name=%n`
- `org.forgerock.agents.authn.cookie.name=%n-cookie-name`
- `org.forgerock.agents.authn.cookie.name=cookie-%n-name`
- `org.forgerock.agents.authn.cookie.name=cookie-name-%n`

The agent compresses and then signs the cookie.

Property name	<code>org.forgerock.agents.authn.cookie.name</code>
Aliases	<code>com.sun.identity.agents.config.cdsso.cookie.name</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 7  <code>org.forgerock.agents.authn.cookie.name</code> Introduced in Java Agent 5.6
Function	Cookie, Pre-authentication
Type	String
Default	<code>amFilterCDSSORequest</code>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Global (from AM 7)  Title: Pre-Authentication Cookie Name  Legacy title: Pre-Authenticated Cookie Name

## Post Data Preservation Cookie Name

The name of the Post Data Preservation cookie. This cookie maintains the security of the data in unauthenticated POST requests. It contains a unique one-time code which is cross-checked against the stored data making it extremely difficult for malicious actors to replay the stored data for other users.

Since Java Agent 5.10, there is the option of creating one cookie for all concurrent PDP requests, or alternatively to have one uniquely named cookie per request.



If you have tests in your environment that make multiple PDP requests to the agent, you may find intermittent failures as browsers can limit how many cookies they handle.

Configure the cookie name as follows:

- To use one cookie for all concurrent PDP requests to AM, configure as a string. For example, `org.forgerock.agents.pdp.cookie.name=cookie-name`.
- To use one cookie for each authentication request to AM, configure as `%n` before, in the middle, or after a string. When the agent creates the cookie, it substitutes `%n` for a unique identifier. For example:
  - `org.forgerock.agents.pdp.cookie.name=%n`
  - `org.forgerock.agents.pdp.cookie.name=%n-cookie-name`
  - `org.forgerock.agents.pdp.cookie.name=cookie-%n-name`
  - `org.forgerock.agents.pdp.cookie.name=cookie-name-%n`

The agent compresses and then signs the cookie.

Property name	<code>org.forgerock.agents.pdp.cookie.name</code>
Aliases	<code>org.forgerock.agents.pdp.cookie.name</code> Introduced in Java Agent 5.10.0 <u>Recognized</u> from AM 7.1
Function	Cookie, POST data preservation
Type	String
Default	PDP_Nonce
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>

## Enable Load Balancer Cookies

When `true`, the agent writes load balancer cookies each time it invokes AM.

Use this property with Load Balancer Cookie Name to improve performance. Load balancer cookies can reduce the number of calls that different AM instances make to the Core Token Service (CTS).

Because the agent invokes AM to log out a user, it creates a load-balancer cookie on logout. To remove these cookies on logout, add them to the [Reset Cookie List](#).

Property name	<code>org.forgerock.agents.load balancer.cookies.enabled</code>
Aliases	<code>org.forgerock.agents.load balancer.cookies.enabled</code> Introduced in Java Agent 5.8.0 <a href="#">Recognized</a> from AM 7.1
Function	Cookie
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>false</code>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Global (from AM 7.1)  Title: Enable Load Balancer Cookies  Legacy title: Load Balancer Cookie Enabled

## Cookie reset

## Reset Cookie List

A list of cookies to reset before redirecting the client for login, and when the client logs out. [Cookie Reset](#) must be `true`.

The agent searches for the cookie name using a case-sensitive search. If it finds a match, the cookie is reset. Otherwise, the agent searches again using a case-insensitive search. If it then finds a match, the cookie is reset and a warning is issued to the logs.

The list does not need to include the names of cookies created when [Profile Attribute Fetch Mode](#) or [Session Attribute Fetch Mode](#) has the value `HTTP_COOKIE`.

Property name	<code>org.forgerock.agents.cookie.reset.name.list</code>
Aliases	<code>org.forgerock.agents.cookie.reset.name.list</code> Introduced in Java Agent 5.6  <code>com.sun.identity.agents.config.cookie.reset.name</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6
Function	Cookie reset
Type	List
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: SS0  Title: Reset Cookie List  Legacy title: Cookies Reset Name List

## Session Attribute Fetch Mode

Map the name of an AM session attribute specified in [Session Attribute Map](#) as follows:

- NONE: Do not map
- HTTP\_HEADER: Map the to the name of an HTTP session header
- HTTP\_COOKIE: Map to the name of an HTTP cookie
- REQUEST\_ATTRIBUTE: Map to the name of an HTTP session attribute

When the value is `HTTP_COOKIE`, [Cookie Reset](#) is automatically set to `true`. Before redirecting the client for login, and when the client logs out, the agent resets profile and session attributes cookies, and cookies in the [Reset Cookie List](#).

Property name	<code>org.forgerock.agents.session.attribute.fetch.mode</code>
---------------	----------------------------------------------------------------

Aliases	<p><code>org.forgerock.agents.session.attribute.fetch.mode</code> Introduced in Java Agent 5.6</p> <p><code>com.sun.identity.agents.config.session.attribute.fetch.mode</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6</p>
Function	Attributes, Cookie reset, Session
Supported settings	<p><b>NONE</b> No AM attributes are mapped.</p> <p><b>HTTP_HEADER</b> The named AM attributes are mapped to headers in the outgoing HTTP response.</p> <p><b>REQUEST_ATTRIBUTE</b> The named AM attributes are mapped to request attributes in the outgoing HTTP response.</p> <p><b>HTTP_COOKIE</b> The named AM attributes are mapped to cookies in the outgoing HTTP response.</p>
Default	NONE
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	<p>Tab: Application</p> <p>Title: Session Attribute Fetch Mode</p>

## Cookie Reset

When `true`, the agent resets the cookies in the response before redirecting the client for login, and when the client logs out.

The agent resets the cookies listed in [Reset Cookie List](#), and cookies that store profile or session attributes (when [Profile Attribute Fetch Mode](#) or [Session Attribute Fetch Mode](#)

has the value `HTTP_COOKIE` ).

To reset cookies that store response attributes (when [Response Attribute Fetch Mode](#) has the value `HTTP_COOKIE` ), add them to the [Reset Cookie List](#).

Property name	<code>org.forgerock.agents.cookie.reset.enabled</code>
Aliases	<code>org.forgerock.agents.cookie.reset.enabled</code> Introduced in Java Agent 5.6  <code>com.sun.identity.agents.config.cookie.reset.enable</code> Introduced in Java Agent 5.0 <a href="#">Recognized</a> from AM 6
Function	Cookie reset
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>false</code>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: <code>SSO</code>  Title: <code>Cookie Reset</code>

## Reset Cookie Domain Map

Maps the cookie name specified in [Reset Cookie List](#) to a domain. After the cookie reset, the cookie is used in the domain.

Property name	<code>org.forgerock.agents.cookie.reset.domain.map</code>
---------------	-----------------------------------------------------------

Aliases	<p><code>org.forgerock.agents.cookie.reset.domain.map</code> Introduced in Java Agent 5.6</p> <p><code>com.sun.identity.agents.config.cookie.reset.domain</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6</p>
Function	Cookie reset
Type	<p>Map</p> <ul style="list-style-type: none"> <li>• Keys: cookie name</li> <li>• Values: cookie domain</li> </ul>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	<p>Tab: SS0</p> <p>Title: Reset Cookie Domain Map</p> <p>Legacy title: Cookies Reset Domain Map</p>

## Reset Cookie Path Map

Maps cookie name specified in [Reset Cookie List](#) to a path. After cookie reset, the cookie is used in the path.

Property name	<code>org.forgerock.agents.cookie.reset.path.map</code>
Aliases	<p><code>com.sun.identity.agents.config.cookie.reset.path</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6</p> <p><code>org.forgerock.agents.cookie.reset.path.map</code> Introduced in Java Agent 5.6</p>
Function	Cookie reset

Type	Map <ul style="list-style-type: none"> <li>• Keys: cookie name</li> <li>• Values: cookie path</li> </ul>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: SS0  Title: Reset Cookie Path Map  Legacy title: Cookies Reset Path Map

## Profile Attribute Fetch Mode

Map the name of an AM profile attribute specified in [Profile Attribute Map](#) as follows:

- NONE: Do not map
- HTTP\_HEADER: Map the to the name of an HTTP profile header
- HTTP\_COOKIE: Map to the name of an HTTP cookie
- REQUEST\_ATTRIBUTE: Map to the name of an HTTP profile attribute

Property name	<code>org.forgerock.agents.profile.attribute.fetch.mode</code>
Aliases	<code>com.sun.identity.agents.config.profile.attribute.fetch.mode</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  <code>org.forgerock.agents.profile.attribute.fetch.mode</code> Introduced in Java Agent 5.6
Function	Attributes, Cookie reset, Profile

Supported settings	<p><b>NONE</b> No AM attributes are mapped.</p> <p><b>HTTP_HEADER</b> The named AM attributes are mapped to headers in the outgoing HTTP response.</p> <p><b>REQUEST_ATTRIBUTE</b> The named AM attributes are mapped to request attributes in the outgoing HTTP response.</p> <p><b>HTTP_COOKIE</b> The named AM attributes are mapped to cookies in the outgoing HTTP response.</p>
Default	NONE
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	<p>Tab: Application</p> <p>Title: Profile Attribute Fetch Mode</p>

## Cross-domain single sign-on

### Transmit Cookies Securely

When `true`, all cookies written by the agent are secure. For backward compatibility, the default is `false`.

Property name	<code>org.forgerock.agents.secure.cookies.enabled</code>
---------------	----------------------------------------------------------



Aliases	<p><code>com.sun.identity.agents.config.cdss0.secure.enable</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6</p> <p><code>org.forgerock.agents.secure.cookies.enabled</code> Introduced in Java Agent 5.6</p> <p><code>com.iplanet.am.cookie.secure</code> Introduced in Java Agent 5.0</p>
Function	Cross-domain single sign-on
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>false</code>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	<p>Tab: SS0</p> <p>Title: Transmit Cookies Securely</p> <p>Legacy title: CDSS0 Secure Enable</p>

## Authentication Redirect URI

The URI the agent uses to process authentication requests.

When this property is not defined, the redirect URI is provided by AM.

When this property is defined and Location of Agent Configuration Repository is `REMOTE`, AM overwrites this property.

If OIDC authentication is being used, changing the value of this property while the agent is running prevents it from functioning. Restart the agent immediately after the value in AM is altered and the properties saved.

Property name	<code>org.forgerock.agents.authn.redirect.uri</code>
---------------	------------------------------------------------------

Aliases	<p><code>org.forgerock.agents.authn.redirect.uri</code> Introduced in Java Agent 5.6</p> <p><code>com.sun.identity.agents.config.cdssso.redirect.uri</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6</p>
Function	Cross-domain single sign-on, Required
Type	String
Bootstrap property	No
Required property	No
Restart required	Yes - Restart the container after changing the property
Local configuration file	<code>AgentConfig.properties</code>
AM console	<p>Tab: SS0</p> <p>Title: Authentication Redirect URI</p> <p>Legacy title: CDSSO Redirect URI</p>

## Cross-site scripting

### XSS Code Element List

Strings that, when found in the request, cause the agent to redirect the client to an error page.

Property name	<code>org.forgerock.agents.xss.code.element.list</code>
Aliases	<p><code>org.forgerock.agents.xss.code.element.list</code> Introduced in Java Agent 5.7</p> <p><code>com.sun.identity.agents.config.xss.code.elements</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6</p>
Function	Cross-site scripting

Type	List
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Advanced Title: XSS Code Element List Legacy title: Possible XSS code elements

## XSS Redirect URI Map

A map of web application name to URI. When a cross-site scripting attack is detected, the agent redirects to the URI specified in the map. The URI is expected to be a page (HTML, or otherwise) indicating that such an attack has been detected.

For example, to redirect clients of MyApp to /myapp/error.html, enter MyApp as the map key and /myapp/error.html as the map value.

Property name	org.forgerock.agents.xss.redirect.uri.map
Aliases	com.sun.identity.agents.config.xss.redirect.uri Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6 org.forgerock.agents.xss.redirect.uri.map Introduced in Java Agent 5.7
Function	Cross-site scripting
Type	Map <ul style="list-style-type: none"> <li>• Keys: web application</li> <li>• Values: cross site scripting URI</li> </ul>
Default	/agentapp/XSSCodeDetected.html
Bootstrap property	No

Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Advanced  Title: XSS Redirect URI Map  Legacy title: XSS detection redirect URI

## Custom login redirect

## Enable SSO Token Acceptance

Set this property as follows:

- `true` : Accept SSO tokens. Use this option when the agent and the token issuer are in the same domain, and for web applications and APIs where the backend accepts user information from SSO tokens.
- `false` : Do not accept SSO tokens; require OIDC JWTs for authentication.

During session upgrade the format of the composite advice is as follows:

- When both this property and [Enable Custom Login Mode](#) are `true`, the composite advice has the following format: ?  
authIndexType=composite\_advice&authIndexValue=<Advices Value>
- When either property is `false`, the composite advice has the following format: ?  
composite\_advice=<Advices Value>

Property name	<code>org.forgerock.agents.accept.sso.tokens.enabled</code>
Aliases	<code>org.forgerock.agents.accept.sso.tokens.enabled</code> Introduced in Java Agent 5.7.1 <a href="#">Recognized</a> from AM 7.1  <code>org.forgerock.agents.accept.sso.tokens</code> Introduced in Java Agent 5.7.1  <code>com.forgerock.agents.accept.sso.tokens</code> Introduced in Java Agent 5.7.1

Function	Custom login redirect, Login redirect, SSO cookie handling
Type	Boolean: true returns true; all other strings return false.
Default	false
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: SSO (from AM 7.1) Title: Enable SSO Token Acceptance Legacy title: Accept SSO Tokens

## OAuth Login URL List

Use this property in the default configuration (where Enable Custom Login Mode is false and AM Login URL List is empty).

Conditionally redirect unauthenticated requests based on the requested URL.

If the incoming request URL matches a domain name in this list, the agent redirects the unauthenticated request to the specified URL for login. The URL can be an AM instance, site, or a different website.

If Enable FQDN Checking is true, the agent iterates through the list of URLs until it finds an appropriate redirect URL that matches the FQDN check values. Otherwise, the agent redirects the user to the URL configured in the conditional redirect rules.

During the redirect, the agent appends the goto parameter configured in Goto Parameter Name, and a nonce parameter, to the agent's CDSSO endpoint.

Format, with no spaces between values:

```
[Domain/path] |[URL?realm=value&parameter1=value1...]
```

### ***Domain/path***

The incoming request URL:

- Domain: For example, `example.com`. The agent must match the domain and its subdomains. For example, `example.com` matches `mydomain.example.com` and `www.example.com`. Domains can also include path information, for example, `example.com/market`, but cannot specify ports.
- Subdomain: For example, `mydomain.example.com`. The agent match the domain, the subdomain, and any sub-subdomain. For example, `mydomain.example.com` matches `true.mydomain.example.com`. Subdomains can include path information, for example, `mydomain.example.com/secure`, but cannot specify ports.
- Path: For example, `/myapp`.
- No value: Nothing is specified before the `|` character and the rule applies to every incoming request.

## URL

The URL to which redirect incoming login requests. The URL may be an AM instance, an AM site, or a website other than AM.

Specify a URL in the format `protocol://FQDN[:port]/URI`, where the port is optional if it is 80 or 443. For example:

```
https://myweb.example.com/authApp/login.jsp
```

```
https://am.example.com:8443/openam/XUI/#login/
```

```
https://am.example.com:8443/openam/customlogin/login.jsp
```

If the redirection URL is not specified, the agent redirects the request to the AM instance or site specified by the following bootstrap properties:

```
org.forgerock.agents.am.protocol://org.forgerock.agents.am.hostname:org
.forgerock.agents.am.port/org.forgerock.agents.am.path
```

### **?realm=value**

The AM realm into which the agent logs the users. For example, `?realm=marketplace`.

When redirecting to AM's XUI, use an ampersand (&) instead of a question mark (?). For example,

```
https://am.example.com:8443/openam/XUI/#login/&realm=marketplace.
```

You do not need to specify the realm in the login URL if any of the following conditions is true:

- The custom login page itself sets the realm parameter, for example, because it lets the user choose it. In this case, you must ensure the custom login page always returns a realm parameter to the agent.

- The realm that the agent is logging the user into has DNS aliases configured in AM.
- AM logs the user into the realm whose DNS alias matches the incoming request URL. For example, an inbound request from the `http://marketplace.example.com` URL logs in the marketplace realm if the realm alias is set to `marketplace.example.com`.
- The users should always log in to the Top Level Realm.

### ***&parameter1=value1***

Parameters that can be added to the URL. Add as many parameters as your custom login pages need. Chain parameters with an ampersand (&), for example, `realm=value&parameter1=value1&parameter2=value2`.

### Examples

```
org.forgerock.agents.oauth.login.url.list[0]= thisdomain.com|?
realm=blue
```

```
org.forgerock.agents.oauth.login.url.list[1]= thatdomain.net|?realm=red
```

```
org.forgerock.agents.oauth.login.url.list[2]=
thatdomain.net/that/path|?realm=grey
```

Property name	<code>org.forgerock.agents.oauth.login.url.list</code>
Aliases	<code>org.forgerock.agents.oauth.login.url.list</code> Introduced in Java Agent 5.6  <code>org.forgerock.openam.agents.config.conditiona          l.login.url</code> Introduced in Java Agent 5.6 <u>Recognized from AM 6</u>
Function	Custom login redirect, Default Login Redirect, Login redirect, Login Redirect (Default)
Type	List
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>

AM console	Tab: AM Services  Title: OAuth Login URL List  Legacy title: AM Conditional Login URL
------------	---------------------------------------------------------------------------------------------------

## Enable Custom Login Mode

Set the login redirection mode, as follows:

- `false` : Use default login redirection mode. The agent can redirect requests to any AM instance supporting the `/oauth2/authorize` endpoint - by default, the AM instance specified during installation.

The `/oauth2/authorize` endpoint returns an OIDC ID token, and this is the only response the agent accepts.

Use with [OAuth Login URL List](#) to modify or redirect calls to the endpoint which provides the tokens.

- `true` : Use custom login redirection mode. The agent handles JWTs or SSO tokens as session tokens for authentication and authorization, and can can redirect login anywhere.

Use with [AM Login URL List](#) and [Legacy Login URL List](#) to modify or redirect calls.

During session upgrade, the format of the composite advice is as follows:

- When both this property and [Enable SSO Token Acceptance](#) are `true`, the composite advice has the following format: ?  
`authIndexType=composite_advice&authIndexValue=<Advices Value>`
- When either property is `false`, the composite advice has the following format: ?  
`composite_advice=<Advices Value>`

Property name	<code>org.forgerock.agents.legacy.login.enabled</code>
Aliases	<code>org.forgerock.agents.legacy.login.enabled</code> Introduced in Java Agent 5.6  <code>org.forgerock.openam.agents.config.allow.custom.login</code> Introduced in Java Agent 5.6 <a href="#">Recognized</a> from AM 7



Function	Custom login redirect, Default Login Redirect, Login redirect, Login Redirect (Default)
Type	Boolean: true returns true; all other strings return false.
Default	false
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: AM Services (from AM 7) Title: Enable Custom Login Mode Legacy title: Allow Custom Login Mode

## AM Login URL List

The URL of the login page to use for authentication.

During the redirect, the agent appends the following parameters to the agent's CDSSO endpoint:

- The goto parameter configured in [Goto Parameter Name](#)
- A nonce parameter

Use the format `URL[?realm=realm_name?parameter1=value1&...]`, where:

- URL : URL of the login page to use for authentication
- `[?realm=realm_name&parameter1=value1&...]` : Optional parameters that the agent passes to the login page, for example, the AM realm at which to authenticate.

You do not need to specify an authentication realm if any of the following conditions are true:

- The custom login page sets the realm parameter, for example, because it lets the user choose the realm.
- The user authenticates into a realm that has DNS aliases configured in AM. AM then logs the user into the realm whose DNS alias matches the incoming request URL.

For example, an inbound request from `http://marketplace.example.com` logs in the marketplace realm if the realm alias is set to `marketplace.example.com`.

- The user authenticates to the top-level realm.

This parameter can be overwritten by the custom login page if, for example, the user chooses the authentication realm.

Specify as many parameters your custom login pages require.

Example:

```
https://login.example.com/login.jsp?realm=marketplace&param1=value1
```

In some versions of AM you can configure more than one value for this property, but only the first value is honored.

Property name	<code>com.sun.identity.agents.config.login.url</code>
Aliases	<code>com.sun.identity.agents.config.login.url</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6
Function	Custom login redirect, Default Login Redirect, Login redirect, Login Redirect (Default)
Type	List
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: AM Services  Title: AM Login URL List  Legacy title: AM Login URL

## Login Reason Parameter Name

When Enable Custom Login Mode is `true`, this property specifies the name of a parameter included in calls to the custom login URL, to indicate why authentication is required. The parameter value can be used in a custom login page to provide additional feedback to the authenticating user.

If this property is specified, the agent includes a parameter named with the property value, and including one of the following values:

- NO\_TOKEN : No token present in the original request.
- TOKEN\_EXPIRED : Expiry time of the JWT was in the past.
- EXCEPTION : An unknown exception occurred, either while parsing the JWT or at some other stage of authentication.

To reduce the risk of leaking useful information, use the property Login Reason Value Map to change the strings for the above values.

For example, specifying

`org.forgerock.agents.login.reason.parameter.name=auth_reason` can cause the agent to redirect authentication to the following URL:

```
https://custom.example.com:8443/.../login_endpoint?...  
&auth_reason=TOKEN_EXPIRED&...
```

Do not enter a value that clashes with other parameters used for authentication; for example, `realm` or `goto`.

Property name	<code>org.forgerock.agents.login.reason.parameter.name</code>
Aliases	<code>org.forgerock.agents.login.reason.parameter.name</code> Introduced in Java Agent 5.7
Function	Custom login redirect, Login redirect
Type	String
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Miscellaneous (from AM 7) Title: Login Reason Parameter Name

## Legacy Login URL List

---

Adds parameters conditionally to legacy login URLs.

Format, with no spaces between values:

`domain/path|url?param1=value1&param2=value2`

### ***Domain/path***

The incoming request URL:

- Domain: For example, `example.com`. The agent must match the domain and its subdomains. For example, `example.com` matches `mydomain.example.com` and `www.example.com`. Domains can also include path information, for example, `example.com/market`, but cannot specify ports.
- Subdomain: For example, `mydomain.example.com`. The agent match the domain, the subdomain, and any sub-subdomain. For example, `mydomain.example.com` matches `true.mydomain.example.com`. Subdomains can include path information, for example, `mydomain.example.com/s6ecure`, but cannot specify ports.
- Path: For example, `/myapp`.
- No value: Nothing is specified before the `|` character and the rule applies to every incoming request.

### ***URL***

The URL to which redirect incoming login requests. The URL may be an AM instance, an AM site, or a website other than AM.

Specify a URL in the format `protocol://FQDN[:port]/URI`, where the port is optional if it is 80 or 443. For example:

`https://myweb.example.com/authApp/login.jsp`

`https://am.example.com:8443/openam/XUI/#login/`

`https://am.example.com:8443/openam/customlogin/login.jsp`

If the URL is not specified, the agent redirects the request to the AM instance or site specified by the following bootstrap properties:

`org.forgerock.agents.am.protocol://org.forgerock.agents.am.hostname:org.forgerock.agents.am.port/org.forgerock.agents.am.path`

### ***&parameter1=value1***

Parameters that can be added to the URL. Add as many parameters as your custom login pages need. Chain parameters with an `&` character, for example, `realm=value&parameter1=value1&parameter2=value2`.

### **Examples**

`org.forgerock.agents.legacy.login.url.list[0]=example.com|https://am.example.com/openam/XUI/#login&realm=customers`

```
org.forgerock.agents.legacy.login.url.list[1]=myapp.domain.com|https://login.example.com/apps/login.jsp?realm=sales
```

```
org.forgerock.agents.legacy.login.url.list[2]=sales.example.com/marketplace|?realm=marketplace
```

```
org.forgerock.agents.legacy.login.url.list[3]=|https://login.example.com/apps/login.jsp?realm=sales&isblue=true&carowner=true
```

```
org.forgerock.agents.legacy.login.url.list[4]=|?realm=sales
```

Property name	<code>org.forgerock.agents.legacy.login.url.list</code>
Aliases	<code>org.forgerock.openam.agents.config.conditional.custom.login.url</code> Introduced in Java Agent 5.6 <u>Recognized</u> from AM 7  <code>org.forgerock.agents.legacy.login.url.list</code> Introduced in Java Agent 5.6
Function	Custom login redirect, Default Login Redirect, Login redirect, Login Redirect (Default)
Type	List
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: AM Services (from AM 7)  Title: Legacy Login URL List  Legacy title: Custom Conditional Login URL

## Default Login Redirect

## OAuth Login URL List

Use this property in the default configuration (where Enable Custom Login Mode is `false` and AM Login URL List is empty).

Conditionally redirect unauthenticated requests based on the requested URL.

If the incoming request URL matches a domain name in this list, the agent redirects the unauthenticated request to the specified URL for login. The URL can be an AM instance, site, or a different website.

If Enable FQDN Checking is `true`, the agent iterates through the list of URLs until it finds an appropriate redirect URL that matches the FQDN check values. Otherwise, the agent redirects the user to the URL configured in the conditional redirect rules.

During the redirect, the agent appends the goto parameter configured in Goto Parameter Name, and a nonce parameter, to the agent's CDSSO endpoint.

Format, with no spaces between values:

```
[Domain/path] | [URL?realm=value&parameter1=value1...]
```

### ***Domain/path***

The incoming request URL:

- **Domain:** For example, `example.com`. The agent must match the domain and its subdomains. For example, `example.com` matches `mydomain.example.com` and `www.example.com`. Domains can also include path information, for example, `example.com/market`, but cannot specify ports.
- **Subdomain:** For example, `mydomain.example.com`. The agent match the domain, the subdomain, and any sub-subdomain. For example, `mydomain.example.com` matches `true.mydomain.example.com`. Subdomains can include path information, for example, `mydomain.example.com/secure`, but cannot specify ports.
- **Path:** For example, `/myapp`.
- **No value:** Nothing is specified before the `|` character and the rule applies to every incoming request.

### ***URL***

The URL to which redirect incoming login requests. The URL may be an AM instance, an AM site, or a website other than AM.

Specify a URL in the format `protocol://FQDN[:port]/URI`, where the port is optional if it is 80 or 443. For example:

```
https://myweb.example.com/authApp/login.jsp
```

```
https://am.example.com:8443/openam/XUI/#login/
```

```
https://am.example.com:8443/openam/customlogin/login.jsp
```

If the redirection URL is not specified, the agent redirects the request to the AM instance or site specified by the following bootstrap properties:

```
org.forgerock.agents.am.protocol://org.forgerock.agents.am.hostname:org
.forgerock.agents.am.port/org.forgerock.agents.am.path
```

### **?realm=value**

The AM realm into which the agent logs the users. For example, ?  
realm=marketplace .

When redirecting to AM's XUI, use an ampersand (&) instead of a question mark (?).  
For example,

```
https://am.example.com:8443/openam/XUI/#login/&realm=marketplace .
```

You do not need to specify the realm in the login URL if any of the following  
conditions is true:

- The custom login page itself sets the realm parameter, for example, because it lets the user choose it. In this case, you must ensure the custom login page always returns a realm parameter to the agent.
- The realm that the agent is logging the user into has DNS aliases configured in AM.
- AM logs the user into the realm whose DNS alias matches the incoming request URL. For example, an inbound request from the `http://marketplace.example.com` URL logs in the marketplace realm if the realm alias is set to `marketplace.example.com`.
- The users should always log in to the Top Level Realm.

### **&parameter1=value1**

Parameters that can be added to the URL. Add as many parameters as your custom login pages need. Chain parameters with an ampersand (&), for example,  
realm=value&parameter1=value1&parameter2=value2 .

### Examples

```
org.forgerock.agents.oauth.login.url.list[0]= thisdomain.com|?
realm=blue
```

```
org.forgerock.agents.oauth.login.url.list[1]= thatdomain.net|?realm=red
```

```
org.forgerock.agents.oauth.login.url.list[2]=
thatdomain.net/that/path|?realm=grey
```

Property name	org.forgerock.agents.oauth.login.url.list
---------------	-------------------------------------------

Aliases	<p><code>org.forgerock.agents.oauth.login.url.list</code> Introduced in Java Agent 5.6</p> <p><code>org.forgerock.openam.agents.config.conditional.login.url</code> Introduced in Java Agent 5.6 <u>Recognized</u> from AM 6</p>
Function	Custom login redirect, Default Login Redirect, Login redirect, Login Redirect (Default)
Type	List
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	<p>Tab: AM Services</p> <p>Title: OAuth Login URL List</p> <p>Legacy title: AM Conditional Login URL</p>

## Enable Custom Login Mode

Set the login redirection mode, as follows:

- `false` : Use default login redirection mode. The agent can redirect requests to any AM instance supporting the `/oauth2/authorize` endpoint - by default, the AM instance specified during installation.

The `/oauth2/authorize` endpoint returns an OIDC ID token, and this is the only response the agent accepts.

Use with [OAuth Login URL List](#) to modify or redirect calls to the endpoint which provides the tokens.

- `true` : Use custom login redirection mode. The agent handles JWTs or SSO tokens as session tokens for authentication and authorization, and can can redirect login anywhere.

Use with [AM Login URL List](#) and [Legacy Login URL List](#) to modify or redirect calls.



During session upgrade, the format of the composite advice is as follows:

- When both this property and Enable SSO Token Acceptance are true, the composite advice has the following format: ?  
authIndexType=composite\_advice&authIndexValue=<Advices Value>
- When either property is false, the composite advice has the following format: ?  
composite\_advice=<Advices Value>

Property name	org.forgerock.agents.legacy.login.enabled
Aliases	org.forgerock.agents.legacy.login.enabled Introduced in Java Agent 5.6  org.forgerock.openam.agents.config.allow.custom.login Introduced in Java Agent 5.6 <u>Recognized</u> from AM 7
Function	Custom login redirect, Default Login Redirect, Login redirect, Login Redirect (Default)
Type	Boolean: true returns true; all other strings return false.
Default	false
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: AM Services (from AM 7)  Title: Enable Custom Login Mode  Legacy title: Allow Custom Login Mode

## AM Login URL List

The URL of the login page to use for authentication.

During the redirect, the agent appends the following parameters to the agent's CDSSO endpoint:

- The goto parameter configured in Goto Parameter Name
- A nonce parameter

Use the format `URL[?realm=realm_name?parameter1=value1&...]` , where:

- URL : URL of the login page to use for authentication
- `[?realm=realm_name&parameter1=value1&...]` : Optional parameters that the agent passes to the login page, for example, the AM realm at which to authenticate.

You do not need to specify an authentication realm if any of the following conditions are true:

- The custom login page sets the realm parameter, for example, because it lets the user choose the realm.
- The user authenticates into a realm that has DNS aliases configured in AM. AM then logs the user into the realm whose DNS alias matches the incoming request URL. For example, an inbound request from `http://marketplace.example.com` logs in the marketplace realm if the realm alias is set to `marketplace.example.com`.
- The user authenticates to the top-level realm.

This parameter can be overwritten by the custom login page if, for example, the user chooses the authentication realm.

Specify as many parameters your custom login pages require.

Example:

`https://login.example.com/login.jsp?realm=marketplace&param1=value1`

In some versions of AM you can configure more than one value for this property, but only the first value is honored.

Property name	<code>com.sun.identity.agents.config.login.url</code>
Aliases	<code>com.sun.identity.agents.config.login.url</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6
Function	Custom login redirect, Default Login Redirect, Login redirect, Login Redirect (Default)
Type	List
Bootstrap property	No
Required property	No

Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: AM Services  Title: AM Login URL List  Legacy title: AM Login URL

## Legacy Login URL List

---

Adds parameters conditionally to legacy login URLs.

Format, with no spaces between values:

domain/path|url?param1=value1&param2=value2

### ***Domain/path***

The incoming request URL:

- Domain: For example, `example.com`. The agent must match the domain and its subdomains. For example, `example.com` matches `mydomain.example.com` and `www.example.com`. Domains can also include path information, for example, `example.com/market`, but cannot specify ports.
- Subdomain: For example, `mydomain.example.com`. The agent match the domain, the subdomain, and any sub-subdomain. For example, `mydomain.example.com` matches `true.mydomain.example.com`. Subdomains can include path information, for example, `mydomain.example.com/s6ecure`, but cannot specify ports.
- Path: For example, `/myapp`.
- No value: Nothing is specified before the `|` character and the rule applies to every incoming request.

### ***URL***

The URL to which redirect incoming login requests. The URL may be an AM instance, an AM site, or a website other than AM.

Specify a URL in the format `protocol://FQDN[:port]/URI`, where the port is optional if it is 80 or 443. For example:

`https://myweb.example.com/authApp/login.jsp`

`https://am.example.com:8443/openam/XUI/#login/`

`https://am.example.com:8443/openam/customlogin/login.jsp`

If the URL is not specified, the agent redirects the request to the AM instance or site specified by the following bootstrap properties:

```
org.forgerock.agents.am.protocol://org.forgerock.agents.am.hostname:org.forgerock.agents.am.port/org.forgerock.agents.am.path
```

### **&parameter1=value1**

Parameters that can be added to the URL. Add as many parameters as your custom login pages need. Chain parameters with an & character, for example, realm=value&parameter1=value1&parameter2=value2 .

### Examples

```
org.forgerock.agents.legacy.login.url.list[0]=example.com|https://am.example.com/openam/XUI/#login&realm=customers
```

```
org.forgerock.agents.legacy.login.url.list[1]=myapp.domain.com|https://login.example.com/apps/login.jsp?realm=sales
```

```
org.forgerock.agents.legacy.login.url.list[2]=sales.example.com/marketplace|?realm=marketplace
```

```
org.forgerock.agents.legacy.login.url.list[3]=|https://login.example.com/apps/login.jsp?realm=sales&isblue=true&carowner=true
```

```
org.forgerock.agents.legacy.login.url.list[4]=|?realm=sales
```

Property name	org.forgerock.agents.legacy.login.url.list
Aliases	org.forgerock.openam.agents.config.conditional.custom.login.url Introduced in Java Agent 5.6 <u>Recognized</u> from AM 7  org.forgerock.agents.legacy.login.url.list Introduced in Java Agent 5.6
Function	Custom login redirect, Default Login Redirect, Login redirect, Login Redirect (Default)
Type	List
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties

AM console	Tab: AM Services (from AM 7)  Title: Legacy Login URL List  Legacy title: Custom Conditional Login URL
------------	--------------------------------------------------------------------------------------------------------------------

## Deprecated

### Debug File Rotation Size (deprecated)

Previously used to say when to rotate the log files based on file size. This should now be specified in the agent-logback.xml file in the agent config directory.

Default: Empty

Property name	<code>org.forgerock.agents.debug.rotation.size.bytes</code>
Aliases	<code>org.forgerock.agents.debug.rotation.size.bytes</code> Introduced in Java Agent 5.7  <code>org.forgerock.openam.debug.rotation.maxsize</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 7
Function	Deprecated
Type	String
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Global (from AM 7)  Title: Debug File Rotation Size (deprecated)

### Log File Directory (deprecated)

Previously used to specify where the log files were written. This should now be specified in the agent-logback.xml file in the agent config directory.

Property name	<code>com.iplanet.services.debug.directory</code>
Aliases	<code>com.iplanet.services.debug.directory</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 7
Function	Deprecated
Type	String
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>

## Debug File Rotation Suffix (deprecated)

Previously used as the suffix for the log file name during rotation. This should now be specified in the agent-logback.xml file in the agent config directory.

Default: Empty

Property name	<code>org.forgerock.agents.debug.suffix</code>
Aliases	<code>org.forgerock.openam.debug.suffix</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 7  <code>org.forgerock.agents.debug.suffix</code> Introduced in Java Agent 5.7
Function	Deprecated
Type	String
Bootstrap property	No
Required property	No
Restart required	No

Local configuration file	AgentConfig.properties
AM console	Tab: Global (from AM 7)  Title: Debug File Rotation Suffix (deprecated)

## Debug File Rotation Retention Count (deprecated)

Previously used to define the number of retained log files. This should now be specified in the agent-logback.xml file in the agent config directory.

Property name	org.forgerock.agents.debug.retention.count
Aliases	org.forgerock.agents.debug.retention.count Introduced in Java Agent 5.7 <u>Recognized</u> from AM 7
Function	Deprecated
Type	String
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Global (from AM 7)  Title: Debug File Rotation Retention Count (deprecated)

## Debug File Rotation Time (deprecated)

Previously used to say when to rotate the log files based on time. This should now be specified in the agent-logback.xml file in the agent config directory.

Default: Empty

Property name	org.forgerock.agents.debug.rotation.time.minutes
---------------	--------------------------------------------------

Aliases	<p><code>org.forgerock.openam.debug.rotation</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 7</p> <p><code>org.forgerock.agents.debug.rotation.time.minutes</code> Introduced in Java Agent 5.7</p>
Function	Deprecated
Type	String
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	<p>Tab: Global (from AM 7)</p> <p>Title: Debug File Rotation Time (deprecated)</p>

## Debug File Rotation Prefix (deprecated)

Previously used as the prefix for the log file name. This should now be specified in the `agent-logback.xml` file in the agent config directory.

Default: Empty

Property name	<code>org.forgerock.agents.debug.prefix</code>
Aliases	<p><code>org.forgerock.openam.debug.prefix</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 7</p> <p><code>org.forgerock.agents.debug.prefix</code> Introduced in Java Agent 5.7</p>
Function	Deprecated
Type	String
Bootstrap property	No



Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Global (from AM 7) Title: Debug File Rotation Prefix (deprecated)

## Encryption

### Encrypting Java class

The Java class used to encrypt the agent password.

During installation, the class is set in the bootstrap properties file with the default value. The default value is secure; it is not recommended or necessary to change it.

Change the class only to reduce your level of encryption. To change the class, make sure that the class is available at runtime, regenerate the agent password using the agent installer, and manually edit the newly generated encrypted password into the bootstrap properties file.

Property name	org.forgerock.agents.encryptor.classname
Aliases	org.forgerock.agents.encryptor.classname Introduced in Java Agent 5.7  com.iplanet.security.encryptor Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6
Function	Authentication service, Encryption, Required
Type	String
Default	org.forgerock.openam.shared.security.crypto.AESWrapEncryption
Bootstrap property	Yes
Required property	Yes - If this property is missing, the agent fails to start
Restart required	Yes - Restart the container after changing the property

Local configuration file	AgentBootstrap.properties
--------------------------	---------------------------

## Encryption Key

---

The key with which to encrypt the agent password.

The key is set during installation process. To change it after installation:

- Manually invoke `agentadmin` with the `--getEncryptKey` option
- Manually edit the result into the bootstrap property file, against the encryption key property
- Re-encrypt your password using `agentadmin` with the `--encrypt` option
- Manually edit the encrypted result into the bootstrap property file, against the encrypted password property

If this property is not set, the agent terminates with a configuration error.

Property name	<code>am.encrypted.password</code>
Aliases	<code>am.encrypted.password</code> Introduced in Java Agent 5.0
Function	Authentication service, Encryption, Required
Type	String
Bootstrap property	No
Required property	Yes - If this property is missing, the agent fails to start
Restart required	Yes - Restart the container after changing the property
Local configuration file	<code>AgentKey.properties</code>

## Encryption Digest

---

The hashing algorithm used internally by the agent.

The algorithm must be the same as that used in AM, and is set to the correct value by default. **Change this property only with extreme caution.**

Property name	<code>org.forgerock.agents.encrypted.password.digest</code>
---------------	-------------------------------------------------------------

Aliases	<p><code>org.forgerock.openam.encryption.key.digest</code> Introduced in Java Agent 5.0</p> <p><code>org.forgerock.agents.encryption.key.digest</code> Introduced in Java Agent 5.6</p>
Function	Authentication service, Encryption
Type	String
Default	SHA256
Bootstrap property	Yes
Required property	No
Restart required	Yes - Restart the container after changing the property
Local configuration file	<code>AgentBootstrap.properties</code>

## Fragment

### Fragment Relay URI

A URI to act as a dummy endpoint within the agent for capturing URL fragments in unauthenticated requests:

- When empty, unauthenticated requests to a URL with a fragment are authenticated and then redirected to the URL without the fragment.
- When set, unauthenticated requests are authenticated and then redirected to the requested URL. An extra redirect is incurred for all unauthenticated requests, to capture and process the URL fragment.

Use a dummy URI within the agent web application, such as `/agentapp/pre-authn-fragment-capture`. Avoid dummy URIs used for other purposes.

Property name	<code>org.forgerock.agents.authn.fragment.relay.uri</code>
Aliases	<p><code>org.forgerock.agents.authn.fragment.relay.uri</code> Introduced in Java Agent 5.7</p> <p><u>Recognized</u> from AM 7</p>
Function	Fragment
Type	String

Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Advanced (from AM 7) Title: Fragment Relay URI

## Fully qualified domain name

### Default FQDN

The default FQDN to use when the agent cannot find a match in the [FQDN Map](#). If this property is not defined, [Enable FQDN Checking](#) is set to `false`.

Use this property to map requests with virtual, invalid, or partial hostnames to URLs that contain a correct FQDN.

Property name	<code>org.forgerock.agents.fqdn.default</code>
Aliases	<code>org.forgerock.agents.fqdn.default</code> Introduced in Java Agent 5.6  <code>com.sun.identity.agents.config.fqdn.default</code> Introduced in Java Agent 5.0 <a href="#">Recognized</a> from AM 6
Function	Fully qualified domain name
Type	String
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties

AM console	Tab: Global  Title: Default FQDN  Legacy title: FQDN Default
------------	--------------------------------------------------------------------------

## FQDN Map

Key:Value maps of incoming hostname to outgoing domain. Use this property to map requests with virtual, invalid, or partial hostnames to a correct FQDN.

This property requires [Enable FQDN Checking](#) to be `true`, and [Default FQDN](#) to be set to suitable default FQDN.

The agent maintains the following maps, which can each contain multiple entries:

- Map 1, where the key is the incoming hostname without wildcards, and the value is the outgoing domain.
- Map 2, where the key is the incoming hostname with wildcards (\* or ?), and the value is the outgoing domain.

Map keys are case insensitive. Incoming hostnames are converted to lowercase before the agent maps them, and the agent automatically converts uppercase keys and values to lowercase before mapping.

The agent maps FQDNs as follows:

1. Searches map 1 for the incoming hostname. If there is a match, the agent redirects the request to the mapped value.
2. Searches map 2 for a pattern that matches the incoming hostname, iterating through the entries in random order. If there is a match, the agent redirects the request to the mapped value.
3. Redirects the request to the hostname in [Default FQDN](#).

Examples:

```
org.forgerock.agents.fqdn.map[agent]=agent.localtest.me
```

```
org.forgerock.agents.fqdn.map[agent.virtualtest.me]=virtual-  
host.localtest.me
```

```
org.forgerock.agents.fqdn.map[agent-*.localtest.me]=agent.localtest.me
```

Property name	<code>org.forgerock.agents.fqdn.map</code>
---------------	--------------------------------------------

Aliases	<code>com.sun.identity.agents.config.fqdn.mapping</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  <code>org.forgerock.agents.fqdn.map</code> Introduced in Java Agent 5.6
Function	Fully qualified domain name
Type	Map <ul style="list-style-type: none"> <li>• Keys: canonical name of invalid server</li> <li>• Values: canonical name of valid server</li> </ul>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Global  Title: FQDN Map  Legacy title: FQDN Virtual Host Map

## Enable FQDN Checking

When `true`, the agent compares the hostname of each request to the mappings in FQDN Map.

- If it finds a match, it transforms the request URL to the mapped URL.
- If it doesn't find a match, it transforms the request URL to the value in Default FQDN.

If Default FQDN is not set, this property is automatically set to `false`.

Property name	<code>org.forgerock.agents.fqdn.check.enabled</code>
---------------	------------------------------------------------------

Aliases	<p><code>com.sun.identity.agents.config.fqdn.check.enabled</code></p> <p>Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6</p> <p><code>org.forgerock.agents.fqdn.check.enabled</code> Introduced in Java Agent 5.6</p>
Function	Fully qualified domain name
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>true</code>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	<p>Tab: Global</p> <p>Title: Enable FQDN Checking</p> <p>Legacy title: FQDN Check</p>

## Global

### Enable Prometheus Monitoring

When `true`, the agent is monitored by Prometheus. When `false`, the agent is not monitored by Prometheus.

Property name	<code>org.forgerock.agents.prometheus.monitoring.enabled</code>
Aliases	<p><code>org.forgerock.agents.prometheus.monitoring.enabled</code></p> <p>Introduced in Java Agent 5.6</p>
Function	Global

Type	Boolean: true returns true; all other strings return false.
Default	true
Bootstrap property	Yes
Required property	No
Restart required	No
Local configuration file	AgentBootstrap.properties
AM console	Tab: Monitoring Title: Enable Prometheus Monitoring

## HTTP 302 Redirect Data

When Enable HTTP 302 Redirects, this property specifies the data to return instead of an HTTP 302 Redirect.

Property name	org.forgerock.agents.302.redirect.http.data
Aliases	org.forgerock.agents.302.redirect.http.data Introduced in Java Agent 5.8.0 <u>Recognized</u> from AM 7.1
Function	Global
Type	String
Default	{ "redirect": { "requestUri": "%REQUEST_URI%", "requestUrl": "%REQUEST_URL%", "targetUrl": "%TARGET%" } }
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Miscellaneous (from AM 7.1) Title: HTTP 302 Redirect Data



## HTTP 302 Redirect Not-Enforced List

---

When [Enable HTTP 302 Redirects](#), this property specifies a list of URLs for which HTTP 302 Redirect does not take place.

If a request matches an entry in the list, HTTP 302 Redirect does not take place for that request, and the agent returns a block of configurable JSON.

Property name	<code>org.forgerock.agents.config.json.url</code>
Aliases	<code>org.forgerock.agents.config.json.url</code> Introduced in Java Agent 5.8.0  <code>org.forgerock.agents.302.redirect.ner.list</code> Introduced in Java Agent 5.8.0 <a href="#">Recognized</a> from AM 7.1
Function	Global
Type	List
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Miscellaneous (from AM 7.1)  Title: HTTP 302 Redirect Not-Enforced List  Legacy title: HTTP 302 Redirect Not Enforced List

## HTTP 302 Redirect Replacement HTTP Status Code

---

When [Enable HTTP 302 Redirects](#) is `false`, this property specifies the HTTP code to return instead of an HTTP 302 (Redirect).

Property name	<code>org.forgerock.agents.302.redirect.http.status.code</code>
---------------	-----------------------------------------------------------------

Aliases	<p><code>org.forgerock.agents.302.redirect.http.status.code</code>  Introduced in Java Agent 5.8.0  <u>Recognized</u> from AM 7.1</p> <p><code>org.forgerock.agents.config.json.response.code</code>  Introduced in Java Agent 5.8.0</p>
Function	Global
Type	Integer
Default	200
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	<p>Tab: Miscellaneous (from AM 7.1)</p> <p>Title: HTTP 302 Redirect Replacement HTTP Status Code</p> <p>Legacy title: HTTP 302 Redirect Replacement HTTP Code</p>

## Goto Parameter Name

Renames the `goto` parameter. During redirection, the agent appends the requested URL to the named parameter.

Use this property when your web application requires a parameter other than `goto`.

In the following example, the parameter is renamed to `goto2`:

```
com.sun.identity.agents.config.redirect.param=goto2
```

The redirection URL becomes like this:

```
https://www.example.com:8443/accessDenied.html?
goto2=http%3A%2F%www.example.com%3A8020%managers%2Findex.jsp
```

The URL appended to the `goto2` parameter is the URL that the user tried to access when the agent redirected the request to the `accessDenied.html` page, configured with [Access Denied URI Map](#).

Property name	<code>com.sun.identity.agents.config.redirect.param</code>
Aliases	<code>com.sun.identity.agents.config.redirect.param</code> Introduced in Java Agent 5.0 <a href="#">Recognized</a> from AM 6
Function	Global
Type	String
Default	<code>goto</code>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Miscellaneous  Title: Goto Parameter Name

## HTTP 302 Redirect Content Type

When [Enable HTTP 302 Redirects](#), this property specifies the content type of the data to return instead of an HTTP 302 Redirect.

Property name	<code>org.forgerock.agents.302.redirect.http.content.type</code>
Aliases	<code>org.forgerock.agents.302.redirect.http.content.type</code> Introduced in Java Agent 5.8.0 <a href="#">Recognized</a> from AM 7.1
Function	Global
Type	String
Default	<code>application/json</code>

Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Miscellaneous (from AM 7.1) Title: HTTP 302 Redirect Content Type

## HTTP 302 Redirect Invert Not-Enforced List

When Enable HTTP 302 Redirects is `false`, and this property is `true`, the agent inverts the meaning of HTTP 302 Redirect Not-Enforced List, so that it specifies a list of URLs for which HTTP 302 Redirect does take place.

Property name	<code>org.forgerock.agents.config.json.url.invert</code>
Aliases	<code>org.forgerock.agents.config.json.url.invert</code> Introduced in Java Agent 5.8.0  <code>org.forgerock.agents.302.redirect.invert.enabled</code> Introduced in Java Agent 5.8.0 <u>Recognized</u> from AM 7.1
Function	Global
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>false</code>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties

AM console	Tab: Miscellaneous (from AM 7.1)  Title: HTTP 302 Redirect Invert Not-Enforced List
------------	-------------------------------------------------------------------------------------------

## Enable HTTP 302 Redirects

Controls how the agent handles redirects, as follows:

- `true` : HTTP 302 Redirects are enabled. When an unauthenticated request is made, and not-enforced rules do not apply, the agent returns an HTTP 302 code to redirect the user to an authentication endpoint.
- `false` : HTTP 302 Redirects are disabled. When an unauthenticated request is made, the agent returns a block of configurable JSON that can be intercepted.

The returned HTTP code, content type, and data is configured by the following properties

- [HTTP 302 Redirect Replacement HTTP Status Code](#)
- [HTTP 302 Redirect Content Type](#)
- [HTTP 302 Redirect Data](#)

Lists of URLs in a `not-enforced` rule style, for which the data is produced are configured by the following properties

- [HTTP 302 Redirect Not-Enforced List](#)
- [HTTP 302 Redirect Invert Not-Enforced List](#)

Use this option when it is difficult to handle 302, for example, when the agent is accessed by a JavaScript application, or by something other than a browser.

Property name	<code>org.forgerock.agents.302.redirects.enabled</code>
Aliases	<code>org.forgerock.agents.302.redirects.enabled</code> Introduced in Java Agent 5.8.0 <a href="#">Recognized</a> from AM 7.1
Function	Global
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>true</code>

Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Miscellaneous (from AM 7.1) Title: Enable HTTP 302 Redirects Legacy title: HTTP 302 Redirects Enabled

## Legacy support

### Enable Legacy Support Handlers (deprecated)

A flag to enable or disable the inbound and outbound legacy support handlers within the agent.

Property name	<code>org.forgerock.agents.legacy.support.enabled</code>
Deprecated in	5.6
Aliases	<code>com.sun.identity.agents.config.legacy.support.enable</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  <code>org.forgerock.agents.legacy.support.enabled</code> Introduced in Java Agent 5.6
Function	Legacy support
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>false</code>
Bootstrap property	No
Required property	No
Restart required	No

Local configuration file	AgentConfig.properties
AM console	Tab: Miscellaneous  Title: Enable Legacy Support Handlers  Legacy title: Legacy User Agent Support Enable

## Legacy User Agent Redirect URI (deprecated)

A URI that triggers the inbound legacy user agent task handler to see if the incoming request is from a legacy agent.

Property name	org.forgerock.agents.legacy.redirect.uri
Deprecated in	5.6
Aliases	com.sun.identity.agents.config.legacy.redirect.uri Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  org.forgerock.agents.legacy.redirect.uri Introduced in Java Agent 5.6
Function	Legacy support
Type	String
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Miscellaneous  Title: Legacy User Agent Redirect URI

## Legacy User Agent List (deprecated)

A list of legacy user agents.

Property name	<code>org.forgerock.agents.legacy.user.agent.list</code>
Deprecated in	5.6
Aliases	<code>com.sun.identity.agents.config.legacy.user.agent</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  <code>org.forgerock.agents.legacy.user.agent.list</code> Introduced in Java Agent 5.6
Function	Legacy support
Type	List
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Miscellaneous  Title: Legacy User Agent List

## Locale

### Locale Country

The agent country. Changing this has no effect.

Property name	<code>org.forgerock.agents.locale.country</code>
Aliases	<code>org.forgerock.agents.locale.country</code> Introduced in Java Agent 5.6  <code>com.sun.identity.agents.config.locale.country</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6
Function	Locale
Type	String



Default	US
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Miscellaneous Title: Locale Country

## Locale Language

The agent language. Changing this has no effect.

Property name	<code>org.forgerock.agents.locale.language</code>
Aliases	<code>org.forgerock.agents.locale.language</code> Introduced in Java Agent 5.6  <code>com.sun.identity.agents.config.locale.language</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6
Function	Locale
Type	String
Default	en
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Miscellaneous Title: Locale Language

## Login

### Enable Redirect to AM Success URL

---

When `true`, the agent redirects to the success URL specified in the AM service, if any. If no success URL is specified in AM, the agent redirects to the original requested URL, if any.

When `false`, the agent redirects to the requested URL, if any.

Property name	<code>org.forgerock.agents.authn.success.redirect.session.url.enabled</code>
Aliases	<code>org.forgerock.agents.authn.success.redirect.session.url.enabled</code> Introduced in Java Agent 5.6.3.0 <u>Recognized</u> from AM 7
Function	Login
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>false</code>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: AM Services (from AM 7) Title: Enable Redirect to AM Success URL Legacy title: Redirect to AM's Success URL

### Login Attempt Limit

---

When the value of this property is greater than zero, it defines the maximum number of failed login attempts allowed during a browser session. After this number, the agent blocks requests from the user.

Specify a value greater than zero. For example, if the property is set to 3, the agent blocks the fourth login request.

Use this property to mitigate the risk of brute force attacks.

Property name	<code>org.forgerock.agents.login.attempt.limit.count</code>
Aliases	<code>org.forgerock.agents.login.attempt.limit.count</code> Introduced in Java Agent 5.6  <code>com.sun.identity.agents.config.login.attempt.limit</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6
Function	Login
Type	Integer
Default	0
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Global  Title: Login Attempt Limit

## Authentication Exchange Cookie Name

A cookie name that will be used by the authentication exchange endpoint. The value is empty by default, and the endpoint is not able to examine cookie values.

Property name	<code>org.forgerock.agents.authn.exchange.cookie.name</code>
Aliases	<code>org.forgerock.agents.authn.exchange.cookie.name</code> Introduced in Java Agent 5.7

Function	Login
Type	String
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: SSO (from AM 7) Title: Authentication Exchange Cookie Name

## Login Attempt Limit Cookie Name

The name of the cookie used to record the number of login attempts.

Property name	<code>org.forgerock.agents.login.counter.cookie.name</code>
Aliases	<code>com.sun.identity.agents.config.login.counter.name</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 7  <code>org.forgerock.agents.login.counter.cookie.name</code> Introduced in Java Agent 5.6
Function	Login
Type	String
Default	<code>amFilterParam</code>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties

AM console	Tab: Global (from AM 7) Title: Login Attempt Limit Cookie Name
------------	-------------------------------------------------------------------

## Login Reason Value Map

When Login Reason Parameter Name is set, this property specifies alternative strings to use for the supported values. For example:

Consider the example where Login Reason Parameter Name is set to `auth_reason`, and this property is set as follows:

```
org.forgerock.agents.login.reason.map[NO_TOKEN]=notoken
```

```
org.forgerock.agents.login.reason.map[TOKEN_EXPIRED]=expired
```

```
org.forgerock.agents.login.reason.map[EXCEPTION]=exception
```

The agent redirects authentication to the following URL:

```
https://custom.example.com:8443/.../login_endpoint?...  
&auth_reason=notoken&...
```

Property name	<code>org.forgerock.agents.login.reason.remapper</code>
Aliases	<code>org.forgerock.agents.login.reason.remapper</code> Introduced in Java Agent 5.7  <code>org.forgerock.agents.login.reason.map</code> Introduced in Java Agent 5.7 <u>Recognized</u> from AM 7
Function	Login
Type	Map <ul style="list-style-type: none"> <li>Keys: failed login reason code</li> <li>Values: masked value</li> </ul>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>

AM console	Tab: Miscellaneous (from AM 7)  Title: Login Reason Value Map
------------	---------------------------------------------------------------------

## Redirect Attempt Limit

When the value of this property is greater than zero, it defines the maximum number of redirects allowed for a browser session. After this number, the agent blocks the request.

Specify a value greater than zero. For example, if the property is set to 3, then the agent blocks the request on the fourth redirect.

Use this property to mitigate the risk of infinite redirection loops.

Property name	<code>org.forgerock.agents.redirect.attempt.limit</code>
Aliases	<code>org.forgerock.agents.redirect.attempt.limit</code> Introduced in Java Agent 5.6  <code>com.sun.identity.agents.config.redirect.attempt.limit</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6
Function	Login
Type	Integer
Default	0
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Global  Title: Redirect Attempt Limit

## Authentication Exchange URI

This property allows the administrator to enable an endpoint to facilitate the exchange of SSO tokens for OIDC JWTs. The value is empty by default and thus the endpoint is not accessible.

Property name	<code>org.forgerock.agents.authn.exchange.uri</code>
Aliases	<code>org.forgerock.agents.authn.exchange.uri</code> Introduced in Java Agent 5.7 <u>Recognized</u> from AM 7
Function	Login
Type	String
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: SSO (from AM 7)  Title: Authentication Exchange URI

## Login Redirect (Default)

## OAuth Login URL List

Use this property in the default configuration (where Enable Custom Login Mode is `false` and AM Login URL List is empty).

Conditionally redirect unauthenticated requests based on the requested URL.

If the incoming request URL matches a domain name in this list, the agent redirects the unauthenticated request to the specified URL for login. The URL can be an AM instance, site, or a different website.

If Enable FQDN Checking is `true`, the agent iterates through the list of URLs until it finds an appropriate redirect URL that matches the FQDN check values. Otherwise, the agent redirects the user to the URL configured in the conditional redirect rules.

During the redirect, the agent appends the goto parameter configured in Goto Parameter Name, and a nonce parameter, to the agent's CDSSO endpoint.

Format, with no spaces between values:

[Domain/path] |[URL?realm=value&parameter1=value1...]

### ***Domain/path***

The incoming request URL:

- Domain: For example, `example.com`. The agent must match the domain and its subdomains. For example, `example.com` matches `mydomain.example.com` and `www.example.com`. Domains can also include path information, for example, `example.com/market`, but cannot specify ports.
- Subdomain: For example, `mydomain.example.com`. The agent match the domain, the subdomain, and any sub-subdomain. For example, `mydomain.example.com` matches `true.mydomain.example.com`. Subdomains can include path information, for example, `mydomain.example.com/s6ecure`, but cannot specify ports.
- Path: For example, `/myapp`.
- No value: Nothing is specified before the `|` character and the rule applies to every incoming request.

### ***URL***

The URL to which redirect incoming login requests. The URL may be an AM instance, an AM site, or a website other than AM.

Specify a URL in the format `protocol://FQDN[:port]/URI`, where the port is optional if it is 80 or 443. For example:

```
https://myweb.example.com/authApp/login.jsp
```

```
https://am.example.com:8443/openam/XUI/#login/
```

```
https://am.example.com:8443/openam/customlogin/login.jsp
```

If the redirection URL is not specified, the agent redirects the request to the AM instance or site specified by the following bootstrap properties:

```
org.forgerock.agents.am.protocol://org.forgerock.agents.am.hostname:org  
.forgerock.agents.am.port/org.forgerock.agents.am.path
```

### ***?realm=value***

The AM realm into which the agent logs the users. For example, `?realm=marketplace`.

When redirecting to AM's XUI, use an ampersand (&) instead of a question mark (?). For example,

```
https://am.example.com:8443/openam/XUI/#login/&realm=marketplace.
```



You do not need to specify the realm in the login URL if any of the following conditions is true:

- The custom login page itself sets the realm parameter, for example, because it lets the user choose it. In this case, you must ensure the custom login page always returns a realm parameter to the agent.
- The realm that the agent is logging the user into has DNS aliases configured in AM.
- AM logs the user into the realm whose DNS alias matches the incoming request URL. For example, an inbound request from the `http://marketplace.example.com` URL logs in the marketplace realm if the realm alias is set to `marketplace.example.com`.
- The users should always log in to the Top Level Realm.

### ***&parameter1=value1***

Parameters that can be added to the URL. Add as many parameters as your custom login pages need. Chain parameters with an ampersand (&), for example, `realm=value&parameter1=value1&parameter2=value2`.

### Examples

```
org.forgerock.agents.oauth.login.url.list[0]= thisdomain.com|?
realm=blue
```

```
org.forgerock.agents.oauth.login.url.list[1]= thatdomain.net|?realm=red
```

```
org.forgerock.agents.oauth.login.url.list[2]=
thatdomain.net/that/path|?realm=grey
```

Property name	<code>org.forgerock.agents.oauth.login.url.list</code>
Aliases	<code>org.forgerock.agents.oauth.login.url.list</code> Introduced in Java Agent 5.6  <code>org.forgerock.openam.agents.config.conditiona                      1.login.url</code> Introduced in Java Agent 5.6 <u>Recognized from AM 6</u>
Function	Custom login redirect, Default Login Redirect, Login redirect, Login Redirect (Default)
Type	List
Bootstrap property	No
Required property	No

Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: AM Services  Title: OAuth Login URL List  Legacy title: AM Conditional Login URL

## Enable Custom Login Mode

Set the login redirection mode, as follows:

- `false` : Use default login redirection mode. The agent can redirect requests to any AM instance supporting the `/oauth2/authorize` endpoint - by default, the AM instance specified during installation.

The `/oauth2/authorize` endpoint returns an OIDC ID token, and this is the only response the agent accepts.

Use with [OAuth Login URL List](#) to modify or redirect calls to the endpoint which provides the tokens.

- `true` : Use custom login redirection mode. The agent handles JWTs or SSO tokens as session tokens for authentication and authorization, and can can redirect login anywhere.

Use with [AM Login URL List](#) and [Legacy Login URL List](#) to modify or redirect calls.

During session upgrade, the format of the composite advice is as follows:

- When both this property and [Enable SSO Token Acceptance](#) are `true`, the composite advice has the following format: ?  
`authIndexType=composite_advice&authIndexValue=<Advices Value>`
- When either property is `false`, the composite advice has the following format: ?  
`composite_advice=<Advices Value>`

Property name	<code>org.forgerock.agents.legacy.login.enabled</code>
---------------	--------------------------------------------------------

Aliases	<p><code>org.forgerock.agents.legacy.login.enabled</code> Introduced in Java Agent 5.6</p> <p><code>org.forgerock.openam.agents.config.allow.custom.login</code> Introduced in Java Agent 5.6 <u>Recognized</u> from AM 7</p>
Function	Custom login redirect, Default Login Redirect, Login redirect, Login Redirect (Default)
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>false</code>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	<p>Tab: AM Services (from AM 7)</p> <p>Title: Enable Custom Login Mode</p> <p>Legacy title: Allow Custom Login Mode</p>

## AM Login URL List

The URL of the login page to use for authentication.

During the redirect, the agent appends the following parameters to the agent's CDSSO endpoint:

- The goto parameter configured in Goto Parameter Name
- A nonce parameter

Use the format `URL[?realm=realm_name?parameter1=value1&...]`, where:

- URL : URL of the login page to use for authentication
- `[?realm=realm_name&parameter1=value1&...]` : Optional parameters that the agent passes to the login page, for example, the AM realm at which to authenticate.

You do not need to specify an authentication realm if any of the following conditions are true:

- The custom login page sets the realm parameter, for example, because it lets the user choose the realm.
- The user authenticates into a realm that has DNS aliases configured in AM. AM then logs the user into the realm whose DNS alias matches the incoming request URL. For example, an inbound request from `http://marketplace.example.com` logs in the marketplace realm if the realm alias is set to `marketplace.example.com`.
- The user authenticates to the top-level realm.

This parameter can be overwritten by the custom login page if, for example, the user chooses the authentication realm.

Specify as many parameters your custom login pages require.

Example:

```
https://login.example.com/login.jsp?realm=marketplace&param1=value1
```

In some versions of AM you can configure more than one value for this property, but only the first value is honored.

Property name	<code>com.sun.identity.agents.config.login.url</code>
Aliases	<code>com.sun.identity.agents.config.login.url</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6
Function	Custom login redirect, Default Login Redirect, Login redirect, Login Redirect (Default)
Type	List
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: AM Services Title: AM Login URL List Legacy title: AM Login URL

# Legacy Login URL List

---

Adds parameters conditionally to legacy login URLs.

Format, with no spaces between values:

`domain/path|url?param1=value1&param2=value2`

## ***Domain/path***

The incoming request URL:

- **Domain:** For example, `example.com`. The agent must match the domain and its subdomains. For example, `example.com` matches `mydomain.example.com` and `www.example.com`. Domains can also include path information, for example, `example.com/market`, but cannot specify ports.
- **Subdomain:** For example, `mydomain.example.com`. The agent match the domain, the subdomain, and any sub-subdomain. For example, `mydomain.example.com` matches `true.mydomain.example.com`. Subdomains can include path information, for example, `mydomain.example.com/s6ecure`, but cannot specify ports.
- **Path:** For example, `/myapp`.
- **No value:** Nothing is specified before the `|` character and the rule applies to every incoming request.

## ***URL***

The URL to which redirect incoming login requests. The URL may be an AM instance, an AM site, or a website other than AM.

Specify a URL in the format `protocol://FQDN[:port]/URI`, where the port is optional if it is 80 or 443. For example:

`https://myweb.example.com/authApp/login.jsp`

`https://am.example.com:8443/openam/XUI/#login/`

`https://am.example.com:8443/openam/customlogin/login.jsp`

If the URL is not specified, the agent redirects the request to the AM instance or site specified by the following bootstrap properties:

`org.forgerock.agents.am.protocol://org.forgerock.agents.am.hostname:org.forgerock.agents.am.port/org.forgerock.agents.am.path`

## ***&parameter1=value1***

Parameters that can be added to the URL. Add as many parameters as your custom login pages need. Chain parameters with an `&` character, for example, `realm=value&parameter1=value1&parameter2=value2`.

## Examples

```
org.forgerock.agents.legacy.login.url.list[0]=example.com|https://am.example.com/openam/XUI/#login&realm=customers
```

```
org.forgerock.agents.legacy.login.url.list[1]=myapp.domain.com|https://login.example.com/apps/login.jsp?realm=sales
```

```
org.forgerock.agents.legacy.login.url.list[2]=sales.example.com/marketplace|?realm=marketplace
```

```
org.forgerock.agents.legacy.login.url.list[3]=|https://login.example.com/apps/login.jsp?realm=sales&isblue=true&carowner=true
```

```
org.forgerock.agents.legacy.login.url.list[4]=|?realm=sales
```

Property name	<code>org.forgerock.agents.legacy.login.url.list</code>
Aliases	<code>org.forgerock.openam.agents.config.conditional.custom.login.url</code> Introduced in Java Agent 5.6 <u>Recognized</u> from AM 7  <code>org.forgerock.agents.legacy.login.url.list</code> Introduced in Java Agent 5.6
Function	Custom login redirect, Default Login Redirect, Login redirect, Login Redirect (Default)
Type	List
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: AM Services (from AM 7)  Title: Legacy Login URL List  Legacy title: Custom Conditional Login URL

## Login redirect

# Enable SSO Token Acceptance

Set this property as follows:

- `true` : Accept SSO tokens. Use this option when the agent and the token issuer are in the same domain, and for web applications and APIs where the backend accepts user information from SSO tokens.
- `false` : Do not accept SSO tokens; require OIDC JWTs for authentication.

During session upgrade the format of the composite advice is as follows:

- When both this property and [Enable Custom Login Mode](#) are `true`, the composite advice has the following format: ?  
`authIndexType=composite_advice&authIndexValue=<Advices Value>`
- When either property is `false`, the composite advice has the following format: ?  
`composite_advice=<Advices Value>`

Property name	<code>org.forgerock.agents.accept.sso.tokens.enabled</code>
Aliases	<code>org.forgerock.agents.accept.sso.tokens.enabled</code> Introduced in Java Agent 5.7.1 <a href="#">Recognized</a> from AM 7.1 <code>org.forgerock.agents.accept.sso.tokens</code> Introduced in Java Agent 5.7.1 <code>com.forgerock.agents.accept.sso.tokens</code> Introduced in Java Agent 5.7.1
Function	Custom login redirect, Login redirect, SSO cookie handling
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>false</code>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>

AM console	Tab: SSO (from AM 7.1) Title: Enable SSO Token Acceptance Legacy title: Accept SSO Tokens
------------	-------------------------------------------------------------------------------------------------

## OAuth Login URL List

---

Use this property in the default configuration (where Enable Custom Login Mode is `false` and AM Login URL List is empty).

Conditionally redirect unauthenticated requests based on the requested URL.

If the incoming request URL matches a domain name in this list, the agent redirects the unauthenticated request to the specified URL for login. The URL can be an AM instance, site, or a different website.

If Enable FQDN Checking is `true`, the agent iterates through the list of URLs until it finds an appropriate redirect URL that matches the FQDN check values. Otherwise, the agent redirects the user to the URL configured in the conditional redirect rules.

During the redirect, the agent appends the goto parameter configured in Goto Parameter Name, and a nonce parameter, to the agent's CDSSO endpoint.

Format, with no spaces between values:

```
[Domain/path] |[URL?realm=value&parameter1=value1...]
```

### ***Domain/path***

The incoming request URL:

- **Domain:** For example, `example.com`. The agent must match the domain and its subdomains. For example, `example.com` matches `mydomain.example.com` and `www.example.com`. Domains can also include path information, for example, `example.com/market`, but cannot specify ports.
- **Subdomain:** For example, `mydomain.example.com`. The agent match the domain, the subdomain, and any sub-subdomain. For example, `mydomain.example.com` matches `true.mydomain.example.com`. Subdomains can include path information, for example, `mydomain.example.com/s6ecure`, but cannot specify ports.
- **Path:** For example, `/myapp`.
- **No value:** Nothing is specified before the `|` character and the rule applies to every incoming request.

### ***URL***



The URL to which redirect incoming login requests. The URL may be an AM instance, an AM site, or a website other than AM.

Specify a URL in the format `protocol://FQDN[:port]/URI`, where the port is optional if it is 80 or 443. For example:

```
https://myweb.example.com/authApp/login.jsp
```

```
https://am.example.com:8443/openam/XUI/#login/
```

```
https://am.example.com:8443/openam/customlogin/login.jsp
```

If the redirection URL is not specified, the agent redirects the request to the AM instance or site specified by the following bootstrap properties:

```
org.forgerock.agents.am.protocol://org.forgerock.agents.am.hostname:org
.forgerock.agents.am.port/org.forgerock.agents.am.path
```

### ***?realm=value***

The AM realm into which the agent logs the users. For example, `?realm=marketplace`.

When redirecting to AM's XUI, use an ampersand (&) instead of a question mark (?). For example,

```
https://am.example.com:8443/openam/XUI/#login/&realm=marketplace
```

You do not need to specify the realm in the login URL if any of the following conditions is true:

- The custom login page itself sets the realm parameter, for example, because it lets the user choose it. In this case, you must ensure the custom login page always returns a realm parameter to the agent.
- The realm that the agent is logging the user into has DNS aliases configured in AM.
- AM logs the user into the realm whose DNS alias matches the incoming request URL. For example, an inbound request from the `http://marketplace.example.com` URL logs in the marketplace realm if the realm alias is set to `marketplace.example.com`.
- The users should always log in to the Top Level Realm.

### ***&parameter1=value1***

Parameters that can be added to the URL. Add as many parameters as your custom login pages need. Chain parameters with an ampersand (&), for example, `realm=value&parameter1=value1&parameter2=value2`.

Examples

```
org.forgerock.agents.oauth.login.url.list[0]= thisdomain.com|?
realm=blue
```

```
org.forgerock.agents.oauth.login.url.list[1]= thatdomain.net|?realm=red
```

```
org.forgerock.agents.oauth.login.url.list[2]=
thatdomain.net/that/path|?realm=grey
```

Property name	<code>org.forgerock.agents.oauth.login.url.list</code>
Aliases	<code>org.forgerock.agents.oauth.login.url.list</code> Introduced in Java Agent 5.6  <code>org.forgerock.openam.agents.config.conditional.login.url</code> Introduced in Java Agent 5.6 <u>Recognized</u> from AM 6
Function	Custom login redirect, Default Login Redirect, Login redirect, Login Redirect (Default)
Type	List
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: AM Services  Title: OAuth Login URL List  Legacy title: AM Conditional Login URL

## Enable Custom Login Mode

Set the login redirection mode, as follows:

- `false` : Use default login redirection mode. The agent can redirect requests to any AM instance supporting the `/oauth2/authorize` endpoint - by default, the AM instance specified during installation.

The `/oauth2/authorize` endpoint returns an OIDC ID token, and this is the only response the agent accepts.

Use with [OAuth Login URL List](#) to modify or redirect calls to the endpoint which provides the tokens.

- `true` : Use custom login redirection mode. The agent handles JWTs or SSO tokens as session tokens for authentication and authorization, and can can redirect login anywhere.

Use with [AM Login URL List](#) and [Legacy Login URL List](#) to modify or redirect calls.

During session upgrade, the format of the composite advice is as follows:

- When both this property and [Enable SSO Token Acceptance](#) are `true` , the composite advice has the following format: ?  
`authIndexType=composite_advice&authIndexValue=<Advices Value>`
- When either property is `false` , the composite advice has the following format: ?  
`composite_advice=<Advices Value>`

Property name	<code>org.forgerock.agents.legacy.login.enabled</code>
Aliases	<code>org.forgerock.agents.legacy.login.enabled</code> Introduced in Java Agent 5.6  <code>org.forgerock.openam.agents.config.allow.custom.login</code> Introduced in Java Agent 5.6 <a href="#">Recognized</a> from AM 7
Function	Custom login redirect, Default Login Redirect, Login redirect, Login Redirect (Default)
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>false</code>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: AM Services (from AM 7)  Title: Enable Custom Login Mode  Legacy title: Allow Custom Login Mode

# AM Login URL List

---

The URL of the login page to use for authentication.

During the redirect, the agent appends the following parameters to the agent's CDSSO endpoint:

- The goto parameter configured in Goto Parameter Name
- A nonce parameter

Use the format `URL[?realm=realm_name?parameter1=value1&...]`, where:

- `URL` : URL of the login page to use for authentication
- `[?realm=realm_name&parameter1=value1&...]` : Optional parameters that the agent passes to the login page, for example, the AM realm at which to authenticate.

You do not need to specify an authentication realm if any of the following conditions are true:

- The custom login page sets the realm parameter, for example, because it lets the user choose the realm.
- The user authenticates into a realm that has DNS aliases configured in AM. AM then logs the user into the realm whose DNS alias matches the incoming request URL. For example, an inbound request from `http://marketplace.example.com` logs in the marketplace realm if the realm alias is set to `marketplace.example.com`.
- The user authenticates to the top-level realm.

This parameter can be overwritten by the custom login page if, for example, the user chooses the authentication realm.

Specify as many parameters your custom login pages require.

Example:

```
https://login.example.com/login.jsp?realm=marketplace&param1=value1
```

In some versions of AM you can configure more than one value for this property, but only the first value is honored.

Property name	<code>com.sun.identity.agents.config.login.url</code>
Aliases	<code>com.sun.identity.agents.config.login.url</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6

Function	Custom login redirect, Default Login Redirect, Login redirect, Login Redirect (Default)
Type	List
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: AM Services Title: AM Login URL List Legacy title: AM Login URL

## Login Reason Parameter Name

When [Enable Custom Login Mode](#) is `true`, this property specifies the name of a parameter included in calls to the custom login URL, to indicate why authentication is required. The parameter value can be used in a custom login page to provide additional feedback to the authenticating user.

If this property is specified, the agent includes a parameter named with the property value, and including one of the following values:

- `NO_TOKEN` : No token present in the original request.
- `TOKEN_EXPIRED` : Expiry time of the JWT was in the past.
- `EXCEPTION` : An unknown exception occurred, either while parsing the JWT or at some other stage of authentication.

To reduce the risk of leaking useful information, use the property [Login Reason Value Map](#) to change the strings for the above values.

For example, specifying

`org.forgerock.agents.login.reason.parameter.name=auth_reason` can cause the agent to redirect authentication to the following URL:

```
https://custom.example.com:8443/.../login_endpoint?...
&auth_reason=TOKEN_EXPIRED&...
```

Do not enter a value that clashes with other parameters used for authentication; for example, `realm` or `goto`.

Property name	<code>org.forgerock.agents.login.reason.parameter.name</code>
Aliases	<code>org.forgerock.agents.login.reason.parameter.name</code> Introduced in Java Agent 5.7
Function	Custom login redirect, Login redirect
Type	String
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Miscellaneous (from AM 7)  Title: Login Reason Parameter Name

## Legacy Login URL List

Adds parameters conditionally to legacy login URLs.

Format, with no spaces between values:

`domain/path|url?param1=value1&param2=value2`

### ***Domain/path***

The incoming request URL:

- Domain: For example, `example.com`. The agent must match the domain and its subdomains. For example, `example.com` matches `mydomain.example.com` and `www.example.com`. Domains can also include path information, for example, `example.com/market`, but cannot specify ports.
- Subdomain: For example, `mydomain.example.com`. The agent match the domain, the subdomain, and any sub-subdomain. For example, `mydomain.example.com` matches `true.mydomain.example.com`. Subdomains can include path information, for example, `mydomain.example.com/secure`, but cannot specify ports.
- Path: For example, `/myapp`.
- No value: Nothing is specified before the `|` character and the rule applies to every incoming request.

## URL

The URL to which redirect incoming login requests. The URL may be an AM instance, an AM site, or a website other than AM.

Specify a URL in the format `protocol://FQDN[:port]/URI`, where the port is optional if it is 80 or 443. For example:

```
https://myweb.example.com/authApp/login.jsp
```

```
https://am.example.com:8443/openam/XUI/#login/
```

```
https://am.example.com:8443/openam/customlogin/login.jsp
```

If the URL is not specified, the agent redirects the request to the AM instance or site specified by the following bootstrap properties:

```
org.forgerock.agents.am.protocol://org.forgerock.agents.am.hostname:org.forgerock.agents.am.port/org.forgerock.agents.am.path
```

### ***&parameter1=value1***

Parameters that can be added to the URL. Add as many parameters as your custom login pages need. Chain parameters with an & character, for example, `realm=value&parameter1=value1&parameter2=value2`.

### Examples

```
org.forgerock.agents.legacy.login.url.list[0]=example.com|https://am.example.com/openam/XUI/#login&realm=customers
```

```
org.forgerock.agents.legacy.login.url.list[1]=myapp.domain.com|https://login.example.com/apps/login.jsp?realm=sales
```

```
org.forgerock.agents.legacy.login.url.list[2]=sales.example.com/marketplace|?realm=marketplace
```

```
org.forgerock.agents.legacy.login.url.list[3]=|https://login.example.com/apps/login.jsp?realm=sales&isblue=true&carowner=true
```

```
org.forgerock.agents.legacy.login.url.list[4]=|?realm=sales
```

Property name	<code>org.forgerock.agents.legacy.login.url.list</code>
Aliases	<code>org.forgerock.openam.agents.config.conditional.custom.login.url</code> Introduced in Java Agent 5.6 <u>Recognized</u> from AM 7  <code>org.forgerock.agents.legacy.login.url.list</code> Introduced in Java Agent 5.6

Function	Custom login redirect, Default Login Redirect, Login redirect, Login Redirect (Default)
Type	List
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: AM Services (from AM 7) Title: Legacy Login URL List Legacy title: Custom Conditional Login URL

## Logout

### Logout URI Map

---

A map of request URIs that trigger logout of the user session. Use the following key:value format:

```
web application name:logout URI
```

When a URL that includes the specified URI is invoked, the agent kills the current session. It invokes the AM REST logout endpoint or the endpoint configured by [Conditional Logout URL List](#).

The agent must be able to access the context for the URL. When a web application is specified, it must exist and the agent must have access to it.

The URL is a dummy URL. Even if a resource exists at the URL, it is never accessed.

Although logout can be triggered within any web application by invoking a single, common, URI, you can tailor it for particular web applications:

- To specify a single, common, URI, leave the key empty.
- To specify a URI unique to a particular web application, specify the name of the web application as the key.

Property name	org.forgerock.agents.logout.endpoint.map
---------------	------------------------------------------



Aliases	<code>com.sun.identity.agents.config.logout.uri</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  <code>org.forgerock.agents.logout.endpoint.map</code> Introduced in Java Agent 5.6
Function	Logout
Type	Map <ul style="list-style-type: none"> <li>• Keys: web application</li> <li>• Values: URI of dummy endpoint which will trigger logout</li> </ul>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Application  Title: Logout URI Map  Legacy title: Application Logout URI

## Logout Request Parameter Map

A map of request parameters that trigger logout of the user session. Use the following key:value format:

```
`web application name:parameter name to trigger logout`
```

The agent searches every incoming request for the parameter. When the agent detects the parameter, it invokes AM to kill the current session for the specified web application or all web applications.

The request URL must contain the parameter, but does not need to assign a value to the parameter.

Although logout can be triggered within any web application by invoking a single, common, URI, you can tailor it for particular web applications:

- To specify a single, common, URI, leave the key empty.
- To specify a URI unique to a particular web application, specify the name of the web application as the key.

Property name	<code>org.forgerock.agents.logout.request.param.map</code>
Aliases	<code>org.forgerock.agents.logout.request.param.map</code> Introduced in Java Agent 5.6  <code>com.sun.identity.agents.config.logout.request.param</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6
Function	Logout
Type	Map <ul style="list-style-type: none"> <li>• Keys: web application</li> <li>• Values: (single) HTTP query parameter to trigger logout</li> </ul>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Application  Title: Logout Request Parameter Map  Legacy title: Logout Request Parameter

## Always invalidate sessions

When this flag is set to false, agent will not invoke the AM logout/rest logout to kill the user session.

Property name	<code>org.forgerock.agents.config.logout.session.invalidate.enabled</code>
---------------	----------------------------------------------------------------------------

Aliases	<p><code>org.forgerock.agents.config.logout.session.invalidate.enabled</code> Introduced in Java Agent 5.10.1</p> <p><code>org.forgerock.agents.config.logout.session.invalidate</code> Introduced in Java Agent 5.10.1</p>
Function	Logout
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>true</code>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>

## Enable Logout Introspection

When `true`, the agent checks the HTTP request body to locate the value of [Logout Request Parameter Map](#).

Property name	<code>org.forgerock.agents.logout.introspection.enabled</code>
Aliases	<p><code>com.sun.identity.agents.config.logout.introspect.enabled</code> Introduced in Java Agent 5.0 <a href="#">Recognized</a> from AM 6</p> <p><code>org.forgerock.agents.logout.introspection.enabled</code> Introduced in Java Agent 5.6</p>
Function	Logout
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>false</code>

Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Application Title: Enable Logout Introspection Legacy title: Logout Introspect Enabled

## Conditional Logout URL List

Change the URL that the agent uses to log out. This property does not trigger logout.

Configure one or more conditions, using this format:

```
domain/path|url?param1=value1&param2=value2
```

The request URL is compared to each condition in the list until the closest match is found. Conditions are evaluated by order of length, starting with the longest, irrespective of their order in the list.

In the following example, `example.com/path` is evaluated before `example.com`; the default condition is the shortest, and is evaluated last:

```
org.forgerock.agents.conditional.logout.url.list[0]=example.com|?additional=value
```

```
org.forgerock.agents.conditional.logout.url.list[1]=example.com/path|?one=red&two=green&three=blue
```

```
org.forgerock.agents.conditional.logout.url.list[2]=mybank.com|http://mybank.com/myapp/logout?param=override
```

```
org.forgerock.agents.conditional.logout.url.list[3]=|?alpha=beta
```

Property name	<code>org.forgerock.agents.conditional.logout.url.list</code>
---------------	---------------------------------------------------------------

Aliases	<p><code>org.forgerock.openam.agents.config.conditional.logout.url</code>  Introduced in Java Agent 5.6  <u>Recognized</u> from AM 6</p> <p><code>org.forgerock.agents.conditional.logout.url.list</code>  Introduced in Java Agent 5.6</p>
Function	Logout
Type	List
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	<p>Tab: AM Services</p> <p>Title: Conditional Logout URL List</p> <p>Legacy title: AM Conditional Logout URL</p>

## Logout Entry URI Map

After logout has been triggered by [Logout URI Map](#) or [Logout Request Parameter Map](#), and is complete, the agent redirects users to a specified resource, such as an HTML page or JSP file.

The specified resource is automatically added to the not-enforced list, so that it can be accessed without authentication.

To redirect for a specific web application, set the key to the name of the web application.

To redirect for all web applications, leave the key empty.

Property name	<code>org.forgerock.agents.logout.goto.map</code>
---------------	---------------------------------------------------

Aliases	<p><code>com.sun.identity.agents.config.logout.entry.uri</code>  Introduced in Java Agent 5.0  <u>Recognized</u> from AM 6</p> <p><code>org.forgerock.agents.logout.goto.map</code>  Introduced in Java Agent 5.6</p>
Function	Logout
Type	Map <ul style="list-style-type: none"> <li>• Keys: web application</li> <li>• Values: URI of page explaining the user has been logged out</li> </ul>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Application  Title: Logout Entry URI Map  Legacy title: Logout Entry URI

## Logs

### Agent Debug Level

The agent log level.

Make sure your container captures messages written to the standard output. Some containers do not, and warnings or critical errors can disappear forever.

Property name	<code>org.forgerock.agents.debug.level</code>
---------------	-----------------------------------------------

Aliases	<p><code>com.iplanet.services.debug.level</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6</p> <p><code>org.forgerock.agents.debug.level</code> Introduced in Java Agent 5.6</p>
Function	Logs
Supported settings	<p><b>OFF</b> (Deprecated) Uses the same log level as <code>ERROR</code>. To disable logging, edit <code>agent-logback.xml</code>. Forgerock advises not to disable logging.</p> <p><b>ERROR</b> Log only errors.</p> <p><b>WARNING</b> Log errors and warnings.</p> <p><b>MESSAGE</b> Log errors, warnings, and informative messages.</p> <p><b>DEBUG</b> Log errors, warnings, informative messages, and some debugging messages.</p> <p><b>TRACE</b> Log fine-grained information, when you need the full visibility of what is happening in your application. This log level can create big log files, so use only when necessary, and then reduce the log level.</p> <p><b>ON</b> (Deprecated) Uses the same log level as <code>TRACE</code>. When the log level is <code>ON</code>, <code>TRACE</code> level logs are written to file. In previous releases, <code>TRACE</code> level logs were written to the standard output. Make sure your container captures messages written to the standard output.</p>
Default	ERROR
Bootstrap property	No
Required property	No
Restart required	No

Local configuration file	AgentConfig.properties
AM console	Tab: Global Title: Agent Debug Level

## Miscellaneous

### Redirect Attempt Cookie Name

The cookie name to use to detect redirect loops while authenticating, which would indicate a cookie domain problem.

Property name	org.forgerock.agents.redirect.cookie.name
Aliases	org.forgerock.agents.redirect.cookie.name Introduced in Java Agent 5.6  com.sun.identity.agents.config.redirect.cookie.name Introduced in Java Agent 5.0 <u>Recognized</u> from AM 7
Function	Miscellaneous
Type	String
Default	amFilterRDParam
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Global (from AM 7) Title: Redirect Attempt Cookie Name

### Encrypted Agent Password

The agent profile password, which must correspond to the value in AM.



Set this property to the encrypted value of the password, where the password is encrypted using the key in the property [Encryption Key](#).

Use the following command to get the encrypted value of the password, where `passwordFile` contains only the password followed by a newline, and has the access permission `400` :

```
$ ./agentadmin --encrypt agentInstance passwordFile
```

Default: Empty

Property name	<code>org.forgerock.agents.encrypted.password</code>
Aliases	<code>com.iplanet.am.service.secret</code> Introduced in Java Agent 5.0  <code>org.forgerock.agents.encrypted.password</code> Introduced in Java Agent 5.6
Function	Miscellaneous, Required
Type	String
Bootstrap property	No
Required property	Yes - If this property is missing, the agent fails to start
Restart required	Yes - Restart the container after changing the property
Local configuration file	<code>AgentPassword.properties</code>

## Enable Ignore Path Info

When `true`, when the request URL contains a wildcard `'*'` character, the path info and query are stripped from the URL before it is compared with the list of not-enforced URLs.

Property name	<code>org.forgerock.agents.ignore.path.info.enabled</code>
Aliases	<code>com.sun.identity.agents.config.ignore.path.info</code> Introduced in Java Agent 5.0 <a href="#">Recognized</a> from AM 6  <code>org.forgerock.agents.ignore.path.info.enabled</code> Introduced in Java Agent 5.6

Function	Miscellaneous
Type	Boolean: true returns true; all other strings return false.
Default	false
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Miscellaneous  Title: Enable Ignore Path Info  Legacy title: Ignore Path Info for Not Enforced URLs

## Custom Response Header Map

A key:value map of custom headers set by the agent for the client, where the key is the header name, and the value is the header value. For example,  
`org.forgerock.agents.response.header.map[Cache-Control]=no-cache`

Format `org.forgerock.agents.response.header.map[HEADER-NAME]=HEADER-VALUE`

Property name	<code>org.forgerock.agents.response.header.map</code>
Aliases	<code>org.forgerock.agents.response.header.map</code> Introduced in Java Agent 5.6  <code>com.sun.identity.agents.config.response.header</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6
Function	Miscellaneous

Type	Map <ul style="list-style-type: none"> <li>• Keys: from header</li> <li>• Values: to header</li> </ul>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Global Title: Custom Response Header Map Legacy title: Custom Response Header

## Idle Time Refresh Window

The interval in minutes at which the agent calls AM to refresh a session idle timeout.

AM sessions have an idle timeout after which they expire. In general, when users access protected resources through an agent, the agent requests a policy decision on behalf of that user, which resets the idle timeout.

When the agent does not need to contact AM frequently, for example, when policy evaluation is already cached, sessions may unexpectedly expire in AM before the user has finished accessing the application.

Agents make one call per active user session at the end of the time interval, provided that the user is actively accessing the web application or site. If the user does not access the application during the configured window interval time, the agent will not make the call to AM at the end of the interval. Eventually, if the user is inactive for enough time, AM will log them out when the session reaches its idle timeout.

Configuring the idle timeout window to a short value, such as one minute, achieves a good balance between making additional calls to AM and providing a good user experience.

Increase this value only if the performance impact of making an extra call to AM every minute is noticeable enough in your environment.

Property name	<code>org.forgerock.agents.idle.time.window.minutes</code>
---------------	------------------------------------------------------------

Aliases	<code>org.forgerock.agents.idle.time.window.minutes</code> Introduced in Java Agent 5.6.2.1 <u>Recognized</u> from AM 7
Function	Miscellaneous
Type	Integer
Default	1
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Advanced (from AM 7)  Title: Idle Time Refresh Window

## Service Resolver Class Name

The Java class name of the service resolver used to override the ForgeRock provided service resolver. Use this property to customize pre-handlers and post-handlers.

Property name	<code>org.forgerock.agents.service.resolver.class.name</code>
Aliases	<code>org.forgerock.agents.service.resolver.class.name</code> Introduced in Java Agent 5.6.2.1 <u>Recognized</u> from AM 7
Function	Miscellaneous
Type	String
Default	<code>com.sun.identity.agents.arch.ServiceResolver</code>
Bootstrap property	Yes
Required property	No
Restart required	Yes - Restart the container after changing the property

Local configuration file	AgentBootstrap.properties
--------------------------	---------------------------

## HTTP Session Binding

---

When `true`, the agent invalidates the HTTP session in these circumstances:

- Login failure
- When the user has no SSO session
- When the principal user name does not match the SSO user name

Property name	<code>org.forgerock.agents.http.session.binding.enabled</code>
Aliases	<code>com.sun.identity.agents.config.httpsession.binding</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  <code>org.forgerock.agents.http.session.binding.enabled</code> Introduced in Java Agent 5.6
Function	Miscellaneous
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>true</code>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Global  Title: HTTP Session Binding

## Public AM URL

---

The assembled "public" URL of AM. This URL is used by the agent to redirect the user's browser to AM for login (customised or not), or if necessary, exchange an SSO token for a JWT.

The following properties make up the URL:

- [AM Authentication Service Protocol](#)
- [AM Authentication Service Host Name](#)
- [AM Authentication Service Port](#)
- [AM Authentication Service Path](#)

The "private" URL is used by the agent for tasks such as establishing websockets, and obtaining authentication tokens or session information. The AM or load balancer instance can be behind a firewall to which the agent has access.

Define this property when public access to AM is restricted to a different URL from the private URL.

Property name	<code>org.forgerock.agents.public.am.url</code>
Aliases	<code>com.forgerock.agents.public.am.url</code> Introduced in Java Agent 5.6.3.0  <code>org.forgerock.agents.public.am.url</code> Introduced in Java Agent 5.6.3.0
Function	Miscellaneous, Required
Type	String
Bootstrap property	Yes
Required property	Yes - If this property is missing, the agent fails to start
Restart required	Yes - Restart the container after changing the property
Local configuration file	<code>AgentBootstrap.properties</code>

## Monitoring

### Export Monitoring Metrics to CSV

When `true`, enables the export of agent performance monitoring metrics to comma-separated value (CSV) files.

Files are written the same directory as the agent instance debug files, for example in `/path/to/java_agents/tomcat_agent/Agent_001/logs/debug/`.

Property name	<code>org.forgerock.agents.config.monitoring.to.csv</code>
Aliases	<code>org.forgerock.agents.config.monitoring.to.csv</code> Introduced in Java Agent 5.6 <u>Recognized</u> from AM 7  <code>org.forgerock.agents.monitoring.to.csv.enabled</code> Introduced in Java Agent 5.6
Function	Monitoring
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>false</code>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Advanced (from AM 7)  Title: Export Monitoring Metrics to CSV

## CSV Monitoring Directory

The full path to the directory where the agent writes CSV monitoring files, when CSV monitoring is enabled.

The default is set by the installer and written to the bootstrap properties file.

Default: `/logs/debug` directory relative to the `definedBy` of the agent installation

Property name	<code>org.forgerock.agents.csv.monitoring.directory</code>
Aliases	<code>org.forgerock.agents.csv.monitoring.directory</code> Introduced in Java Agent 5.7
Function	Monitoring

Type	String
Bootstrap property	Yes
Required property	No
Restart required	Yes - Restart the container after changing the property
Local configuration file	AgentBootstrap.properties

## Not-enforced

## Not-Enforced URIs

A space-delimited list of URIs for which the agent does not enforce authentication or request policy evaluations. In the following example, the agent does not enforce authentication or request policy evaluations for the public and images directories of myapp.example.com :

```
org.forgerock.agents.notenforced.uri.list=https://myapp.example.com:8443/public/* https://myapp.example.com:8443/images/*
```

For more information and examples, see [Conventions for Not-Enforced Rules](#).

Property name	org.forgerock.agents.notenforced.uri.list
Aliases	org.forgerock.agents.notenforced.uri.list Introduced in Java Agent 5.6  com.sun.identity.agents.config.notenforced.uri Introduced in Java Agent 5.0 <a href="#">Recognized</a> from AM 6
Function	Not-enforced
Type	List
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties



## Not-Enforced Client IP List

---

A space-delimited list of IP addresses or network CIDR notation addresses for which the agent does not enforce authentication or request policy evaluations.

Supported values are IPV4 and IPV6 addresses, IPV4 and IPV6 ranges of addresses delimited by the - character, and network ranges specified in CIDR notation.

Property name	<code>org.forgerock.agents.notenforced.ip.list</code>
Aliases	<code>org.forgerock.agents.notenforced.ip.list</code> Introduced in Java Agent 5.6  <code>com.sun.identity.agents.config.notenforced.ip</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6
Function	Not-enforced
Type	List
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>

## Not-Enforced Favicon

---

When `true`, the agent does not enforce access to any files named `favicon.ico`, by inserting an internal not-enforced rule of `GET */favicon.ico`.

Property name	<code>org.forgerock.agents.auto.not.enforce.favicon</code>
Aliases	<code>org.forgerock.agents.auto.not.enforce.favicon</code> Introduced in Java Agent 5.7 <u>Recognized</u> from AM 7  <code>org.forgerock.agents.auto.not.enforce.favicon.enabled</code> Introduced in Java Agent 5.7
Function	Not-enforced

Type	Boolean: true returns true; all other strings return false .
Default	true
Bootstrap property	Yes
Required property	No
Restart required	Yes - Restart the container after changing the property
Local configuration file	AgentBootstrap.properties
AM console	Tab: Application (from AM 7)  Title: Not-Enforced Favicon  Legacy title: Not Enforced Favicon

## Enable Not-Enforced URIs Cache

When `true` , the agent caches evaluations of the Not-Enforced URIs.

Enable this setting when configuring many rules.

Property name	<code>org.forgerock.agents.notenforced.uri.cache.enabled</code>
Aliases	<code>org.forgerock.agents.notenforced.uri.cache.enabled</code> Introduced in Java Agent 5.6  <code>com.sun.identity.agents.config.notenforced.uri.cache.enable</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6
Function	Not-enforced
Type	Boolean: true returns true; all other strings return false .
Default	true
Bootstrap property	No

Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Application Title: Enable Not-Enforced URIs Cache Legacy title: Not Enforced URIs Cache Enabled

## Container Character Encoding

The character encoding used by the agent when encoding extended characters in the resource paths of not-enforced rules.

Property name	<code>org.forgerock.agents.container.encoding</code>
Aliases	<code>org.forgerock.agents.container.encoding</code> Introduced in Java Agent 5.9.1
Function	Container, Not-enforced
Type	String
Default	UTF-8
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties

## Java Class for Matching Not Enforced Rules

The Java class used to match URIs and IP addresses embedded within not enforced rules.

The specified class must implement the interface `com.sun.identity.agents.common.RulePatternMatcher`.

If the class fails to instantiate, an error is logged and the default `NotEnforcedRulePatternMatcher` is created instead.

Property name	<code>org.forgerock.agents.not.enforced.rule.pattern.matcher.classname</code>
Aliases	<code>org.forgerock.agents.not.enforced.rule.pattern.matcher.classname</code> Introduced in Java Agent 5.9.0
Function	Not-enforced
Type	String
Default	<code>com.sun.identity.agents.common.NotEnforcedRulePatternMatcher</code>
Bootstrap property	Yes
Required property	No
Restart required	No
Local configuration file	<code>AgentBootstrap.properties</code>

## Not-Enforced Compound Rule Separator

A delimiter for not-enforced compound rules. The delimiter can be a single character or a string. For example, setting the delimiter to `&&` allows compound rules to be specified as:

```
GET 10.5.1.5 100.2.21.36 && /public/*
```

```
REGEX 10\.4\.3\.5 && [^/]+\./free.jpg
```

Property name	<code>org.forgerock.agents.notenforced.compound.separator</code>
Aliases	<code>org.forgerock.agents.notenforced.compound.separator</code> Introduced in Java Agent 5.6  <code>com.sun.identity.agents.config.notenforced.rule.compound.separator</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 7

Function	Not-enforced
Type	String
Default	
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Application Title: Not-Enforced Compound Rule Separator

## Invert Not-Enforced URIs

### NOTE

The use of this property is NOT recommended.

When `true`, enforce policy for the URIs and patterns specified by the [Not-Enforced URIs](#) property, instead of allowing access to them without authentication.

For security considerations, do not enable this property. Instead, ForgeRock recommends using the NOT keyword to invert specific rules in the [Not-Enforced URIs](#).

Property name	<code>org.forgerock.agents.notenforced.uri.invert.enabled</code>
Aliases	<code>com.sun.identity.agents.config.notenforced.uri.invert</code> Introduced in Java Agent 5.0 <a href="#">Recognized</a> from AM 6  <code>org.forgerock.agents.notenforced.uri.invert.enabled</code> Introduced in Java Agent 5.6
Function	Not-enforced
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .

Default	false
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Application Title: Invert Not-Enforced URIs Legacy title: Invert Not Enforced URIs

## Max Entries in Not-Enforced URI Cache

The maximum number of cached resource URLs that are matched by a not-enforced rule (inverted or not inverted).

Property name	org.forgerock.agents.notenforced.uri.cache.size
Aliases	com.sun.identity.agents.config.notenforced.uri.cache.size Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  org.forgerock.agents.notenforced.uri.cache.size Introduced in Java Agent 5.6
Function	Not-enforced
Type	Integer
Default	10000
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties

AM console	Tab: Application Title: Max Entries in Not-Enforced URI Cache Legacy title: Not Enforced URIs Cache Size
------------	----------------------------------------------------------------------------------------------------------------

## Enable Not-Enforced IP Cache

### NOTE

The use of this property is NOT recommended.

When `true`, the agent caches evaluations of the [Not-Enforced Client IP List](#).

Enable this setting if you are configuring many rules.

Property name	<code>org.forgerock.agents.notenforced.ip.cache.enabled</code>
Aliases	<code>org.forgerock.agents.notenforced.ip.cache.enabled</code> Introduced in Java Agent 5.6  <code>com.sun.identity.agents.config.notenforced.ip.cache.enable</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6
Function	Not-enforced
Type	Boolean: <code>true</code> returns true; all other strings return false.
Default	<code>true</code>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>

AM console	Tab: Application  Title: Enable Not-Enforced IP Cache  Legacy title: Not Enforced IP Cache Flag
------------	-------------------------------------------------------------------------------------------------------------

## Invert Not-Enforced IPs

When `true`, enforce policy for the IPs specified by the [Not-Enforced Client IP List](#) property, instead of allowing access to them without authentication.

For security considerations, do not enable this property. Instead, ForgeRock recommends using the NOT keyword to invert specific rules in the [Not-Enforced Client IP List](#).

Property name	<code>org.forgerock.agents.notenforced.ip.invert.enabled</code>
Aliases	<code>org.forgerock.agents.notenforced.ip.invert.enabled</code> Introduced in Java Agent 5.6  <code>com.sun.identity.agents.config.notenforced.ip.invert</code> Introduced in Java Agent 5.0 <a href="#">Recognized</a> from AM 6
Function	Not-enforced
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>false</code>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>



AM console	Tab: Application  Title: Invert Not-Enforced IPs  Legacy title: Invert Not Enforced IPs
------------	-----------------------------------------------------------------------------------------------------

## Max Entries in Not-Enforced IP Cache

---

The maximum number of cached IP addresses that are matched by a not-enforced rule (inverted or not inverted).

Property name	<code>org.forgerock.agents.notenforced.ip.cache.size</code>
Aliases	<code>org.forgerock.agents.notenforced.ip.cache.size</code> Introduced in Java Agent 5.6  <code>com.sun.identity.agents.config.notenforced.ip.cache.size</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6
Function	Not-enforced
Type	Integer
Default	1000
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Application  Title: Max Entries in Not-Enforced IP Cache  Legacy title: Not Enforced IP Cache Size

## Container Parameter Encoding

---

The character encoding used by the agent when encoding extended characters in the HTTP query parameters of not-enforced rules.

Property name	<code>org.forgerock.agents.container.param.encoding</code>
Aliases	<code>org.forgerock.agents.container.param.encoding</code> Introduced in Java Agent 5.9.1
Function	Container, Not-enforced
Type	String
Default	ISO-8859-1
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>

## Notifications

### Enable Notifications of Agent Configuration Change

Flag to indicate whether the agent subscribes to WebSocket notifications from AM for configuration changes. This property applies only the agent profile is stored in AM's configuration data store.

Property name	<code>org.forgerock.agents.config.change.notifications.enabled</code>
Aliases	<code>org.forgerock.agents.config.change.notifications.enabled</code> Introduced in Java Agent 5.6  <code>com.sun.identity.agents.config.change.notification.enable</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6
Function	Notifications

Type	Boolean: true returns true; all other strings return false.
Default	true
Bootstrap property	Yes
Required property	No
Restart required	No
Local configuration file	AgentBootstrap.properties
AM console	Tab: Global  Title: Enable Notifications of Agent Configuration Change  Legacy title: Agent Configuration Change Notification

## Obsolete Notification URL (deprecated)

Nominates a URI representing a dummy endpoint within the agent, which accepts incoming notifications from AM.

This mechanism was replaced by websocket notifications, so if anything is sent to this dummy endpoint, it will not be processed, but will be acknowledged with "OK".

Property name	org.forgerock.agents.obsolete.notification.url
Deprecated in	5.6
Aliases	com.sun.identity.client.notification.url Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  org.forgerock.agents.obsolete.notification.url Introduced in Java Agent 5.6
Function	Notifications
Type	String

Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties

## Enable Notification of Session Logout (deprecated)

---

Flag to indicate whether the agent subscribes to WebSocket notifications from AM for session logout.

Use [Enable Notification of Session Logout](#) instead of this property.

Property name	<code>com.ipplanet.am.session.client.polling.enabled</code>
Deprecated in	5.6
Aliases	<code>com.ipplanet.am.session.client.polling.enabled</code> Introduced in Java Agent 5.6  <code>com.ipplanet.am.session.client.polling.enable</code> Introduced in Java Agent 5.0 <a href="#">Recognized</a> from AM 6
Function	Notifications
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties

## Enable Notification of Policy Changes

---

Flag to indicate whether the agent subscribes to WebSocket notifications from AM for policy changes.

Property name	<code>org.forgerock.agents.policy.change.notifications.enabled</code>
Aliases	<code>org.forgerock.agents.policy.change.notifications.enabled</code> Introduced in Java Agent 5.6  <code>com.sun.identity.agents.notification.enabled</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6
Function	Notifications
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>true</code>
Bootstrap property	Yes
Required property	No
Restart required	No
Local configuration file	<code>AgentBootstrap.properties</code>
AM console	Tab: AM Services  Title: Enable Notification of Policy Changes

## Enable Notification of Session Logout

Flag to indicate whether the agent subscribes to WebSocket notifications from AM for session logout.

If this property and Enable Notification of Session Logout (deprecated) are not set, the agent subscribes to WebSocket notifications from AM for session logout.

Property name	<code>org.forgerock.agents.session.change.notifications.enabled</code>
Aliases	<code>org.forgerock.agents.session.change.notifications.enabled</code> Introduced in Java Agent 5.6 <u>Recognized</u> from AM 7

Function	Notifications
Type	Boolean: true returns true; all other strings return false .
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Global (from AM 7) Title: Enable Notification of Session Logout

## POST data preservation

### POST Data Preservation Directory Sweep Interval

The interval in seconds at which the [POST Data Preservation File Directory](#) is swept for expired files. Files expire after the time defined by [POST Data Preservation Cache TTL](#).

This property is valid only when [Enable POST Data Preservation](#) and [POST Data Preservation in Files or Cache](#) are true , and [POST Data Preservation File Directory](#) is a valid directory.

Property name	org.forgerock.agents.pdp.directory.sweep.seconds
Aliases	org.forgerock.agents.pdp.directory.sweep.seconds Introduced in Java Agent 5.10.0
Function	POST data preservation
Type	Integer
Default	10
Bootstrap property	Yes
Required property	No
Restart required	Yes - Restart the container after changing the property

Local configuration file	AgentBootstrap.properties
--------------------------	---------------------------

## Missing POST Data Preservation Entry URI Map

---

A map of URLs to which the agent redirects when the POST data preservation cache entry is discarded due to a cache timeout. The URL is expected to be a page explaining what has happened.

Property name	<code>org.forgerock.agents.pdp.noentry.url.map</code>
Aliases	<code>org.forgerock.agents.pdp.noentry.url.map</code> Introduced in Java Agent 5.6  <code>com.sun.identity.agents.config.postdata.preserve.cache.noentry.url</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6
Function	POST data preservation
Type	Map <ul style="list-style-type: none"><li>• Keys: web application</li><li>• Values: URL of page explaining the PDP entry was discarded</li></ul>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Advanced  Title: Missing POST Data Preservation Entry URI Map  Legacy title: Missing PDP entry URI

## POST Data Preservation Cache TTL

---

The interval in minutes at which entries in the POST data preservation cache timeout and are purged.

If this property and [POST Data Preservation Cache TTL in Milliseconds \(deprecated\)](#) are set, [POST Data Preservation Cache TTL in Milliseconds \(deprecated\)](#) takes precedence.

Property name	<code>org.forgerock.agents.pdp.cache.ttl.minutes</code>
Aliases	<code>org.forgerock.agents.pdp.cache.ttl.minutes</code> Introduced in Java Agent 5.6 <a href="#">Recognized</a> from AM 7
Function	POST data preservation
Type	Integer
Default	5
Bootstrap property	Yes
Required property	No
Restart required	Yes - Restart the container after changing the property
Local configuration file	<code>AgentBootstrap.properties</code>
AM console	Tab: Advanced (from AM 7)  Title: POST Data Preservation Cache TTL  Legacy title: PDP Cache TTL in Minutes

## POST Data Preservation Sticky Session Key Value

A name/value pair separated by = , as follows:

When [POST Data Preservation Sticky Session Mode](#) is `URL` , this property sets the query parameter name and value.

When [POST Data Preservation Sticky Session Mode](#) is `Cookie` , this property sets the cookie name and value.

Property name	<code>org.forgerock.agents.pdp.sticky.session.value</code>
---------------	------------------------------------------------------------



Aliases	<p><code>com.sun.identity.agents.config.postdata.preserve.stickysession.value</code>  Introduced in Java Agent 5.0  <u>Recognized</u> from AM 6</p> <p><code>org.forgerock.agents.pdp.sticky.session.value</code>  Introduced in Java Agent 5.6</p>
Function	POST data preservation
Type	String
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	<p>Tab: Advanced</p> <p>Title: POST Data Preservation Sticky Session Key Value</p> <p>Legacy title: PDP Stickysession key-value</p>

## POST Data Preservation Sticky Session Mode

Property name	<code>org.forgerock.agents.pdp.sticky.session.mode</code>
Aliases	<p><code>org.forgerock.agents.pdp.sticky.session.mode</code>  Introduced in Java Agent 5.6</p> <p><code>com.sun.identity.agents.config.postdata.preserve.stickysession.mode</code>  Introduced in Java Agent 5.0  <u>Recognized</u> from AM 6</p>
Function	POST data preservation

Supported settings	<p><b>COOKIE</b></p> <p>The sticky session mode is sent as a cookie (name/value specified by "POST Data Preservation Sticky Session Key Value" (org.forgerock.agents.pdp.sticky.session.value)).</p> <p><b>URL</b></p> <p>The sticky session mode is sent as an HTTP parameter name/value pair (specified by "POST Data Preservation Sticky Session Key Value" (org.forgerock.agents.pdp.sticky.session.value)).</p>
Default	URL
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	<p>Tab: Advanced</p> <p>Title: POST Data Preservation Sticky Session Mode</p> <p>Legacy title: PDP Stickysession mode</p>

## Enable POST Data Preservation

When `true`, unauthenticated POST data is stored before redirecting to the login screen, then auto-submitted after successful authentication.

Property name	<code>org.forgerock.agents.post.data.preservation.enabled</code>
Aliases	<p><code>org.forgerock.agents.post.data.preservation.enabled</code> Introduced in Java Agent 5.6</p> <p><code>com.sun.identity.agents.config.postdata.preserve.enable</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6</p>

Function	POST data preservation
Type	Boolean: true returns true; all other strings return false .
Default	false
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Advanced  Title: Enable POST Data Preservation  Legacy title: Post Data Preservation enabled

## POST Data Preservation in Files or Cache

When Enable POST Data Preservation is true , this property determines how POST data is saved:

true : Save POST data to files

false (default): Save POST data to the in-memory cache

Files are stored in the POST Data Preservation File Directory. Expired files are removed at the interval given by POST Data Preservation Directory Sweep Interval.

Property name	org.forgerock.agents.pdp.use.filesystem.enabled
Aliases	org.forgerock.agents.pdp.use.filesystem.enabled Introduced in Java Agent 5.10.0
Function	POST data preservation
Type	Boolean: true returns true; all other strings return false .
Default	false

Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties

## Pre-Authn and Post Data Preservation Cookie Signing Value

If set to a non-zero length, the value is used to generate a derived key to sign pre-authentication and POST data preservation cookies.

Property name	org.forgerock.agents.cookie.signing.value
Aliases	org.forgerock.agents.cookie.signing.value Introduced in Java Agent 5.10.0
Function	Cookie, POST data preservation, Pre-authentication
Type	String
Bootstrap property	No
Required property	No
Restart required	Yes - Restart the container after changing the property
Local configuration file	AgentKey.properties

## POST Data Preservation Storage Size

The maximum number of megabytes allocated to store POST data. When the maximum is reached, old entries are discarded.

Use this property to mitigate the risk of DDoS attacks.

This property takes precedence over [Max Entries in POST Data Preservation Storage](#).

Property name	org.forgerock.agents.pdp.cache.total.size.mb
---------------	----------------------------------------------

Aliases	<p><code>org.forgerock.agents.pdp.cache.total.size.mb</code> Introduced in Java Agent 5.6</p> <p><code>org.forgerock.openam.agents.config.postdata.preserve.cache.entry.max.total.size.mb</code> Introduced in Java Agent 5.6 <u>Recognized</u> from AM 6</p>
Function	POST data preservation
Type	Integer
Default	``
Bootstrap property	Yes
Required property	No
Restart required	Yes - Restart the container after changing the property
Local configuration file	<code>AgentBootstrap.properties</code>
AM console	<p>Tab: Advanced</p> <p>Title: POST Data Preservation Storage Size</p> <p>Legacy title: PDP Maximum Cache Size</p>

## Max Entries in POST Data Preservation Storage

When POST Data Preservation in Files or Cache is `false`, the maximum number of entries in the POST data preservation storage cache.

When POST Data Preservation in Files or Cache is `true`, the maximum number of files in the POST Data Preservation File Directory.

When the maximum is reached, old entries are discarded.

Use this property to mitigate the risk of DoS attacks.

POST Data Preservation Storage Size takes precedence over this property.

Property name	<code>org.forgerock.agents.pdp.cache.size</code>
---------------	--------------------------------------------------

Aliases	<p><code>org.forgerock.agents.pdp.cache.size</code> Introduced in Java Agent 5.6</p> <p><code>org.forgerock.openam.agents.config.postdata.preserve.cache.entry.max.entries</code> Introduced in Java Agent 5.6 <u>Recognized</u> from AM 6</p>
Function	POST data preservation
Type	Integer
Default	1000
Bootstrap property	Yes
Required property	No
Restart required	Yes - Restart the container after changing the property
Local configuration file	<code>AgentBootstrap.properties</code>
AM console	<p>Tab: Advanced</p> <p>Title: Max Entries in POST Data Preservation Storage</p> <p>Legacy title: PDP Maximum Number of Cache Entries</p>

## POST Data Preservation File Directory

When Enable POST Data Preservation and POST Data Preservation in Files or Cache are true , this property defines the directory in which POST data preservation data files are saved.

The agent must be able to access the directory. If the directory does not exist, or the agent cannot access it, Enable POST Data Preservation is set to false .

Default: `/path/to/java_agents/agent_type/Agent_n/pdp` .

Property name	<code>org.forgerock.agents.pdp.directory</code>
Aliases	<p><code>org.forgerock.agents.pdp.directory</code> Introduced in Java Agent 5.10.0</p>
Function	POST data preservation

Type	String
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties

## Post Data Preservation Cookie Name

The name of the Post Data Preservation cookie. This cookie maintains the security of the data in unauthenticated POST requests. It contains a unique one-time code which is cross-checked against the stored data making it extremely difficult for malicious actors to replay the stored data for other users.

Since Java Agent 5.10, there is the option of creating one cookie for all concurrent PDP requests, or alternatively to have one uniquely named cookie per request.

If you have tests in your environment that make multiple PDP requests to the agent, you may find intermittent failures as browsers can limit how many cookies they handle.

Configure the cookie name as follows:

- To use one cookie for all concurrent PDP requests to AM, configure as a string. For example, `org.forgerock.agents.pdp.cookie.name=cookie-name`.
- To use one cookie for each authentication request to AM, configure as `%n` before, in the middle, or after a string. When the agent creates the cookie, it substitutes `%n` for a unique identifier. For example:
  - `org.forgerock.agents.pdp.cookie.name=%n`
  - `org.forgerock.agents.pdp.cookie.name=%n-cookie-name`
  - `org.forgerock.agents.pdp.cookie.name=cookie-%n-name`
  - `org.forgerock.agents.pdp.cookie.name=cookie-name-%n`

The agent compresses and then signs the cookie.

Property name	<code>org.forgerock.agents.pdp.cookie.name</code>
Aliases	<code>org.forgerock.agents.pdp.cookie.name</code> Introduced in Java Agent 5.10.0 <u>Recognized</u> from AM 7.1
Function	Cookie, POST data preservation

Type	String
Default	PDP_Nonce
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties

## POST Data Preservation Cache TTL in Milliseconds (deprecated)

Specifies the POST data preservation cache timeout in milliseconds.

Use [POST Data Preservation Cache TTL](#) instead of this property.

If this property and [POST Data Preservation Cache TTL](#) are set, this property takes precedence.

Property name	<code>com.sun.identity.agents.config.postdata.preserve.cache.entry.ttl</code>
Deprecated in	5.6
Aliases	<code>com.sun.identity.agents.config.postdata.preserve.cache.entry.ttl</code> Introduced in Java Agent 5.0
Function	POST data preservation
Type	Integer
Default	``
Bootstrap property	Yes
Required property	No
Restart required	Yes - Restart the container after changing the property
Local configuration file	AgentBootstrap.properties

## Policy enforcement



## POST Parameter List for URL Policy Env

The list of HTTP POST request parameters whose names and values the agent sets in the environment map for URL policy evaluation by the AM server.

Property name	<code>org.forgerock.agents.continuous.security.post.list</code>
Aliases	<code>com.sun.identity.agents.config.policy.env.post.param</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  <code>org.forgerock.agents.continuous.security.post.list</code> Introduced in Java Agent 5.7
Function	Policy enforcement
Type	List
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: AM Services  Title: POST Parameter List for URL Policy Env  Legacy title: URL Policy Env POST Parameters

## Max Entries in Policy Cache per Session

The maximum number of policy evaluation entries allowed in the policy evaluation cache for each session.

The number of policy evaluation results that can be stored is this property multiplied by the value of Max Sessions in Policy Cache.

Property name	<code>org.forgerock.agents.policy.cache.per.session.size</code>
---------------	-----------------------------------------------------------------

Aliases	<p><code>com.sun.identity.policy.client.cacheResultsPerUserCap</code> Introduced in Java Agent 5.0</p> <p><code>org.forgerock.agents.policy.cache.per.session.size</code> Introduced in Java Agent 5.6 <u>Recognized</u> from AM 7</p>
Function	Policy enforcement
Type	Integer
Default	50
Bootstrap property	Yes
Required property	No
Restart required	Yes - Restart the container after changing the property
Local configuration file	<code>AgentBootstrap.properties</code>
AM console	<p>Tab: Advanced (from AM 7)</p> <p>Title: Max Entries in Policy Cache per Session</p> <p>Legacy title: Policy Cache Per User</p>

## Restrict to Realm Map

A map to restrict access to the specified web application to users authenticated in the specified realm.

Property name	<code>org.forgerock.agents.restrict.to.realm.map</code>
Aliases	<p><code>org.forgerock.agents.restrict.to.realm.map</code> Introduced in Java Agent 5.6.2.1 <u>Recognized</u> from AM 7</p>
Function	Policy enforcement
Type	<p>Map</p> <ul style="list-style-type: none"> <li>• Keys: web application</li> <li>• Values: allowed realms as CSV</li> </ul>

Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	<p>Tab: AM Services (from AM 7)</p> <p>Title: Restrict to Realm Map</p> <p>Legacy title: Restrict To Realm</p>

## Enable Composite Advice Encoding

When `true`, composite advices are base64 URL-encoded before being sent to custom login endpoints. Use this property to increase security, and protect against cross-site scripting attacks.

Property name	<code>org.forgerock.agents.advice.b64.url.encode.enabled</code>
Aliases	<p><code>com.forgerock.agents.advice.b64.url.encode</code>  Introduced in Java Agent 5.6.2.1  <u>Recognized</u> from AM 7</p> <p><code>org.forgerock.agents.advice.b64.url.encode.enabled</code>  Introduced in Java Agent 5.6.2.1</p> <p><code>org.forgerock.agents.advice.b64.url.encode</code>  Introduced in Java Agent 5.6.2.1</p>
Function	Policy enforcement
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>false</code>
Bootstrap property	No
Required property	No
Restart required	No

Local configuration file	AgentConfig.properties
AM console	Tab: AM Services (from AM 7)  Title: Enable Composite Advice Encoding  Legacy title: Composite Advice Encode

## Max Sessions in Policy Cache

The maximum number of sessions (distinct users) that can be stored in the policy evaluation cache at any time.

Property name	<code>org.forgerock.agents.policy.cache.session.size</code>
Aliases	<code>org.forgerock.agents.policy.cache.session.size</code> Introduced in Java Agent 5.6 <u>Recognized</u> from AM 7  <code>com.sun.identity.policy.client.cachedSessionCap</code> Introduced in Java Agent 5.0
Function	Policy enforcement
Type	Integer
Default	5000
Bootstrap property	Yes
Required property	No
Restart required	Yes - Restart the container after changing the property
Local configuration file	AgentBootstrap.properties
AM console	Tab: Advanced (from AM 7)  Title: Max Sessions in Policy Cache  Legacy title: Policy Cache Size

## Enable Policy Evaluation in User Authentication Realm

When `true`, perform policy evaluation in the realm to which the user is authenticated, and ignore the value in [Policy Evaluation Realm Map](#).

Use this property for web applications that dynamically set the realm for authentication.

Property name	<code>org.forgerock.agents.user.realm.overrides.policy.evaluation.realm.enabled</code>
Aliases	<code>org.forgerock.agents.user.realm.overrides.policy.evaluation.realm.enabled</code> Introduced in Java Agent 5.7.1 <a href="#">Recognized</a> from AM 7.1
Function	Policy enforcement
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>false</code>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: AM Services (from AM 7.1)  Title: Enable Policy Evaluation in User Authentication Realm  Legacy title: Perform Policy Evaluation in User Authenticated Realm

## GET Parameter List for URL Policy Env

The list of HTTP GET request parameters whose names and values the agent sets in the environment map for URL policy evaluation by the AM server.

Property name	<code>org.forgerock.agents.continuous.security.get.list</code>
---------------	----------------------------------------------------------------

Aliases	<code>com.sun.identity.agents.config.policy.env.get.param</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  <code>org.forgerock.agents.continuous.security.get.list</code> Introduced in Java Agent 5.7
Function	Policy enforcement
Type	List
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: AM Services  Title: GET Parameter List for URL Policy Env  Legacy title: URL Policy Env GET Parameters

## Policy Cache TTL

The interval in minutes at which entries in the policy cache time out and are purged.

Property name	<code>org.forgerock.agents.policy.cache.ttl.minutes</code>
Aliases	<code>org.forgerock.agents.policy.cache.ttl.minutes</code> Introduced in Java Agent 5.6  <code>com.sun.identity.agents.polling.interval</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 7
Function	Policy enforcement
Type	Integer
Default	3

Bootstrap property	Yes
Required property	No
Restart required	Yes - Restart the container after changing the property
Local configuration file	AgentBootstrap.properties
AM console	Tab: Advanced  Title: Policy Cache TTL

## JSession Parameter List for URL Policy Env

The list of HTTP session attributes whose names and values the agent sets in the environment map for URL policy evaluation by the AM server.

Property name	<code>org.forgerock.agents.continuous.security.http.session.list</code>
Aliases	<code>org.forgerock.agents.continuous.security.http.session.list</code> Introduced in Java Agent 5.7  <code>com.sun.identity.agents.config.policy.env.jsession.param</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6
Function	Policy enforcement
Type	List
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties

AM console	Tab: AM Services  Title: JSession Parameter List for URL Policy Env  Legacy title: URL Policy Env jsession Parameters
------------	-----------------------------------------------------------------------------------------------------------------------------------

## Policy Evaluation Realm Map

The name of an AM realm to use for policy evaluations. Different web applications can use different policy realms.

### NOTE

To prevent errors, use only characters in the standard ASCII set. The agent automatically percent-encodes characters in the extended ASCII set, however, the name must be manually encoded in AM.

Property name	<code>org.forgerock.agents.policy.evaluation.realm.map</code>
Aliases	<code>org.forgerock.openam.agents.config.policy.evaluation.realm</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  <code>org.forgerock.agents.policy.evaluation.realm.map</code> Introduced in Java Agent 5.6.2.1
Function	Policy enforcement
Type	Map <ul style="list-style-type: none"> <li>• Keys: web application</li> <li>• Values: realm</li> </ul>
Default	/
Bootstrap property	No
Required property	No
Restart required	No



Local configuration file	AgentConfig.properties
AM console	Tab: AM Services  Title: Policy Evaluation Realm Map  Legacy title: Policy Evaluation Realm

## Policy Set Map

The name of an AM policy set to use for policy evaluations. Different web applications can use a different policy set in their chosen realm.

### NOTE

To prevent errors, use only characters in the standard ASCII set. The agent automatically percent-encodes characters in the extended ASCII set, however, the name must be manually encoded in AM.

The following example causes AM to use `mypolicyset` to evaluate policies for all web applications:

```
org.forgerock.agents.policy.set.map=mypolicyset
```

The following example causes AM to use `mypolicyset` to evaluate policies for `mywebapp`. For all other web applications, AM uses `iPlanetAMWebAgentService`:

```
org.forgerock.agents.policy.set.map[mywebapp]=mypolicyset
```

Property name	<code>org.forgerock.agents.policy.set.map</code>
Aliases	<code>org.forgerock.openam.agents.config.policy.evaluation.application</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  <code>org.forgerock.agents.policy.set.map</code> Introduced in Java Agent 5.6.2.1
Function	Policy enforcement
Type	Map <ul style="list-style-type: none"> <li>• Keys: web application</li> <li>• Values: policy set</li> </ul>

Default	iPlanetAMWebAgentService
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: AM Services Title: Policy Set Map Legacy title: Policy Set

## Port check

### Port Check Filename (deprecated)

Nominates a file containing port numbers to be checked when port checking is enabled. See [Enable Port Checking \(deprecated\)](#).

Property name	org.forgerock.agents.port.check.file
Deprecated in	5.6
Aliases	com.sun.identity.agents.config.port.check.file Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6 org.forgerock.agents.port.check.file Introduced in Java Agent 5.6
Function	Port check
Type	String
Default	PortCheckContent.txt
Bootstrap property	No
Required property	No
Restart required	No

Local configuration file	AgentConfig.properties
AM console	Tab: Miscellaneous Title: Port Check Filename Legacy title: Port Check File

## Port Check Protocol Map (deprecated)

A map of allowed protocols for each port, valid when port checking is enabled. See [Enable Port Checking \(deprecated\)](#).

Property name	org.forgerock.agents.port.check.map
Deprecated in	5.6
Aliases	com.sun.identity.agents.config.port.check.setting Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  org.forgerock.agents.port.check.map Introduced in Java Agent 5.6
Function	Port check
Type	Map <ul style="list-style-type: none"> <li>• Keys: port number</li> <li>• Values: protocol scheme</li> </ul>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Miscellaneous Title: Port Check Protocol Map Legacy title: Port Check Setting

## Enable Port Checking (deprecated)

---

A flag to enable port checking when the filter mode is `SSO_ONLY`. See [Agent Filter Mode Map](#).

Property name	<code>org.forgerock.agents.port.check.enabled</code>
Deprecated in	5.6
Aliases	<code>com.sun.identity.agents.config.port.check.enable</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  <code>org.forgerock.agents.port.check.enabled</code> Introduced in Java Agent 5.6
Function	Port check
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>false</code>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Miscellaneous  Title: Enable Port Checking  Legacy title: Port Check Enable

## Pre-authentication

### Pre-Authn and Post Data Preservation Cookie Signing Value

---

If set to a non-zero length, the value is used to generate a derived key to sign pre-authentication and POST data preservation cookies.

Property name	<code>org.forgerock.agents.cookie.signing.value</code>
Aliases	<code>org.forgerock.agents.cookie.signing.value</code> Introduced in Java Agent 5.10.0
Function	Cookie, POST data preservation, Pre-authentication
Type	String
Bootstrap property	No
Required property	No
Restart required	Yes - Restart the container after changing the property
Local configuration file	<code>AgentKey.properties</code>

## Max Age of Pre-Authentication Cookie

The maximum age in seconds of the pre-authentication cookie configured in [Pre-Authentication Cookie Name](#).

Property name	<code>org.forgerock.agents.authn.cookie.max.age.seconds</code>
Aliases	<code>org.forgerock.agents.authn.cookie.max.age.seconds</code> Introduced in Java Agent 5.6.3.0 <a href="#">Recognized</a> from AM 7
Function	Cookie, Pre-authentication
Type	Integer
Default	600
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>

AM console	Tab: Global (from AM 7)  Title: Max Age of Pre-Authentication Cookie  Legacy title: Pre-Authenticated Cookie Max Age
------------	----------------------------------------------------------------------------------------------------------------------------------

## Pre-Authentication Cookie Name

---

The name of the pre-authentication cookie. This cookie tracks the progress of authentication with AM, and protects requests from replay attacks. It contains the following information:

- URL of the original request
- HTTP mode
- Secure ID (subsequently baked into the nonce of the returned JWT)
- Relevant ACR information
- Transaction ID
- Expiry time configured by Max Age of Pre-Authentication Cookie

(Before Java Agent 5.7), The agent creates a single cookie containing records to identify all concurrent authentication requests to AM. In environments with lots of concurrent requests, or where the protected URLs are long, the cookie can reach the maximum size supported by the browser. When this happens, new authentication requests fail and the agent issues a 403 HTTP message to the user.

(Java Agent 5.7 and later versions) The agent can optionally create a cookie for each authentication request to AM. In some environments, this creates a large number of cookies. If you have tests in your environment that make multiple requests to AM from the same browser, you may find intermittent 403 HTTP messages; browsers can limit how many cookies they handle.

Configure the cookie name as follows:

- To use one cookie for all concurrent authentication requests to AM, configure as a string. For example, `org.forgerock.agents.authn.cookie.name=cookie-name`.
- To use one cookie for each authentication request to AM, configure as `%n`, or as `%n` before, in the middle of, or after a string. When the agent creates the cookie, it translates the string `%n` into a unique identifier. For example:
  - `org.forgerock.agents.authn.cookie.name=%n`
  - `org.forgerock.agents.authn.cookie.name=%n-cookie-name`
  - `org.forgerock.agents.authn.cookie.name=cookie-%n-name`

- `org.forgerock.agents.authn.cookie.name=cookie-name-%n`

The agent compresses and then signs the cookie.

Property name	<code>org.forgerock.agents.authn.cookie.name</code>
Aliases	<code>com.sun.identity.agents.config.cdsso.cookie.name</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 7  <code>org.forgerock.agents.authn.cookie.name</code> Introduced in Java Agent 5.6
Function	Cookie, Pre-authentication
Type	String
Default	<code>amFilterCDSSORequest</code>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Global (from AM 7)  Title: Pre-Authentication Cookie Name  Legacy title: Pre-Authenticated Cookie Name

## Profile

## Fall-Forward Mode (deprecated)

Use [Strategy when AM unavailable](#) instead of this property.

Property name	<code>org.forgerock.agents.fallforward.mode.enabled</code>
Deprecated in	5.9

Aliases	<code>org.forgerock.agents.fallforward.mode.enabled</code> Introduced in Java Agent 5.7 <u>Recognized</u> from AM 7.1
Function	Profile
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>false</code>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Global (not available from AM 7.2)  Title: Fall-Forward Mode

## Location of Agent Configuration Repository

The location of the agent configuration.

Property name	<code>org.forgerock.agents.config.location</code>
Aliases	<code>com.sun.identity.agents.config.repository.location</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  <code>org.forgerock.agents.config.location</code> Introduced in Java Agent 5.6
Function	Profile, Required
Supported settings	<b>LOCAL</b> The agent configuration is read from <code>AgentConfiguration.properties</code> (only).  <b>REMOTE</b> The agent configuration is downloaded from AM.



Default	REMOTE
Bootstrap property	Yes
Required property	Yes - If this property is missing, the agent fails to start
Restart required	Yes - Restart the container after changing the property
Local configuration file	AgentBootstrap.properties
AM console	Tab: Global  Title: Location of Agent Configuration Repository

## JWT Cookie Domain List

A list of domains in which the agent attempts to creates JWT cookies:

- If the list is empty, the agent creates cookies only in its own domain.
- If the agent is running behind a browser, it can create cookies only in its own domain.
- If the agent is running behind a proxy, it should be able to create cookies in any required domains.

Default: Empty

Property name	<code>org.forgerock.agents.jwt.cookie.domain.list</code>
Aliases	<code>com.sun.identity.agents.config.cdsso.domain</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  <code>org.forgerock.agents.jwt.cookie.domain.list</code> Introduced in Java Agent 5.6
Function	Profile
Type	List
Bootstrap property	No
Required property	No
Restart required	No

Local configuration file	AgentConfig.properties
AM console	Tab: SSO (from AM 7.1)  Title: JWT Cookie Domain List  Legacy title: CDSSO Domain List

## JWT Cache TTL

---

The interval in minutes at which entries in the JWT cache timeout and are purged.

Parsing JWTs is a CPU intensive process. As all JWTs in the cache have already been parsed, consider using a long timeout for this cache.

Property name	<code>org.forgerock.agents.jwt.cache.ttl.minutes</code>
Aliases	<code>org.forgerock.openam.agents.config.jwt.cache.ttl.minutes</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 7  <code>org.forgerock.agents.jwt.cache.ttl.minutes</code> Introduced in Java Agent 5.6
Function	Profile
Type	Integer
Default	30
Bootstrap property	Yes
Required property	No
Restart required	Yes - Restart the container after changing the property
Local configuration file	AgentBootstrap.properties
AM console	Tab: Advanced (from AM 7)  Title: JWT Cache TTL

## Max Entries in JWT Cache

---

The maximum number of entries in the JWT cache.

Property name	<code>org.forgerock.agents.jwt.cache.size</code>
Aliases	<code>org.forgerock.agents.jwt.cache.size</code> Introduced in Java Agent 5.6  <code>org.forgerock.openam.agents.config.jwt.cache.size</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 7
Function	Profile
Type	Integer
Default	5000
Bootstrap property	Yes
Required property	No
Restart required	Yes - Restart the container after changing the property
Local configuration file	<code>AgentBootstrap.properties</code>
AM console	Tab: Advanced (from AM 7)  Title: Max Entries in JWT Cache  Legacy title: JWT Cache Size

## JWT Cookie Name

---

The name of the cookie that holds the OIDC JWT on the user's browser.

Before changing the name of this cookie, consider the following points:

- This cookie is only used by the agent and is never presented to AM.
- The cookie name must be unique in the cookies the user's browser receives. For example, do not set the JWT cookie name to `iPlanetDirectoryPro`, which is the default name of the AM session cookie.

If the agent does not find the cookie named by JWT Cookie Name, authentication fails. The user can only access resources that are available through not-enforced rules.

Property name	<code>org.forgerock.agents.jwt.cookie.name</code>
Aliases	<code>org.forgerock.openam.agents.config.jwt.name</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  <code>org.forgerock.agents.jwt.cookie.name</code> Introduced in Java Agent 5.6
Function	Profile
Type	String
Default	<code>am-auth-jwt</code>
Bootstrap property	Yes
Required property	No
Restart required	No
Local configuration file	<code>AgentBootstrap.properties</code>
AM console	Tab: Global  Title: JWT Cookie Name

## Agent Profile Realm

The realm in which the agent profile is defined.

When Enable Policy Evaluation in User Authentication Realm is `true`, AM uses this realm to evaluate policies for policy decision requests from the agent.

Property name	<code>org.forgerock.agents.agent.profile.realm</code>
Aliases	<code>org.forgerock.agents.agent.profile.realm</code> Introduced in Java Agent 5.6  <code>com.sun.identity.agents.config.organization.name</code> Introduced in Java Agent 5.0
Function	Profile, Required
Type	String

Default	/
Bootstrap property	Yes
Required property	Yes - If this property is missing, the agent fails to start
Restart required	Yes - Restart the container after changing the property
Local configuration file	AgentBootstrap.properties

## Exchanged SSO Token Cache TTL

The interval in minutes at which entries in the SSO token exchange cache timeout and are purged.

The exchanged JWT is cached against the relevant SSO token. If the same SSO token is presented again, before the cache entry expires, the agent does not need to exchange the token again, but retrieves the one stored in its cache.

Because exchanging SSO tokens for JWTs is an expensive process, previously exchanged SSO tokens are cached. When an entity is unable to permanently store its JWT in a cookie, calls to AM can be avoided.

Property name	<code>org.forgerock.agents.sso.exchange.cache.ttl.minutes</code>
Aliases	<code>org.forgerock.agents.sso.exchange.cache.ttl.minutes</code> Introduced in Java Agent 5.6.2.1 <u>Recognized</u> from AM 7
Function	Profile
Type	Integer
Default	5
Bootstrap property	Yes
Required property	No
Restart required	Yes - Restart the container after changing the property
Local configuration file	AgentBootstrap.properties

AM console	<p>Tab: Advanced (from AM 7)</p> <p>Title: Exchanged SS0 Token Cache TTL</p> <p>Legacy title: Exchanged SS0 Token Cache Time to Live</p>
------------	------------------------------------------------------------------------------------------------------------------------------------------

## Configuration Reload Interval

When the Location of Agent Configuration Repository is LOCAL , this is the number of seconds after which the agent reloads its configuration if it has been changed since it was last read.

Property name	<code>org.forgerock.agents.config.reload.seconds</code>
Aliases	<p><code>com.sun.identity.agents.config.load.interval</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6</p> <p><code>org.forgerock.agents.config.reload.seconds</code> Introduced in Java Agent 5.6</p>
Function	Profile
Type	Integer
Default	0
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	<p>Tab: Global</p> <p>Title: Configuration Reload Interval</p>

## Agent Profile Name

The profile name used to fetch agent configuration data from AM, to evaluate policies for users, retrieve session info, and so on.

Default: Empty

Property name	<code>org.forgerock.agents.profile.name</code>
Aliases	<code>com.sun.identity.agents.app.username</code> Introduced in Java Agent 5.0  <code>com.sun.identity.agents.config.profilename</code> Introduced in Java Agent 5.0  <code>org.forgerock.agents.profile.name</code> Introduced in Java Agent 5.6
Function	Profile, Required
Type	String
Bootstrap property	Yes
Required property	Yes - If this property is missing, the agent fails to start
Restart required	Yes - Restart the container after changing the property
Local configuration file	<code>AgentBootstrap.properties</code>

## Enable Configuration Lock

When `true`, an agent restart is required to allow configuration changes, even for hot-swappable parameters.

Property name	<code>org.forgerock.agents.lock.config.enabled</code>
Aliases	<code>com.sun.identity.agents.config.lock.enable</code> Introduced in Java Agent 5.0  <code>org.forgerock.agents.lock.config.enabled</code> Introduced in Java Agent 5.6
Function	Profile
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>false</code>
Bootstrap property	Yes

Required property	No
Restart required	No
Local configuration file	AgentBootstrap.properties

## Profile Attribute Map

Map the value of an AM profile attribute to one or more HTTP headers, HTTP cookies, or request attributes, depending on the value of [Profile Attribute Fetch Mode](#).

- Map key: The name of an AM profile attribute
- Map value: The name of one or more HTTP headers, HTTP cookies, or request attributes

The user profile can be stored in LDAP or any other arbitrary data store

Consider the following points for HTTP cookies:

- If an HTTP cookie with the mapped name does not exist, the agent creates it.
- If an HTTP cookie with the mapped name already exists and the cookie value is different from the mapped value, the agent overwrites the cookie.
- If an HTTP cookie with the mapped name already exists and the cookie value is the same as the mapped value, the agent does nothing.
- If the profile attribute name (key) does not exist, the agent does not create the HTTP cookie.
- The agent does not automatically clear cookies. To prevent a build up of cookies, consider adding them to the [Reset Cookie List](#).

Consider the following points for HTTP headers:

- If an HTTP header with the mapped name does not exist, the agent creates it.
- If an HTTP header with the mapped name already exists, the agent does not overwrite it but simply appends information to the header.
- If the profile attribute name (key) does not exist, the agent does not create the HTTP header.
- When an HTTP header name is used in a request header, it is prefixed by HTTP\_ . The agent automatically changes lower case letters to upper case, and hyphens ( - ) to underscores ( \_ ). For example, CUSTOM-userid becomes HTTP\_CUSTOM\_USERID .

Format: profile attribute = HEADER-NAME(S) , profile attribute = COOKIE-NAME(S) , profile attribute = REQUEST-ATTRIBUTE(S)



Default: Empty

Examples:

In the following example, the AM response attribute `uid` is mapped to `CUSTOM-User-Name` :

```
com.sun.identity.agents.config.response.attribute.mapping[uid]=Custom-User-Name
```

Example: `[cn]=HEADER-1|HEADER-2`

Property name	<code>org.forgerock.agents.profile.attribute.map</code>
Aliases	<code>com.sun.identity.agents.config.profile.attribute.mapping</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  <code>org.forgerock.agents.profile.attribute.map</code> Introduced in Java Agent 5.6
Function	Profile
Type	Map <ul style="list-style-type: none"><li>• Keys: source response profile name</li><li>• Values: one or more target response profile names</li></ul>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Application  Title: Profile Attribute Map  Legacy title: Profile Attribute Mapping

## Max Entries in SSO Exchange Cache

The maximum number of entries in the SSO exchange cache, used when SSO tokens are exchanged for JWTs.

When the maximum is reached, the oldest records are overwritten.

Property name	<code>org.forgerock.agents.sso.exchange.cache.size</code>
Aliases	<code>org.forgerock.agents.sso.exchange.cache.size</code> Introduced in Java Agent 5.6.2.1 <u>Recognized</u> from AM 7
Function	Profile
Type	Integer
Default	100
Bootstrap property	Yes
Required property	No
Restart required	Yes - Restart the container after changing the property
Local configuration file	<code>AgentBootstrap.properties</code>
AM console	Tab: Advanced (from AM 7)  Title: Max Entries in SSO Exchange Cache  Legacy title: Exchanged SSO Token Cache Size

## Profile Attribute Fetch Mode

Map the name of an AM profile attribute specified in Profile Attribute Map as follows:

- NONE: Do not map
- HTTP\_HEADER: Map the to the name of an HTTP profile header
- HTTP\_COOKIE: Map to the name of an HTTP cookie
- REQUEST\_ATTRIBUTE: Map to the name of an HTTP profile attribute

Property name	<code>org.forgerock.agents.profile.attribute.fetch.mode</code>
---------------	----------------------------------------------------------------

Aliases	<p><code>com.sun.identity.agents.config.profile.attribute.fetch.mode</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6</p> <p><code>org.forgerock.agents.profile.attribute.fetch.mode</code> Introduced in Java Agent 5.6</p>
Function	Attributes, Cookie reset, Profile
Supported settings	<p><b>NONE</b> No AM attributes are mapped.</p> <p><b>HTTP_HEADER</b> The named AM attributes are mapped to headers in the outgoing HTTP response.</p> <p><b>REQUEST_ATTRIBUTE</b> The named AM attributes are mapped to request attributes in the outgoing HTTP response.</p> <p><b>HTTP_COOKIE</b> The named AM attributes are mapped to cookies in the outgoing HTTP response.</p>
Default	NONE
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	<p>Tab: Application</p> <p>Title: Profile Attribute Fetch Mode</p>

## WebSocket Connection Interval

The interval in minutes at which WebSockets to AM are killed and reopened. This property helps ensure a balanced distribution of connections across the AM servers on the site.

Property name	<code>org.forgerock.agents.balance.websocket.interval.minutes</code>
Aliases	<code>org.forgerock.openam.agents.config.balance.websocket.connection.interval.in.minutes</code> Introduced in Java Agent 5.6 <u>Recognized</u> from AM 6  <code>org.forgerock.agents.balance.websocket.interval.minutes</code> Introduced in Java Agent 5.6
Function	Profile
Type	Integer
Default	30
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Global  Title: WebSocket Connection Interval

## Query parameter

## Regex Remove Query Parameters List for Policy Evaluation

A list of regular expressions the agent uses to match query parameters to be removed from the incoming URL for policy evaluation and caching purposes. The property has the following format, with no spaces between values:

```
[Domain[/path]]|parameter[, parameter...]
```

Consider the following constraints when constructing your list of regular expressions:

- Add a comma (,) character at the beginning or the end of the list to remove all unnamed parameters. For example, `myapp.example.com/customers|,lang` would match both `lang` and any unnamed parameters.

- Consider creating multiple simple regular expressions instead of a single complicated one.
- The remaining parameters (those that do not match the list of parameters) are sorted alphabetically.

Examples:

```
org.forgerock.agents.unwanted.http.url.params.regex.list[0]=myapp.example.com|b.*,gp(a|p|s),
```

```
org.forgerock.agents.unwanted.http.url.params.regex.list[1]=|.*
```

The following incoming URL request that matches a rule such as `myapp.example.com/customers|, coun.*?`:

```
http://myapp.example.com/customers?
country=uk&=bristol&lang=en_GB&area=1343456
```

It is cached by the agent as `http://myapp.example.com/customers? =bristol&lang=en_GB`, where both `country` and unnamed parameter are removed and the remaining parameters are sorted alphabetically.

Property name	<code>org.forgerock.agents.unwanted.http.url.params.regex.list</code>
Aliases	<code>org.forgerock.agents.unwanted.http.url.params.regex.list</code> Introduced in Java Agent 5.6  <code>org.forgerock.openam.agents.config.conditional.unwanted.http.url.params.regex</code> Introduced in Java Agent 5.6 <u>Recognized</u> from AM 7  <code>org.forgerock.agents.unwanted.http.url.params.regex.list</code> Introduced in Java Agent 5.6
Function	Query parameter
Type	List
Bootstrap property	No
Required property	No
Restart required	No

Local configuration file	AgentConfig.properties
AM console	<p>Tab: Miscellaneous (from AM 7)</p> <p>Title: Regex Remove Query Parameters List for Policy Evaluation</p> <p>Legacy title: Regular Expression Remove Query Parameters</p>

## Remove Query Parameters List for Policy Evaluation

A list of query parameters to be removed from the incoming URL for policy evaluation and caching.

The property has the following format, with no spaces between values:

```
[Domain[/path]]|parameter[,parameter...]
```

Consider the following constraints when constructing the list of parameters:

- Add a comma (,) character at the beginning or the end of the list to remove all unnamed parameters. The following example would match both lang and any unnamed parameters: myapp.example.com/customers|,lang
- Add the asterisk (\*) character to the list to remove all parameters, including unnamed ones.
- The remaining parameters (those that do not match the list of parameters) are sorted alphabetically.

Examples:

```
org.forgerock.agents.unwanted.http.url.param.list[0]=myapp.example.com/customers|location,lang
```

```
org.forgerock.agents.unwanted.http.url.param.list[1]=example.com/customers|*
```

The following incoming URL request matches a rule such as myapp.example.com/customers|,lang :

```
http://myapp.example.com/customers?country=uk&=bristol&lang=en_GB&area=1343456
```

It is cached by the agent as http://myapp.example.com/customers?area=1343456&country=uk, where both lang and the unnamed parameter are removed and the rest of the parameters are sorted alphabetically.

Property name	<code>org.forgerock.agents.unwanted.http.url.param.list</code>
Aliases	<code>org.forgerock.agents.unwanted.http.url.param.list</code> Introduced in Java Agent 5.6  <code>org.forgerock.openam.agents.config.conditional.unwanted.http.url.params</code> Introduced in Java Agent 5.6 <u>Recognized</u> from AM 7
Function	Query parameter
Type	List
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Miscellaneous (from AM 7)  Title: Remove Query Parameters List for Policy Evaluation  Legacy title: Remove Query Parameters

## Regex Query Parameters List for Policy Evaluation

A list of regular expressions the agent uses to match query parameters, for policy evaluation and caching.

The property has the following format, with no spaces between values:

```
[Domain[/path]]|regexp[, regexp, ...]
```

Property name	<code>org.forgerock.agents.wanted.http.url.params.regex.list</code>
---------------	---------------------------------------------------------------------

Aliases	<p><code>org.forgerock.agents.wanted.http.url.params.regex.list</code> Introduced in Java Agent 5.6</p> <p><code>org.forgerock.openam.agents.config.conditional.wanted.http.url.params.regex</code> Introduced in Java Agent 5.6 <u>Recognized</u> from AM 7</p> <p><code>org.forgerock.agents.wanted.http.url.params.regex.list</code> Introduced in Java Agent 5.6</p>
Function	Query parameter
Type	List
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	<p>Tab: Miscellaneous (from AM 7)</p> <p>Title: Regex Query Parameters List for Policy Evaluation</p>

## Query Parameter List for Policy Evaluation

A list of query parameters to be retained for policy evaluation and caching purposes. The property has the following format, with no spaces between values:

```
[Domain[/path]]|parameter[,parameter...]
```

Consider the following constraints when constructing the list of parameters:

- Add a comma (,) character at the beginning or the end of the list to retain all unnamed parameters. For example, `myapp.example.com/customers|,lang` matches both `lang` and any unnamed parameters.
- Add the asterisk (\*) character to the list to retain all parameters, including unnamed ones.
- The remaining parameters (those that match the list of parameters) are sorted alphabetically.



Examples:

```
org.forgerock.agents.wanted.http.url.param.list[0]=myapp.example.com/news|area
```

```
org.forgerock.agents.wanted.http.url.param.list[1]=example.com/news|area, country, location,
```

The following incoming URL request matches a rule such as  
myapp.example.com/customers|, lang :

```
http://myapp.example.com/customers?  
country=uk&=bristol&lang=en_GB&area=1343456
```

It is cached by the agent as http://myapp.example.com/customers?  
=bristol&lang=en\_GB , where both lang and the unnamed parameter are retained and sorted alphabetically.

Property name	org.forgerock.agents.wanted.http.url.param.list
Aliases	org.forgerock.openam.agents.config.conditional.wanted.http.url.params Introduced in Java Agent 5.6 <u>Recognized</u> from AM 7  org.forgerock.agents.wanted.http.url.param.list Introduced in Java Agent 5.6
Function	Query parameter
Type	List
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Miscellaneous (from AM 7)  Title: Query Parameter List for Policy Evaluation  Legacy title: Retain Query Parameters

## Required

### AM Authentication Service Path

---

The path to the AM server.

Property name	<code>org.forgerock.agents.am.path</code>
Aliases	<code>com.iplanet.am.services.deploymentDescriptor</code> Introduced in Java Agent 5.0  <code>org.forgerock.agents.am.path</code> Introduced in Java Agent 5.6
Function	Authentication service, Required
Type	String
Bootstrap property	Yes
Required property	Yes - If this property is missing, the agent fails to start
Restart required	Yes - Restart the container after changing the property
Local configuration file	<code>AgentBootstrap.properties</code>

### AM Authentication Service Protocol

---

The protocol used by the AM server. Set to one of the following values:

- HTTP
- HTTPS

Property name	<code>org.forgerock.agents.am.protocol</code>
Aliases	<code>org.forgerock.agents.am.protocol</code> Introduced in Java Agent 5.6  <code>com.iplanet.am.server.protocol</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6
Function	Authentication service, Required

Type	String
Bootstrap property	Yes
Required property	Yes - If this property is missing, the agent fails to start
Restart required	Yes - Restart the container after changing the property
Local configuration file	AgentBootstrap.properties
AM console	Tab: AM Services  Title: AM Authentication Service Protocol

## Encrypted Agent Password

The agent profile password, which must correspond to the value in AM.

Set this property to the encrypted value of the password, where the password is encrypted using the key in the property [Encryption Key](#).

Use the following command to get the encrypted value of the password, where `passwordFile` contains only the password followed by a newline, and has the access permission `400`:

```
$ ./agentadmin --encrypt agentInstance passwordFile
```

Default: Empty

Property name	<code>org.forgerock.agents.encrypted.password</code>
Aliases	<code>com.iplanet.am.service.secret</code> Introduced in Java Agent 5.0  <code>org.forgerock.agents.encrypted.password</code> Introduced in Java Agent 5.6
Function	Miscellaneous, Required
Type	String
Bootstrap property	No
Required property	Yes - If this property is missing, the agent fails to start
Restart required	Yes - Restart the container after changing the property

Local configuration file	AgentPassword.properties
--------------------------	--------------------------

## Location of Agent Configuration Repository

The location of the agent configuration.

Property name	org.forgerock.agents.config.location
Aliases	<p>com.sun.identity.agents.config.repository.location</p> <p>Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6</p> <p>org.forgerock.agents.config.location</p> <p>Introduced in Java Agent 5.6</p>
Function	Profile, Required
Supported settings	<p><b>LOCAL</b></p> <p>The agent configuration is read from AgentConfiguration.properties (only).</p> <p><b>REMOTE</b></p> <p>The agent configuration is downloaded from AM.</p>
Default	REMOTE
Bootstrap property	Yes
Required property	Yes - If this property is missing, the agent fails to start
Restart required	Yes - Restart the container after changing the property
Local configuration file	AgentBootstrap.properties
AM console	<p>Tab: Global</p> <p>Title: Location of Agent Configuration Repository</p>

## Public AM URL

The assembled "public" URL of AM. This URL is used by the agent to redirect the user's browser to AM for login (customised or not), or if necessary, exchange an SSO token for

a JWT.

The following properties make up the URL:

- [AM Authentication Service Protocol](#)
- [AM Authentication Service Host Name](#)
- [AM Authentication Service Port](#)
- [AM Authentication Service Path](#)

The "private" URL is used by the agent for tasks such as establishing websockets, and obtaining authentication tokens or session information. The AM or load balancer instance can be behind a firewall to which the agent has access.

Define this property when public access to AM is restricted to a different URL from the private URL.

Property name	<code>org.forgerock.agents.public.am.url</code>
Aliases	<code>com.forgerock.agents.public.am.url</code> Introduced in Java Agent 5.6.3.0  <code>org.forgerock.agents.public.am.url</code> Introduced in Java Agent 5.6.3.0
Function	Miscellaneous, Required
Type	String
Bootstrap property	Yes
Required property	Yes - If this property is missing, the agent fails to start
Restart required	Yes - Restart the container after changing the property
Local configuration file	<code>AgentBootstrap.properties</code>

## Authentication Redirect URI

---

The URI the agent uses to process authentication requests.

When this property is not defined, the redirect URI is provided by AM.

When this property is defined and [Location of Agent Configuration Repository](#) is REMOTE , AM overwrites this property.

If OIDC authentication is being used, changing the value of this property while the agent is running prevents it from functioning. Restart the agent immediately after the value in AM is altered and the properties saved.

Property name	<code>org.forgerock.agents.authn.redirect.uri</code>
Aliases	<code>org.forgerock.agents.authn.redirect.uri</code> Introduced in Java Agent 5.6  <code>com.sun.identity.agents.config.cdssso.redirect.uri</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6
Function	Cross-domain single sign-on, Required
Type	String
Bootstrap property	No
Required property	No
Restart required	Yes - Restart the container after changing the property
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: SS0  Title: Authentication Redirect URI  Legacy title: CDSSO Redirect URI

## Encrypting Java class

The Java class used to encrypt the agent password.

During installation, the class is set in the bootstrap properties file with the default value. The default value is `secure`; it is not recommended or necessary to change it.

Change the class only to reduce your level of encryption. To change the class, make sure that the class is available at runtime, regenerate the agent password using the agent installer, and manually edit the newly generated encrypted password into the bootstrap properties file.

Property name	<code>org.forgerock.agents.encryptor.classname</code>
---------------	-------------------------------------------------------

Aliases	<code>org.forgerock.agents.encryptor.classname</code> Introduced in Java Agent 5.7  <code>com.iplanet.security.encryptor</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6
Function	Authentication service, Encryption, Required
Type	String
Default	<code>org.forgerock.openam.shared.security.crypto.AESWrapEncryption</code>
Bootstrap property	Yes
Required property	Yes - If this property is missing, the agent fails to start
Restart required	Yes - Restart the container after changing the property
Local configuration file	<code>AgentBootstrap.properties</code>

## Agent Profile Realm

The realm in which the agent profile is defined.

When Enable Policy Evaluation in User Authentication Realm is `true`, AM uses this realm to evaluate policies for policy decision requests from the agent.

Property name	<code>org.forgerock.agents.agent.profile.realm</code>
Aliases	<code>org.forgerock.agents.agent.profile.realm</code> Introduced in Java Agent 5.6  <code>com.sun.identity.agents.config.organization.name</code> Introduced in Java Agent 5.0
Function	Profile, Required
Type	String
Default	/
Bootstrap property	Yes

Required property	Yes - If this property is missing, the agent fails to start
Restart required	Yes - Restart the container after changing the property
Local configuration file	AgentBootstrap.properties

## Agent Profile Name

The profile name used to fetch agent configuration data from AM, to evaluate policies for users, retrieve session info, and so on.

Default: Empty

Property name	<code>org.forgerock.agents.profile.name</code>
Aliases	<code>com.sun.identity.agents.app.username</code> Introduced in Java Agent 5.0  <code>com.sun.identity.agents.config.profilename</code> Introduced in Java Agent 5.0  <code>org.forgerock.agents.profile.name</code> Introduced in Java Agent 5.6
Function	Profile, Required
Type	String
Bootstrap property	Yes
Required property	Yes - If this property is missing, the agent fails to start
Restart required	Yes - Restart the container after changing the property
Local configuration file	AgentBootstrap.properties

## Autonomous mode

When `true` the agent operates independently of AM, without needing to contact an AM instance. Agents allow access to resources as defined in not-enforced lists; otherwise, they deny access.

Property name	<code>org.forgerock.agents.fallback.mode.enabled</code>
---------------	---------------------------------------------------------



Aliases	<p><code>com.forgerock.agents.config.fallback.mode</code> Introduced in Java Agent 5.9.0</p> <p><code>org.forgerock.agents.fallback.mode.enabled</code> Introduced in Java Agent 5.9.0</p> <p><code>org.forgerock.agents.autonomous.mode.enabled</code> Introduced in Java Agent 5.9.0</p>
Function	Agent, Required
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>false</code>
Bootstrap property	Yes
Required property	Yes - If this property is missing, the agent fails to start
Restart required	Yes - Restart the container after changing the property
Local configuration file	<code>AgentBootstrap.properties</code>

## AM Authentication Service Host Name

The AM server host name.

Property name	<code>org.forgerock.agents.am.hostname</code>
Aliases	<p><code>com.ipplanet.am.server.host</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6</p> <p><code>org.forgerock.agents.am.hostname</code> Introduced in Java Agent 5.6</p>
Function	Authentication service, Required
Type	String
Bootstrap property	Yes
Required property	Yes - If this property is missing, the agent fails to start
Restart required	Yes - Restart the container after changing the property

Local configuration file	AgentBootstrap.properties
AM console	Tab: AM Services  Title: AM Authentication Service Host Name

## AM Authentication Service Port

The AM server port number.

Property name	org.forgerock.agents.am.port
Aliases	com.ipplanet.am.server.port Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  org.forgerock.agents.am.port Introduced in Java Agent 5.6
Function	Authentication service, Required
Type	String
Bootstrap property	Yes
Required property	Yes - If this property is missing, the agent fails to start
Restart required	Yes - Restart the container after changing the property
Local configuration file	AgentBootstrap.properties
AM console	Tab: AM Services  Title: AM Authentication Service Port

## Encryption Key

The key with which to encrypt the agent password.

The key is set during installation process. To change it after installation:

- Manually invoke `agentadmin` with the `--getEncryptKey` option
- Manually edit the result into the bootstrap property file, against the encryption key property

- Re-encrypt your password using `agentadmin` with the `--encrypt` option
- Manually edit the encrypted result into the bootstrap property file, against the encrypted password property

If this property is not set, the agent terminates with a configuration error.

Property name	<code>am.encrypted.pwd</code>
Aliases	<code>am.encrypted.pwd</code> Introduced in Java Agent 5.0
Function	Authentication service, Encryption, Required
Type	String
Bootstrap property	No
Required property	Yes - If this property is missing, the agent fails to start
Restart required	Yes - Restart the container after changing the property
Local configuration file	<code>AgentKey.properties</code>

## Response

### Response Attribute Map

---

Map the value of a response attribute specified in AM to one or more HTTP headers, HTTP cookies, or request attributes, depending on the value of [Response Attribute Fetch Mode](#).

- Map key: The name of a response attribute returned by AM with a policy decision
- Map value: The name of one or more HTTP headers, HTTP cookies, or request attributes

Consider the following points for response cookies:

- If an HTTP cookie with the mapped name does not exist, the agent creates it.
- If an HTTP cookie with the mapped name already exists and the cookie value is different from the mapped value, the agent overwrites the cookie.
- If an HTTP cookie with the mapped name already exists and the cookie value is the same as the mapped value, the agent does nothing.
- If the profile attribute name (key) does not exist, the agent does not create the HTTP cookie.

- The agent does not automatically clear cookies. To prevent a build up of cookies, consider adding them to the [Reset Cookie List](#).

Consider the following points for response headers:

- If an HTTP header with the mapped name does not exist, the agent creates it.
- If an HTTP header with the mapped name already exists, the agent does not overwrite it but simply appends information to the HTTP header.
- If the profile attribute name (key) does not exist, the agent does not create the HTTP header.
- When an HTTP header name is used in a request header, it is prefixed by HTTP\_ . The agent automatically changes lower case letters to upper case, and hyphens ( - ) to underscores ( \_ ). For example, CUSTOM-userid becomes HTTP\_CUSTOM\_USERID .

Format: response attribute = HEADER-NAME(S) , response attribute = COOKIE-NAME(S) , response attribute = REQUEST-ATTRIBUTE(S)

Default: Empty

Examples:

In the following example, the AM response attribute uid is mapped to CUSTOM-User-Name :

```
com.sun.identity.agents.config.response.attribute.mapping[uid]=Custom-User-Name
```

Example: [uid]=HEADER1|HEADER2

Property name	org.forgerock.agents.response.attribute.map
Aliases	org.forgerock.agents.response.attribute.map Introduced in Java Agent 5.6  com.sun.identity.agents.config.response.attribute.mapping Introduced in Java Agent 5.0 <a href="#">Recognized</a> from AM 6
Function	Response
Type	Map <ul style="list-style-type: none"> <li>• Keys: source response attribute name</li> <li>• Values: one or more target response attribute names</li> </ul>

Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Application Title: Response Attribute Map Legacy title: Response Attribute Mapping

## Response Attribute Fetch Mode

Map the name of an AM policy response attribute specified in [Response Attribute Map](#) as follows:

- NONE: Do not map
- HTTP\_HEADER: Map the to the name of an HTTP response header
- HTTP\_COOKIE: Map to the name of an HTTP cookie
- REQUEST\_ATTRIBUTE: Map to the name of an HTTP request attribute

Property name	org.forgerock.agents.response.attribute.fetch.mode
Aliases	com.sun.identity.agents.config.response.attribute.fetch.mode Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  org.forgerock.agents.response.attribute.fetch.mode Introduced in Java Agent 5.6
Function	Attributes, Response

Supported settings	<p><b>NONE</b> No AM attributes are mapped.</p> <p><b>HTTP_HEADER</b> The named AM attributes are mapped to headers in the outgoing HTTP response.</p> <p><b>REQUEST_ATTRIBUTE</b> The named AM attributes are mapped to request attributes in the outgoing HTTP response.</p> <p><b>HTTP_COOKIE</b> The named AM attributes are mapped to cookies in the outgoing HTTP response.</p>
Default	NONE
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	<p>Tab: Application</p> <p>Title: Response Attribute Fetch Mode</p>

## SSO cookie handling

### Enable SSO Token Acceptance

Set this property as follows:

- `true` : Accept SSO tokens. Use this option when the agent and the token issuer are in the same domain, and for web applications and APIs where the backend accepts user information from SSO tokens.
- `false` : Do not accept SSO tokens; require OIDC JWTs for authentication.

During session upgrade the format of the composite advice is as follows:

- When both this property and Enable Custom Login Mode are `true`, the composite advice has the following format: ?  
authIndexType=composite\_advice&authIndexValue=<Advices Value>

- When either property is `false`, the composite advice has the following format: `? composite_advice=<Advices Value>`

Property name	<code>org.forgerock.agents.accept.sso.tokens.enabled</code>
Aliases	<code>org.forgerock.agents.accept.sso.tokens.enabled</code> Introduced in Java Agent 5.7.1 <u>Recognized</u> from AM 7.1  <code>org.forgerock.agents.accept.sso.tokens</code> Introduced in Java Agent 5.7.1  <code>com.forgerock.agents.accept.sso.tokens</code> Introduced in Java Agent 5.7.1
Function	Custom login redirect, Login redirect, SSO cookie handling
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>false</code>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: SSO (from AM 7.1)  Title: Enable SSO Token Acceptance  Legacy title: Accept SSO Tokens

## Convert SSO Tokens Into OIDC JWTs

For each incoming request, the agent looks for an OIDC JWT in the cookie named by JWT Cookie Name. Set this property as follows:

- `true` : Use this value to allow users to access resources protected with systems that continue to use SSO tokens, and to use the default login redirection mode.

- If the agent does not find a JWT in the cookie, the agent looks for an SSO token in the iPDP cookie defined during AM installation. During agent startup, the agent retrieves the name of this cookie from AM.
  - If the agent finds an SSO token in the iPDP cookie, it makes a request to AM to convert the SSO token into an OIDC JWT.
  - The agent caches the SSO token, so that if it is presented in another incoming request, the agent substitutes the JWT without making a request to AM.
  - If the agent does not find either token, authentication fails. The user can only access resources that are available through not-enforced rules.
- `false` : Do not convert SSO tokens into OIDC JWTs.

Property name	<code>org.forgerock.agents.accept.ipdp.cookie</code>
Aliases	<code>com.forgerock.agents.accept.ipdp.cookie</code> Introduced in Java Agent 5.6 <u>Recognized</u> from AM 7  <code>org.forgerock.agents.accept.ipdp.cookie.enabled</code> Introduced in Java Agent 5.7
Function	SSO cookie handling
Type	Boolean: <code>true</code> returns true; all other strings return <code>false</code> .
Default	<code>false</code>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: SSO (from AM 7)  Title: Convert SSO Tokens Into OIDC JWTs  Legacy title: Convert SSO Tokens into OpenID Connect JWTs

## SSO Cookie Domain List



When the property `Enable SSO Token Acceptance` is `true`, a list of domains in which the agent attempts to create SSO cookies:

- If the list is empty, the agent creates cookies only in its own domain.
- If the agent is running behind a browser, it can create cookies only in its own domain.
- If the agent is running behind a proxy, it should be able to create cookies in any required domains.

Default: Empty

Property name	<code>org.forgerock.agents.ipdp.cookie.domain.list</code>
Aliases	<code>org.forgerock.agents.ipdp.cookie.domain.list</code> Introduced in Java Agent 5.7.1 <u>Recognized</u> from AM 7.1
Function	SSO cookie handling
Type	List
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: SSO (from AM 7.1)  Title: SSO Cookie Domain List

## SameSite

## Set-Cookie Internal Map

---

When creating internal cookies, such as `am-auth-jwt` and the pre-authentication cookies, this property sets additional attributes by adding text into the `Set-Cookie` header.

Specify a key:value map, where the key is the cookie name, and the value is the string to add to the `Set-Cookie` header. If the key is omitted, the value becomes the default for all cookies.

Separate multiple values with a semicolon.

Examples:

- Set the SameSite attribute of the am-auth-jwt cookie:  
`org.forgerock.agents.set.cookie.internal.map[am-auth-jwt]=samesite=strict`
- Set the SameSite attribute of all cookies:  
`org.forgerock.agents.set.cookie.internal.map=samesite=strict`
- Set several attributes of mycookie :  
`org.forgerock.agents.set.cookie.internal.map[myCookie]=Max-Age=10000; Domain=.my.default.fqdn`

Property name	<code>org.forgerock.agents.set.cookie.internal.map</code>
Aliases	<code>org.forgerock.agents.set.cookie.internal.map</code> Introduced in Java Agent 5.6.3.0 <u>Recognized</u> from AM 7
Function	SameSite
Type	Map <ul style="list-style-type: none"><li>• Keys: Agent internal cookie name</li><li>• Values: (samesite) text to be added to the Set-Cookie header</li></ul>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: SS0 (from AM 7)  Title: Set-Cookie Internal Map

## Exclude Agents From Samesite Cookie Attributes

List of user agents excluded from receiving SameSite cookie attributes.

To specify different user agent patterns, add them in AM as custom properties, When user agent patterns are specified, the default list of user agents is ignored.

Property name	<code>org.forgerock.agents.samesite.excluded.user.agents.list</code>
Aliases	<code>org.forgerock.agents.samesite.excluded.user.agents.list</code> Introduced in Java Agent 5.6.3.0 <u>Recognized</u> from AM 7
Function	SameSite
Type	List
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: SS0 (from AM 7)  Title: Exclude Agents From Samesite Cookie Attributes  Legacy title: Samesite Cookie Attributes Excluded User Agents Pattern List

## Set-Cookie Attribute Map

When creating cookies with the `AttributeTaskHandler`, this property sets additional attributes by adding text into the `Set-Cookie` header.

Specify a key:value map, where the key is the cookie name, and the value the string to add to the the `Set-Cookie` header.

Separate multiple values with a semicolon.

Property name	<code>org.forgerock.agents.set.cookie.attribute.map</code>
Aliases	<code>org.forgerock.agents.set.cookie.attribute.map</code> Introduced in Java Agent 5.6.3.0 <u>Recognized</u> from AM 7
Function	SameSite

Type	Map <ul style="list-style-type: none"> <li>• Keys: Cookie name</li> <li>• Values: (samesite) text to be added to the Set-Cookie header</li> </ul>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: SSO (from AM 7)  Title: Set-Cookie Attribute Map

## Session

### Session Attribute Fetch Mode

Map the name of an AM session attribute specified in [Session Attribute Map](#) as follows:

- NONE: Do not map
- HTTP\_HEADER: Map the to the name of an HTTP session header
- HTTP\_COOKIE: Map to the name of an HTTP cookie
- REQUEST\_ATTRIBUTE: Map to the name of an HTTP session attribute

When the value is HTTP\_COOKIE , [Cookie Reset](#) is automatically set to true . Before redirecting the client for login, and when the client logs out, the agent resets profile and session attributes cookies, and cookies in the [Reset Cookie List](#).

Property name	org.forgerock.agents.session.attribute.fetch.mode
---------------	---------------------------------------------------

Aliases	<p><code>org.forgerock.agents.session.attribute.fetch.mode</code> Introduced in Java Agent 5.6</p> <p><code>com.sun.identity.agents.config.session.attribute.fetch.mode</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6</p>
Function	Attributes, Cookie reset, Session
Supported settings	<p><b>NONE</b> No AM attributes are mapped.</p> <p><b>HTTP_HEADER</b> The named AM attributes are mapped to headers in the outgoing HTTP response.</p> <p><b>REQUEST_ATTRIBUTE</b> The named AM attributes are mapped to request attributes in the outgoing HTTP response.</p> <p><b>HTTP_COOKIE</b> The named AM attributes are mapped to cookies in the outgoing HTTP response.</p>
Default	NONE
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	<p>Tab: Application</p> <p>Title: Session Attribute Fetch Mode</p>

## Session Attribute Map

Map the value of an AM session attribute to one or more HTTP headers, HTTP cookies, or request attributes, depending on the value of Session Attribute Fetch Mode. The session attribute is the attribute in the session to be fetched.

- Map key: The name of an AM session attribute

- Map value: The name of one or more HTTP headers, HTTP cookies, or request attributes

Consider the following points for HTTP cookies:

- If an HTTP cookie with the mapped name does not exist, the agent creates it.
- If an HTTP cookie with the mapped name already exists and the cookie value is different from the mapped value, the agent overwrites the cookie.
- If an HTTP cookie with the mapped name already exists and the cookie value is the same as the mapped value, the agent does nothing.
- If the profile attribute name (key) does not exist, the agent does not create the HTTP cookie.
- The agent does not automatically clear cookies. To prevent a build up of cookies, consider adding them to the [Reset Cookie List](#).

Consider the following points for HTTP headers:

- If an HTTP header with the mapped name does not exist, the agent creates it.
- If an HTTP header with the mapped name already exists, the agent does not overwrite it but simply appends information to the header.
- If the profile attribute name (key) does not exist, the agent does not create the response header.
- When an HTTP header name is used in a request header, it is prefixed by HTTP\_ . The agent automatically changes lower case letters to upper case, and hyphens ( - ) to underscores ( \_ ). For example, CUSTOM-userid becomes HTTP\_CUSTOM\_USERID .

Format: session attribute = HEADER-NAME(S) , session attribute = COOKIE-NAME(S) , session attribute = REQUEST-ATTRIBUTE(S)

Default: Empty

Examples:

In the following example, the AM response attribute uid is mapped to CUSTOM-User-Name :

```
com.sun.identity.agents.config.response.attribute.mapping[uid]=Custom-User-Name
```

Example: [UserToken]=HEADER-1|HEADER-2

Property name	org.forgerock.agents.session.attribute.map
---------------	--------------------------------------------

Aliases	<code>org.forgerock.agents.session.attribute.map</code> Introduced in Java Agent 5.6  <code>com.sun.identity.agents.config.session.attribute.mapping</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6
Function	Session
Type	Map <ul style="list-style-type: none"> <li>• Keys: source session attribute name</li> <li>• Values: one or more target session attribute names</li> </ul>
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Application  Title: Session Attribute Map  Legacy title: Session Attribute Mapping

## Session Cache TTL

The interval in minutes at which entries in the session cache timeout and are purged.

If an entry is not cached, the agent must retrieve session information from AM.

Therefore, by default the timeout is much longer than for the policy cache.

Property name	<code>org.forgerock.agents.session.cache.ttl.minutes</code>
---------------	-------------------------------------------------------------

Aliases	<p><code>org.forgerock.agents.session.cache.ttl.minutes</code> Introduced in Java Agent 5.6</p> <p><code>org.forgerock.openam.agents.config.active.session.cache.ttl.minutes</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 7</p>
Function	Session
Type	Integer
Default	15
Bootstrap property	Yes
Required property	No
Restart required	Yes - Restart the container after changing the property
Local configuration file	<code>AgentBootstrap.properties</code>
AM console	<p>Tab: Advanced (from AM 7)</p> <p>Title: Session Cache TTL</p>

## Max Entries in Expired Session Cache

The maximum number of entries in the expired session cache. When the maximum is reached, the oldest records are overwritten.

Property name	<code>org.forgerock.agents.expired.session.cache.size</code>
Aliases	<p><code>org.forgerock.agents.expired.session.cache.size</code> Introduced in Java Agent 5.7.1 <u>Recognized</u> from AM 7.1</p>
Function	Session
Type	Integer
Default	500



Bootstrap property	Yes
Required property	No
Restart required	Yes - Restart the container after changing the property
Local configuration file	AgentBootstrap.properties
AM console	<p>Tab: Advanced (from AM 7.1)</p> <p>Title: Max Entries in Expired Session Cache</p> <p>Legacy title: Expired Session Cache Max Records</p>

## Expired Session Cache Timeout

The interval in minutes at which entries in the expired session cache timeout and are purged.

The expired session cache records sessions that have been killed by AM. Use the cache to reduce network traffic and load on AM. When the agent receives a request using an invalidated token, it rejects the request without requesting session information from AM.

Property name	<code>org.forgerock.agents.sso.expired.session.cache.ttl.minutes</code>
Aliases	<code>org.forgerock.agents.sso.expired.session.cache.ttl.minutes</code> Introduced in Java Agent 5.7.1 <u>Recognized</u> from AM 7.1
Function	Session
Type	Integer
Default	20
Bootstrap property	Yes
Required property	No
Restart required	Yes - Restart the container after changing the property
Local configuration file	AgentBootstrap.properties

AM console	Tab: Advanced (from AM 7.1) Title: Expired Session Cache Timeout
------------	---------------------------------------------------------------------

## Timeout

### Websocket Idle Timeout

The idle timeout in milliseconds for WebSockets. If the connection is not active for this time, the agent pings AM to keep the WebSocket alive.

Property name	<code>org.forgerock.agents.ping.websocket.after.inactive.milliseconds</code>
Aliases	<code>org.forgerock.agents.ping.websocket.after.inactive.milliseconds</code> Introduced in Java Agent 5.8
Function	Timeout
Type	Integer
Default	20000
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>

### Websocket Expired Timeout

The allowed ping response time in milliseconds for WebSockets. If the WebSocket does not respond to a ping within this time, the agent closes the connection.

Property name	<code>org.forgerock.agents.declare.websocket.dead.after.milliseconds</code>
---------------	-----------------------------------------------------------------------------

Aliases	<code>org.forgerock.agents.declare.websocket.dead.after.milliseconds</code> Introduced in Java Agent 5.8
Function	Timeout
Type	Integer
Default	40000
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>

## User mapping

### User Attribute Name

When the property User Mapping Mode is `HTTP_HEADER`, this property is the name of the HTTP header attribute to identify the user. The named header must be present in the incoming headers.

Property name	<code>org.forgerock.agents.user.mapping.mode.attribute.name</code>
Aliases	<code>com.sun.identity.agents.config.user.attribute.name</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  <code>org.forgerock.agents.user.mapping.mode.attribute.name</code> Introduced in Java Agent 5.6
Function	User mapping
Type	String
Default	<code>employeenumber</code>
Bootstrap property	No

Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	Tab: Global Title: User Attribute Name

## User Mapping Mode

---

Specifies where to obtain the user ID

Property name	org.forgerock.agents.user.mapping.mode
Aliases	org.forgerock.agents.user.mapping.mode Introduced in Java Agent 5.6  com.sun.identity.agents.config.user.mapping.m ode Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6
Function	User mapping

Supported settings	<p><b>USER_ID</b></p> <p>If "Enable User Principal Flag" (org.forgerock.agents.userid.mapping.mode.use.dn.enabled) is true, the user ID is set from the User Principal. Otherwise, the user ID is set from the user's session property nominated by "User Session Name" (org.forgerock.agents.userid.mapping.mode.use.session.property.name).</p> <p><b>PROFILE_ATTRIBUTE</b></p> <p>The user ID is set to the value of a named profile attribute specified by "User Attribute Name" (org.forgerock.agents.user.mapping.mode.attribute.name).</p> <p><b>HTTP_HEADER</b></p> <p>The user ID is set to the value of the HTTP header specified by the "User Attribute Name" (org.forgerock.agents.user.mapping.mode.attribute.name).</p> <p><b>SESSION_PROPERTY</b></p> <p>The user ID is set to the value of the session property specified by the "User Attribute Name" (org.forgerock.agents.user.mapping.mode.attribute.name).</p>
Default	USER_ID
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	AgentConfig.properties
AM console	<p>Tab: Global</p> <p>Title: User Mapping Mode</p>

## User Session Name

The user is identified by the value of this property when User Mapping Mode is `USER_ID`, and Enable User Principal Flag is `false`.

Property name	<code>org.forgerock.agents.userid.mapping.mode.use.session.property.name</code>
Aliases	<code>com.sun.identity.agents.config.user.token</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6  <code>org.forgerock.agents.userid.mapping.mode.use.session.property.name</code> Introduced in Java Agent 5.6
Function	User mapping
Type	String
Default	UserToken
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	Tab: Global  Title: User Session Name  Legacy title: User Token Name

## Enable User Principal Flag

When the property User Mapping Mode is `USER_ID`, this flag indicates whether to identify the user through the user DN, as follows:

- If `true`, the DN is taken from `universalId`, retrieved from the AM user session info.
- If `false`, the user is identified by the the property User Session Name.

Property name	<code>org.forgerock.agents.userid.mapping.mode.use.dn.enabled</code>
---------------	----------------------------------------------------------------------

Aliases	<p><code>com.sun.identity.agents.config.user.principal</code> Introduced in Java Agent 5.0 <u>Recognized</u> from AM 6</p> <p><code>org.forgerock.agents.userid.mapping.mode.use.dn.enabled</code> Introduced in Java Agent 5.6</p>
Function	User mapping
Type	Boolean: true returns true; all other strings return false.
Default	false
Bootstrap property	No
Required property	No
Restart required	No
Local configuration file	<code>AgentConfig.properties</code>
AM console	<p>Tab: Global</p> <p>Title: Enable User Principal Flag</p> <p>Legacy title: User Principal Flag</p>

Was this helpful?  

Copyright © 2010-2024 ForgeRock, all rights reserved.